

Package ‘inferr’

October 13, 2022

Type Package

Title Inferential Statistics

Version 0.3.1

Description

Select set of parametric and non-parametric statistical tests. ‘inferr’ builds upon the solid set of statistical tests provided in ‘stats’ package by including additional data types as inputs, expanding and restructuring the test results. The tests included are t tests, variance tests, proportion tests, chi square tests, Levene’s test, McNemar Test, Cochran’s Q test and Runs test.

Depends R(>= 3.2)

License MIT + file LICENSE

URL <https://rsquaredacademy.github.io/inferr/>,
<https://github.com/rsquaredacademy/inferr>

BugReports <https://github.com/rsquaredacademy/inferr/issues>

Imports data.table, magrittr, Rcpp, stats, utils

Suggests covr, knitr, rmarkdown, testthat, xplorerr

Encoding UTF-8

LazyData true

VignetteBuilder knitr

RoxygenNote 7.1.1

LinkingTo Rcpp

NeedsCompilation yes

Author Aravind Hebbali [aut, cre] (<<https://orcid.org/0000-0001-9220-9669>>)

Maintainer Aravind Hebbali <hebbali.aravind@gmail.com>

Repository CRAN

Date/Publication 2021-05-28 17:30:02 UTC

R topics documented:

exam	2
hsb	3
inferr	3
infer_binom_calc	4
infer_chisq_assoc_test	5
infer_chisq_gof_test	6
infer_cochran_qtest	8
infer_launch_shiny_app	9
infer_levene_test	9
infer_mcnemar_test	11
infer_oneway_anova	12
infer_os_prop_test	14
infer_os_t_test	15
infer_os_var_test	17
infer_runs_test	19
infer_ts_ind_ttest	20
infer_ts_paired_ttest	22
infer_ts_prop_test	24
infer_ts_var_test	26
treatment	28
treatment2	28

Index

29

exam	<i>Dummy data set for Cochran's Q test</i>
------	--

Description

A dataset containing information about results of three exams.

Usage

`exam`

Format

A data frame with 15 rows and 3 variables:

exam1 result of exam1

exam2 result of exam2

exam3 result of exam3

Source

<https://www.spss-tutorials.com/spss-cochran-q-test/>

hsb

High School and Beyond Data Set

Description

A dataset containing demographic information and standardized test scores of high school students.

Usage

hsb

Format

A data frame with 200 rows and 10 variables:

id id of the student
female gender of the student
race ethnic background of the student
ses socio-economic status of the student
schtyp school type
prog program type
read scores from test of reading
write scores from test of writing
math scores from test of math
science scores from test of science
socst scores from test of social studies

Source

<https://nces.ed.gov/surveys/hsb/>

inferr

inferr package

Description

Parametric and non parametric statistical tests

Details

See the README on [GitHub](#)

<code>infer_binom_calc</code>	<i>Binomial Test</i>
-------------------------------	----------------------

Description

Test whether the proportion of successes on a two-level categorical dependent variable significantly differs from a hypothesized value.

Usage

```
infer_binom_calc(n, success, prob = 0.5, ...)
infer_binom_test(data, variable, prob = 0.5)
```

Arguments

<code>n</code>	number of observations
<code>success</code>	number of successes
<code>prob</code>	assumed probability of success on a trial
<code>...</code>	additional arguments passed to or from other methods
<code>data</code>	a <code>data.frame</code> or a <code>tibble</code>
<code>variable</code>	factor; column in data

Value

`infer_binom_test` returns an object of class "infer_binom_test". An object of class "infer_binom_test" is a list containing the following components:

<code>exp_k</code>	expected number of successes
<code>exp_p</code>	expected probability of success
<code>k</code>	number of successes
<code>n</code>	number of observations
<code>obs_p</code>	assumed probability of success
<code>pval_lower</code>	lower one sided p value
<code>pval_upper</code>	upper one sided p value

Deprecated Functions

`binom_calc()` and `binom_test()` have been deprecated. Instead use `infer_binom_cal()` and `infer_binom_test()`.

References

Hoel, P. G. 1984. Introduction to Mathematical Statistics. 5th ed. New York: Wiley.

See Also[binom.test](#)**Examples**

```
# using calculator  
infer_binom_calc(32, 13, prob = 0.5)  
  
# using data set  
infer_binom_test(hsb, female, prob = 0.5)
```

infer_chisq_assoc_test*Chi Square Test of Association***Description**

Chi Square test of association to examine if there is a relationship between two categorical variables.

Usage

```
infer_chisq_assoc_test(data, x, y)
```

Arguments

data	a <code>data.frame</code> or <code>tibble</code>
x	factor; column in data
y	factor; column in data

Value

`infer_chisq_assoc_test` returns an object of class "infer_chisq_assoc_test". An object of class "infer_chisq_assoc_test" is a list containing the following components:

chisquare	chi square
chisquare_lr	likelihood ratio chi square
chisquare_mantel_haenszel	mantel haenszel chi square
chisquare_adjusted	continuity adjusted chi square
contingency_coefficient	contingency coefficient
cramers_v	cramer's v
df	degrees of freedom
ds	product of dimensions of the table of x and y

```

phi_coefficient
    phi coefficient
pval_chisquare p-value of chi square
pval_chisquare_adjusted
    p-value of continuity adjusted chi square
pval_chisquare_lr
    p-value of likelihood ratio chi square
pval_chisquare_mantel_haenszel
    p-value of mantel haenszel chi square

```

Deprecated Function

`chisq_test()` has been deprecated. Instead use `infer_chisq_assoc_test()`.

References

Sheskin, D. J. 2007. Handbook of Parametric and Nonparametric Statistical Procedures, 4th edition.
: Chapman & Hall/CRC.

See Also

[chisq.test](#)

Examples

```

infer_chisq_assoc_test(hsb, female, schtyp)
infer_chisq_assoc_test(hsb, female, ses)

```

infer_chisq_gof_test Chi Square Goodness of Fit Test

Description

Test whether the observed proportions for a categorical variable differ from hypothesized proportions

Usage

```
infer_chisq_gof_test(data, x, y, correct = FALSE)
```

Arguments

<code>data</code>	a <code>data.frame</code> or <code>tibble</code>
<code>x</code>	factor; column in <code>data</code>
<code>y</code>	expected proportions
<code>correct</code>	logical; if TRUE continuity correction is applied

Value

`infer_chisq_gof_test` returns an object of class "infer_chisq_gof_test". An object of class "infer_chisq_gof_test" is a list containing the following components:

categories	levels of x
chisquare	chi square statistic
deviation	deviation of observed from frequency
degrees_of_freedom	chi square degrees of freedom
expected_frequency	expected frequency/proportion
n_levels	number of levels of x
observed_frequency	observed frequency/proportion
pvalue	p-value
sample_size	number of observations
std_residuals	standardized residuals
varname	name of categorical variable

Deprecated Function

`chisq_gof()` has been deprecated. Instead use `infer_chisq_gof_test()`

References

Sheskin, D. J. 2007. Handbook of Parametric and Nonparametric Statistical Procedures, 4th edition. : Chapman & Hall/CRC.

See Also

[chisq.test](#)

Examples

```
infer_chisq_gof_test(hsb, race, c(20, 20, 20, 140))

# apply continuity correction
infer_chisq_gof_test(hsb, race, c(20, 20, 20, 140), correct = TRUE)
```

infer_cochran_qtest *Cochran Q Test*

Description

Test if the proportions of 3 or more dichotomous variables are equal in the same population.

Usage

```
infer_cochran_qtest(data, ...)
```

Arguments

data	a <code>data.frame</code> or <code>tibble</code>
...	columns in data

Value

`infer_cochran_qtest` returns an object of class "`infer_cochran_qtest`". An object of class "`infer_cochran_qtest`" is a list containing the following components:

df	degrees of freedom
n	number of observations
pvalue	p value
q	cochran's q statistic

Deprecated Function

`cochran_test()` has been deprecated. Instead use `infer_cochran_qtest()`.

References

Sheskin, D. J. 2007. Handbook of Parametric and Nonparametric Statistical Procedures, 4th edition.
: Chapman & Hall/CRC.

Examples

```
infer_cochran_qtest(exam, exam1, exam2, exam3)
```

infer_launch_shiny_app
Launch Shiny App

Description

Launches shiny app

Usage

```
infer_launch_shiny_app()
```

Examples

```
## Not run:  
infer_launch_shiny_app()  
  
## End(Not run)
```

infer_levene_test *Levene's test for equality of variances*

Description

infer_levene_test reports Levene's robust test statistic for the equality of variances and the two statistics proposed by Brown and Forsythe that replace the mean in Levene's formula with alternative location estimators. The first alternative replaces the mean with the median. The second alternative replaces the mean with the 10

Usage

```
infer_levene_test(data, ...)  
  
## Default S3 method:  
infer_levene_test(data, ..., group_var = NULL, trim_mean = 0.1)
```

Arguments

data	a <code>data.frame</code> or <code>tibble</code>
...	numeric; columns in data
group_var	factor; column in data
trim_mean	trimmed mean

Value

infer_levene_test returns an object of class "infer_levene_test". An object of class "infer_levene_test" is a list containing the following components:

bf	Brown and Forsythe f statistic
p_bf	p-value for Brown and Forsythe f statistic
lev	Levene's f statistic
p_lev	p-value for Levene's f statistic
bft	Brown and Forsythe f statistic using trimmed mean
p_bft	p-value for Brown and Forsythe f statistic using trimmed mean
avgs	mean for each level of the grouping variable
sds	standard deviations for each level of the grouping variable
avg	combined mean
sd	combined standard deviation
n	number of observations
n_df	numerator degrees of freedom
d_df	denominator degrees of freedom
levs	levels of the grouping variable
lens	number of observations for each level of the grouping variable
type	alternative hypothesis

Deprecated Function

`levene_test()` has been deprecated. Instead use `infer_levene_test()`.

References

- Bland, M. 2000. An Introduction to Medical Statistics. 3rd ed. Oxford: Oxford University Press.
- Brown, M. B., and A. B. Forsythe. 1974. Robust tests for the equality of variances. *Journal of the American Statistical Association* 69: 364–367.
- Carroll, R. J., and H. Schneider. 1985. A note on Levene's tests for equality of variances. *Statistics and Probability Letters* 3: 191–194.

Examples

```
# using grouping variable
infer_levene_test(hsb, read, group_var = race)

# using variables
infer_levene_test(hsb, read, write, socst)
```

infer_mcnemar_test	<i>McNemar Test</i>
--------------------	---------------------

Description

Test if the proportions of two dichotomous variables are equal in the same population.

Usage

```
infer_mcnemar_test(data, x = NULL, y = NULL)
```

Arguments

data	a <code>data.frame</code> or <code>tibble</code>
x	factor; column in data
y	factor; column in data

Value

`infer_mcnemar_test` returns an object of class "`infer_mcnemar_test`". An object of class "`infer_mcnemar_test`" is a list containing the following components:

statistic	chi square statistic
df	degrees of freedom
pvalue	p-value
exactp	exact p-value
cstat	continuity correction chi square statistic
cpvalue	continuity correction p-value
kappa	kappa coefficient; measure of interrater agreement
std_err	asymptotic standard error
kappa_cil	95% kappa lower confidence limit
kappa_ciu	95% kappa upper confidence limit
cases	cases
controls	controls
ratio	ratio of proportion with factor
odratio	odds ratio
tbl	two way table

Deprecated Function

`mcnemar_test()` has been deprecated. Instead use `infer_mcnemar_test()`.

References

Sheskin, D. J. 2007. Handbook of Parametric and Nonparametric Statistical Procedures, 4th edition. : Chapman & Hall/CRC.

See Also

[mcnemar.test](#)

Examples

```
# using variables from data
hb <- hsb
hb$himath <- ifelse(hsb$math > 60, 1, 0)
hb$hiread <- ifelse(hsb$read > 60, 1, 0)
infer_mcnemar_test(hb, himath, hiread)

# test if the proportion of students in himath and hiread group is same
himath <- ifelse(hsb$math > 60, 1, 0)
hiread <- ifelse(hsb$read > 60, 1, 0)
infer_mcnemar_test(table(himath, hiread))

# using matrix
infer_mcnemar_test(matrix(c(135, 18, 21, 26), nrow = 2))
```

infer_oneway_anova *One Way ANOVA*

Description

One way analysis of variance

Usage

```
infer_oneway_anova(data, x, y, ...)
```

Arguments

data	a <code>data.frame</code> or a <code>tibble</code>
x	numeric; column in data
y	factor; column in data
...	additional arguments passed to or from other methods

Value

`infer_oneway_anova` returns an object of class "`infer_oneway_anova`". An object of class "`infer_oneway_anova`" is a list containing the following components:

<code>adjusted_r2</code>	adjusted r squared value
<code>df_btwn</code>	between groups degrees of freedom
<code>df_within</code>	within groups degrees of freedom
<code>df_total</code>	total degrees of freedom
<code>fstat</code>	f value
<code>group_stats</code>	group statistics
<code>ms_btwn</code>	between groups mean square
<code>ms_within</code>	within groups mean square
<code>obs</code>	number of observations
<code>pval</code>	p value
<code>r2</code>	r squared value
<code>rmse</code>	root mean squared error
<code>ss_btwn</code>	between group sum of squares
<code>ss_within</code>	within group sum of squares
<code>ss_total</code>	total sum of squares

References

Kutner, M. H., Nachtsheim, C., Neter, J., & Li, W. (2005). Applied linear statistical models. Boston: McGraw-Hill Irwin.

See Also

[anova](#)

Examples

```
infer_oneway_anova(mtcars, mpg, cyl)
infer_oneway_anova(hsb, write, prog)
```

infer_os_prop_test *One Sample Test of Proportion*

Description

`infer_os_prop_test` compares proportion in one group to a specified population proportion.

Usage

```
infer_os_prop_test(
  data,
  variable = NULL,
  prob = 0.5,
  phat = 0.5,
  alternative = c("both", "less", "greater", "all")
)

## Default S3 method:
infer_os_prop_test(
  data,
  variable = NULL,
  prob = 0.5,
  phat = 0.5,
  alternative = c("both", "less", "greater", "all")
)
```

Arguments

<code>data</code>	numeric vector of length 1 or a <code>data.frame</code> or <code>tibble</code>
<code>variable</code>	factor; column in <code>data</code>
<code>prob</code>	hypothesised proportion
<code>phat</code>	observed proportion
<code>alternative</code>	a character string specifying the alternative hypothesis, must be one of "both" (default), "greater", "less" or "all". You can specify just the initial letter.

Value

`infer_os_prop_test` returns an object of class "`infer_os_prop_test`". An object of class "`infer_os_prop_test`" is a list containing the following components:

<code>n</code>	number of observations
<code>phat</code>	proportion of 1's
<code>p</code>	assumed probability of success
<code>z</code>	<code>z</code> statistic
<code>sig</code>	p-value for <code>z</code> statistic

alt	alternative hypothesis
obs	observed number of 0's and 1's
exp	expected number of 0's and 1's
deviation	deviation of observed from expected
std	standardized residuals

Deprecated Function

`prop_test()` has been deprecated. Instead use `infer_os_prop_test()`.

References

Sheskin, D. J. 2007. Handbook of Parametric and Nonparametric Statistical Procedures, 4th edition.
: Chapman & Hall/CRC.

See Also

[prop.test](#) [binom.test](#)

Examples

```
# use as a calculator
infer_os_prop_test(200, prob = 0.5, phat = 0.3)

# using data set
infer_os_prop_test(hsb, female, prob = 0.5)
```

`infer_os_t_test` *One Sample t Test*

Description

`infer_os_t_test` performs t tests on the equality of means. It tests the hypothesis that a sample has a mean equal to a hypothesized value.

Usage

```
infer_os_t_test(
  data,
  x,
  mu = 0,
  alpha = 0.05,
  alternative = c("both", "less", "greater", "all"),
  ...
)
```

Arguments

<code>data</code>	a <code>data.frame</code> or <code>tibble</code>
<code>x</code>	numeric; column in <code>data</code>
<code>mu</code>	a number indicating the true value of the mean
<code>alpha</code>	acceptable tolerance for type I error
<code>alternative</code>	a character string specifying the alternative hypothesis, must be one of "both" (default), "greater", "less" or "all". You can specify just the initial letter
<code>...</code>	additional arguments passed to or from other methods

Value

`infer_os_t_test` returns an object of class "`infer_os_t_test`". An object of class "`infer_os_t_test`" is a list containing the following components:

<code>mu</code>	a number indicating the true value of the mean
<code>n</code>	number of observations
<code>df</code>	degrees of freedom
<code>Mean</code>	observed mean of <code>x</code>
<code>stddev</code>	standard deviation of <code>x</code>
<code>std_err</code>	estimate of standard error
<code>test_stat</code>	t statistic
<code>confint</code>	confidence interval for the mean
<code>mean_diff</code>	mean difference
<code>mean_diff_l</code>	lower confidence limit for mean difference
<code>mean_diff_u</code>	upper confidence limit for mean difference
<code>p_l</code>	lower one-sided p-value
<code>p_u</code>	upper one-sided p-value
<code>p</code>	two sided p-value
<code>conf</code>	confidence level
<code>type</code>	alternative hypothesis
<code>var_name</code>	name of <code>x</code>

Deprecated Function

`ttest()` has been deprecated. Instead use `infer_os_t_test()`.

References

Sheskin, D. J. 2007. Handbook of Parametric and Nonparametric Statistical Procedures, 4th edition. : Chapman & Hall/CRC.

See Also[t.test](#)**Examples**

```
# lower tail
infer_os_t_test(hsb, write, mu = 50, alternative = 'less')

# upper tail
infer_os_t_test(hsb, write, mu = 50, alternative = 'greater')

# both tails
infer_os_t_test(hsb, write, mu = 50, alternative = 'both')

# all tails
infer_os_t_test(hsb, write, mu = 50, alternative = 'all')
```

infer_os_var_test*One Sample Variance Comparison Test***Description**

`infer_os_var_test` performs tests on the equality of standard deviations (variances). It tests that the standard deviation of a sample is equal to a hypothesized value.

Usage

```
infer_os_var_test(
  data,
  x,
  sd,
  confint = 0.95,
  alternative = c("both", "less", "greater", "all"),
  ...
)
```

Arguments

<code>data</code>	a <code>data.frame</code> or <code>tibble</code>
<code>x</code>	numeric; column in <code>data</code>
<code>sd</code>	hypothesised standard deviation
<code>confint</code>	confidence level
<code>alternative</code>	a character string specifying the alternative hypothesis, must be one of "both" (default), "greater", "less" or "all". You can specify just the initial letter
<code>...</code>	additional arguments passed to or from other methods

Value

`infer_os_var_test` returns an object of class "`infer_os_var_test`". An object of class "`infer_os_var_test`" is a list containing the following components:

<code>n</code>	number of observations
<code>sd</code>	hypothesised standard deviation of x
<code>sigma</code>	observed standard deviation
<code>se</code>	estimated standard error
<code>chi</code>	chi-square statistic
<code>df</code>	degrees of freedom
<code>p_lower</code>	lower one-sided p-value
<code>p_upper</code>	upper one-sided p-value
<code>p_two</code>	two-sided p-value
<code>xbar</code>	mean of x
<code>c_lwr</code>	lower confidence limit of standard deviation
<code>c_upr</code>	upper confidence limit of standard deviation
<code>var_name</code>	name of x
<code>conf</code>	confidence level
<code>type</code>	alternative hypothesis

Deprecated Function

`os_vartest()` has been deprecated. Instead use `infer_os_var_test()`.

References

Sheskin, D. J. 2007. Handbook of Parametric and Nonparametric Statistical Procedures, 4th edition.
: Chapman & Hall/CRC.

See Also

[var.test](#)

Examples

```
# lower tail
infer_os_var_test(mtcars, mpg, 5, alternative = 'less')

# upper tail
infer_os_var_test(mtcars, mpg, 5, alternative = 'greater')

# both tails
infer_os_var_test(mtcars, mpg, 5, alternative = 'both')

# all tails
infer_os_var_test(mtcars, mpg, 5, alternative = 'all')
```

infer_runs_test	<i>Test for Random Order</i>
------------------------	------------------------------

Description

`runttest` tests whether the observations of `x` are serially independent i.e. whether they occur in a random order, by counting how many runs there are above and below a threshold. By default, the median is used as the threshold. A small number of runs indicates positive serial correlation; a large number indicates negative serial correlation.

Usage

```
infer_runs_test(
  data,
  x,
  drop = FALSE,
  split = FALSE,
  mean = FALSE,
  threshold = NA
)
```

Arguments

<code>data</code>	a <code>data.frame</code> or <code>tibble</code>
<code>x</code>	numeric; column in <code>data</code>
<code>drop</code>	logical; if <code>TRUE</code> , values equal to the threshold will be dropped from <code>x</code>
<code>split</code>	logical; if <code>TRUE</code> , data will be recoded in binary format
<code>mean</code>	logical; if <code>TRUE</code> , mean will be used as threshold
<code>threshold</code>	threshold to be used for counting runs, specify 0 if data is coded as a binary.

Value

`infer_runs_test` returns an object of class "infer_runs_test". An object of class "infer_runs_test" is a list containing the following components:

<code>n</code>	number of observations
<code>threshold</code>	within group sum of squares
<code>n_below</code>	number below the threshold
<code>n_above</code>	number above the threshold
<code>mean</code>	expected number of runs
<code>var</code>	variance of the number of runs
<code>n_runs</code>	number of runs
<code>z</code>	<code>z</code> statistic
<code>p</code>	p-value of <code>z</code>

Deprecated Function

`runs_test()` has been deprecated. Instead use `infer_runs_test()`.

References

- Sheskin, D. J. 2007. Handbook of Parametric and Nonparametric Statistical Procedures, 4th edition. : Chapman & Hall/CRC.
- Edgington, E. S. 1961. Probability table for number of runs of signs of first differences in ordered series. *Journal of the American Statistical Association* 56: 156–159.
- Madansky, A. 1988. Prescriptions for Working Statisticians. New York: Springer.
- Swed, F. S., and C. Eisenhart. 1943. Tables for testing randomness of grouping in a sequence of alternatives. *Annals of Mathematical Statistics* 14: 66–87.

Examples

```
infer_runs_test(hsb, read)

infer_runs_test(hsb, read, drop = TRUE)

infer_runs_test(hsb, read, split = TRUE)

infer_runs_test(hsb, read, mean = TRUE)

infer_runs_test(hsb, read, threshold = 0)
```

infer_ts_ind_ttest Two Independent Sample t Test

Description

`infer_ts_ind_ttest` compares the means of two independent groups in order to determine whether there is statistical evidence that the associated population means are significantly different.

Usage

```
infer_ts_ind_ttest(
  data,
  x,
  y,
  confint = 0.95,
  alternative = c("both", "less", "greater", "all"),
  ...
)
```

Arguments

data	a data frame
x	factor; a column in data
y	numeric; a column in data
confint	confidence level
alternative	a character string specifying the alternative hypothesis, must be one of "both" (default), "greater", "less" or "all". You can specify just the initial letter
...	additional arguments passed to or from other methods

Value

`infer_ts_ind_ttest` returns an object of class "`infer_ts_ind_ttest`". An object of class "`infer_ts_ind_ttest`" is a list containing the following components:

levels	levels of x
obs	number of observations of y for each level of x
n	total number of observations
mean	mean of y for each level of x
sd	standard deviation of y for each level of x
se	estimate of standard error of y for each level of x
lower	lower limit for the mean of y for each level of x
upper	upper limit for the mean of y for each level of x
combined	a data frame; mean, standard deviation, standard error and confidence limit of mean of y
mean_diff	difference in mean of y for the two groups of x
se_dif	estimate of the standard error for difference in mean of y for the two groups of x
sd_dif	degrees of freedom
conf_diff	confidence interval for <code>mean_diff</code>
df_pooled	degrees of freedom for the pooled method
df_satterthwaite	degrees of freedom for the Satterthwaite method
t_pooled	t statistic for the pooled method
t_satterthwaite	t statistic for the Satterthwaite method
sig_pooled	two-sided p-value for the pooled method
sig_pooled_l	lower one-sided p-value for the pooled method
sig_pooled_u	upper one-sided p-value for the pooled method
sig	two-sided p-value for the Satterthwaite method
sig_l	lower one-sided p-value for the Satterthwaite method
sig_u	upper one-sided p-value for the Satterthwaite method

<code>num_df</code>	numerator degrees of freedom for folded f test
<code>den_df</code>	denominator degrees of freedom for folded f test
<code>f</code>	f value for the equality of variances test
<code>f_sig</code>	p-value for the folded f test
<code>var_y</code>	name of y
<code>confint</code>	confidence level
<code>alternative</code>	alternative hypothesis

Deprecated Function

`ind_ttest()` has been deprecated. Instead use `infer_ts_ind_ttest()`.

References

Sheskin, D. J. 2007. Handbook of Parametric and Nonparametric Statistical Procedures, 4th edition. : Chapman & Hall/CRC.

See Also

[t.test](#)

Examples

```
# lower tail
infer_ts_ind_ttest(hsb, female, write, alternative = 'less')

# upper tail
infer_ts_ind_ttest(hsb, female, write, alternative = 'greater')

# both tails
infer_ts_ind_ttest(hsb, female, write, alternative = 'both')

# all tails
infer_ts_ind_ttest(hsb, female, write, alternative = 'all')
```

`infer_ts_paired_ttest` *Paired t test*

Description

`infer_ts_paired_ttest` tests that two samples have the same mean, assuming paired data.

Usage

```
infer_ts_paired_ttest(
  data,
  x,
  y,
  confint = 0.95,
  alternative = c("both", "less", "greater", "all")
)
```

Arguments

<code>data</code>	a <code>data.frame</code> or <code>tibble</code>
<code>x</code>	numeric; column in <code>data</code>
<code>y</code>	numeric; column in <code>data</code>
<code>confint</code>	confidence level
<code>alternative</code>	a character string specifying the alternative hypothesis, must be one of "both" (default), "greater", "less" or "all". You can specify just the initial letter.

Value

`infer_ts_paired_ttest` returns an object of class "infer_ts_paired_ttest". An object of class "infer_ts_paired_ttest" is a list containing the following components:

<code>Obs</code>	number of observations
<code>b</code>	mean, standard deviation and standard error of <code>x</code> , <code>y</code> and their difference
<code>tstat</code>	t statistic
<code>p_lower</code>	lower one-sided p-value
<code>p_upper</code>	upper one-sided p-value
<code>p_two_tail</code>	two sided p-value
<code>corr</code>	Correlation of <code>x</code> and <code>y</code>
<code>corsig</code>	p-value of correlation test
<code>conf_int1</code>	confidence interval for mean of <code>x</code>
<code>conf_int2</code>	confidence interval for mean of <code>y</code>
<code>conf_int_diff</code>	confidence interval for mean of difference of <code>x</code> and <code>y</code>
<code>df</code>	degrees of freedom
<code>confint</code>	confidence level
<code>alternative</code>	alternative hypothesis
<code>var_names</code>	names of <code>x</code> and <code>y</code>
<code>xy</code>	string used in printing results of the test

Deprecated Function

`paired_ttest()` has been deprecated. Instead use `infer_ts_paired_ttest()`.

References

Sheskin, D. J. 2007. Handbook of Parametric and Nonparametric Statistical Procedures, 4th edition.
: Chapman & Hall/CRC.

See Also

[t.test](#)

Examples

```
# lower tail
infer_ts_paired_ttest(hsb, read, write, alternative = 'less')

# upper tail
infer_ts_paired_ttest(hsb, read, write, alternative = 'greater')

# both tails
infer_ts_paired_ttest(hsb, read, write, alternative = 'both')

# all tails
infer_ts_paired_ttest(hsb, read, write, alternative = 'all')
```

infer_ts_prop_test Two Sample Test of Proportion

Description

Tests on the equality of proportions using large-sample statistics. It tests that a sample has the same proportion within two independent groups or two samples have the same proportion.

Usage

```
infer_ts_prop_test(
  data,
  var1,
  var2,
  alternative = c("both", "less", "greater", "all"),
  ...
)

infer_ts_prop_group(
  data,
  var,
  group,
  alternative = c("both", "less", "greater", "all")
)

infer_ts_prop_calc(
```

```

n1,
n2,
p1,
p2,
alternative = c("both", "less", "greater", "all"),
...
)

```

Arguments

data	a <code>data.frame</code> or <code>tibble</code>
var1	factor; column in data
var2	factor; column in data
alternative	a character string specifying the alternative hypothesis, must be one of "both" (default), "greater", "less" or "all". You can specify just the initial letter
...	additional arguments passed to or from other methods
n1	sample 1 size
n2	sample 2 size
p1	sample 1 proportion
p2	sample 2 proportion
var	factor; column in data
group	factor; column in data

Value

an object of class "`infer_ts_prop_test`". An object of class "`infer_ts_prop_test`" is a list containing the following components:

n1	sample 1 size
n2	sample 2 size
phat1	sample 1 proportion
phat2	sample 2 proportion
z	z statistic
sig	p-value for z statistic
alt	alternative hypothesis

Deprecated Functions

`infer_ts_prop_test()`, `infer_ts_prop_grp()` and `infer_ts_prop_calc()` have been deprecated. Instead use `infer_ts_prop_test()`, `infer_ts_prop_group()` and `infer_ts_prop_calc()`.

References

Sheskin, D. J. 2007. Handbook of Parametric and Nonparametric Statistical Procedures, 4th edition. : Chapman & Hall/CRC.

See Also[prop.test](#)**Examples**

```
# using variables
# lower tail
infer_ts_prop_test(treatment, treatment1, treatment2,
alternative = 'less')

# using groups
# lower tail
infer_ts_prop_group(treatment2, outcome, female,
alternative = 'less')

# using sample size and proportions
# lower tail
infer_ts_prop_calc(n1 = 30, n2 = 25, p1 = 0.3, p2 = 0.5, alternative = 'less')
```

infer_ts_var_test *Two Sample Variance Comparison Test*

Description

`infer_ts_var_test` performs tests on the equality of standard deviations (variances).

Usage

```
infer_ts_var_test(
  data,
  ...,
  group_var = NULL,
  alternative = c("less", "greater", "all")
)
```

Arguments

<code>data</code>	a <code>data.frame</code> or <code>tibble</code>
<code>...</code>	numeric; column(s) in <code>data</code>
<code>group_var</code>	factor; column in <code>data</code>
<code>alternative</code>	a character string specifying the alternative hypothesis, must be one of "both" (default), "greater", "less" or "all". You can specify just the initial letter.

Value

`infer_ts_var_test` returns an object of class "infer_ts_var_test". An object of class "infer_ts_var_test" is a list containing the following components:

<code>f</code>	f statistic
<code>lower</code>	lower one-sided p-value
<code>upper</code>	upper one-sided p-value
<code>two_tail</code>	two-sided p-value
<code>vars</code>	variances for each level of the grouping variable
<code>avgs</code>	means for each level of the grouping variable
<code>sds</code>	standard deviations for each level of the grouping variable
<code>ses</code>	standard errors for each level of the grouping variable
<code>avg</code>	combined mean
<code>sd</code>	combined standard deviation
<code>se</code>	estimated combined standard error
<code>n1</code>	numerator degrees of freedom
<code>n2</code>	denominator degrees of freedom
<code>lens</code>	number of observations for each level of grouping variable
<code>len</code>	number of observations
<code>lev</code>	levels of the grouping variable
<code>type</code>	alternative hypothesis

Deprecated Function

`var_test()` has been deprecated. Instead use `infer_ts_var_test()`.

References

Sheskin, D. J. 2007. Handbook of Parametric and Nonparametric Statistical Procedures, 4th edition.
: Chapman & Hall/CRC.

See Also

[var.test](#)

Examples

```
# using grouping variable
infer_ts_var_test(hsb, read, group_var = female, alternative = 'less')

# using two variables
infer_ts_var_test(hsb, read, write, alternative = 'less')
```

treatment*Dummy data set for 2 Sample Proportion test*

Description

A dataset containing information about two treatments

Usage

treatment

Format

A data frame with 50 rows and 2 variables:

treatment1 result of treatment type 1

treatment2 result of treatment type 2

treatment2*Dummy data set for 2 Sample Proportion test*

Description

A dataset containing information about treatment outcomes

Usage

treatment2

Format

A data frame with 200 rows and 2 variables:

outcome outcome of treatment

female gender of patient, 0 for male and 1 for female

Index

* datasets
exam, 2
hsb, 3
treatment, 28
treatment2, 28

anova, 13

binom.test, 5, 15

chisq.test, 6, 7

exam, 2

hsb, 3

infer_binom_calc, 4
infer_binom_test (infer_binom_calc), 4
infer_chisq_assoc_test, 5
infer_chisq_gof_test, 6
infer_cochran_qtest, 8
infer_launch_shiny_app, 9
infer_levene_test, 9
infer_mcneamar_test, 11
infer_oneway_anova, 12
infer_os_prop_test, 14
infer_os_t_test, 15
infer_os_var_test, 17
infer_runs_test, 19
infer_ts_ind_ttest, 20
infer_ts_paired_ttest, 22
infer_ts_prop_calc
 (infer_ts_prop_test), 24
infer_ts_prop_group
 (infer_ts_prop_test), 24
infer_ts_prop_test, 24
infer_ts_var_test, 26
inferr, 3

mcneamar.test, 12