

Package ‘leaflet.extras2’

August 21, 2023

Type Package

Title Extra Functionality for 'leaflet' Package

Version 1.2.2

Description

Several 'leaflet' plugins are integrated, which are available as extension to the 'leaflet' package.

License GPL-3 | file LICENSE

Encoding UTF-8

LazyData true

Depends R (>= 3.1.0), leaflet (>= 2.0.0)

Imports htmltools, magrittr, utils

Suggests jsonlite, shiny, sf, geojsonsf, sp, testthat (>= 2.1.0),
fontawesome, htmlwidgets, covr, curl

URL <https://trafficonese.github.io/leaflet.extras2/>,
<https://github.com/trafficonese/leaflet.extras2>

BugReports <https://github.com/trafficonese/leaflet.extras2/issues>

RoxygenNote 7.2.0

NeedsCompilation no

Author Gatscha Sebastian [aut, cre],
Ricardo Rodrigo Basa [ctb],
Jeffrey O Hanson [ctb] (<<https://orcid.org/0000-0002-4716-6134>>)

Maintainer Gatscha Sebastian <sebastian_gatscha@gmx.at>

Repository CRAN

Date/Publication 2023-08-21 09:22:43 UTC

R topics documented:

addAntpath	4
addArrowhead	6
addContextmenu	8

addEasyprint	9
addGIBS	10
addHeightgraph	11
addHexbin	13
addHistory	15
addItemContextmenu	16
addLabelgun	16
addLeafletsync	17
addLeafletsyncDependency	18
addMapkeyMarkers	19
addMovingMarker	21
addOpenweathermapCurrent	22
addOpenweathermapTiles	24
addPlayback	25
addReachability	28
addSidebar	29
addSidebyside	30
addSpinner	31
addTangram	32
addTimeslider	33
addVelocity	35
addWMS	36
antpathOptions	38
arrowheadOptions	39
clearAntpath	40
clearArrowhead	41
clearFuture	42
clearHexbin	42
clearHistory	43
closeSidebar	43
context_mapmenuItems	44
context_markermenuItems	45
context_menuItem	45
disableContextmenu	46
easyprintMap	47
easyprintOptions	48
enableContextmenu	49
gibs_layers	50
goBackHistory	50
goForwardHistory	51
heightgraphOptions	51
hexbinOptions	53
hideContextmenu	54
hideHexbin	55
historyOptions	55
insertItemContextmenu	57
isSynced	57
leaflet.extras2	58

leafletSyncOptions	58
makeMapkeyIcon	59
mapkeyIconList	60
mapkeyIcons	61
mapmenuItems	62
markermenuItems	63
menuItem	64
movingMarkerOptions	64
openSidebar	65
openweatherCurrentOptions	66
openweatherOptions	66
playbackOptions	67
reachabilityOptions	69
removeallItemsContextmenu	69
removeAntpath	70
removeArrowhead	71
removeEasyprint	71
removeItemContextmenu	72
removePlayback	72
removeReachability	73
removeSidebar	73
removeSidebyside	74
removeTimeslider	74
removeVelocity	75
setDate	75
setDisabledContextmenu	76
setOptionsVelocity	77
setTransparent	77
showContextmenu	78
showHexbin	79
sidebar_pane	79
sidebar_tabs	80
startMoving	81
timesliderOptions	82
to_jsonformat	84
to_ms	84
unsync	85
updateHexbin	85
velocityOptions	86
[.leaflet_mapkey_icon_set	87

addAntpath*Add Antpath Lines***Description**

Can be used almost exactly like `addPolylines` but instead of `pathOptions` you can use `antpathOptions` to adapt the Antpath behaviour. See [leaflet-ant-path](#) for further details.

Usage

```
addAntpath(
  map,
  lng = NULL,
  lat = NULL,
  layerId = NULL,
  group = NULL,
  stroke = TRUE,
  color = "#03F",
  weight = 5,
  opacity = 0.5,
  fill = FALSE,
  fillColor = color,
  fillOpacity = 0.2,
  dashArray = NULL,
  smoothFactor = 1,
  noClip = FALSE,
  popup = NULL,
  popupOptions = NULL,
  label = NULL,
  labelOptions = NULL,
  options = antpathOptions(),
  highlightOptions = NULL,
  data = getMapData(map)
)
```

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>lng</code>	a numeric vector of longitudes, or a one-sided formula of the form <code>~x</code> where <code>x</code> is a variable in <code>data</code> ; by default (if not explicitly provided), it will be automatically inferred from <code>data</code> by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
<code>lat</code>	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from <code>data</code>)
<code>layerId</code>	the layer id

group	the name of the group the newly created layers should belong to (for <code>clearGroup</code> and <code>addLayersControl</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
stroke	whether to draw stroke along the path (e.g. the borders of polygons or circles)
color	stroke color
weight	stroke width in pixels
opacity	stroke opacity (or layer opacity for tile layers)
fill	whether to fill the path with color (e.g. filling on polygons or circles)
fillColor	fill color
fillOpacity	fill opacity
dashArray	a string that defines the stroke <code>dash pattern</code>
smoothFactor	how much to simplify the polyline on each zoom level (more means better performance and less accurate representation)
noClip	whether to disable polyline clipping
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using <code>htmlEscape()</code> for security reasons)
popupOptions	A Vector of <code>popupOptions</code> to provide popups
label	a character vector of the HTML content for the labels
labelOptions	A Vector of <code>labelOptions</code> to provide label options for each label. Default NULL
options	A named list of options. See <code>antpathOptions</code>
highlightOptions	Options for highlighting the shape on mouse over.
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden

Value

A modified leaflet map, with an 'ant-path' animated polyline

References

<https://github.com/rubenspgcavalcante/leaflet-ant-path>

See Also

Other Antpath Functions: `antpathOptions()`, `clearAntpath()`, `removeAntpath()`

Examples

```
library(leaflet)
leaflet() %>%
  addAntpath(data = atlStorms2005)
```

<code>addArrowhead</code>	<i>Add Lines with an arrowhead</i>
---------------------------	------------------------------------

Description

Can be used almost exactly like `addPolylines` but instead of `pathOptions` you can use `arrowheadOptions`. See [leaflet-arrowheads](#) for further details.

Usage

```
addArrowhead(
  map,
  lng = NULL,
  lat = NULL,
  layerId = NULL,
  group = NULL,
  stroke = TRUE,
  color = "#03F",
  weight = 5,
  opacity = 0.5,
  fill = FALSE,
  fillColor = color,
  fillOpacity = 0.2,
  dashArray = NULL,
  smoothFactor = 1,
  noClip = FALSE,
  popup = NULL,
  popupOptions = NULL,
  label = NULL,
  labelOptions = NULL,
  options = arrowheadOptions(),
  highlightOptions = NULL,
  data = getMapData(map)
)
```

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>lng</code>	a numeric vector of longitudes, or a one-sided formula of the form $\sim x$ where x is a variable in <code>data</code> ; by default (if not explicitly provided), it will be automatically inferred from <code>data</code> by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
<code>lat</code>	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from <code>data</code>)
<code>layerId</code>	the layer id

group	the name of the group the newly created layers should belong to (for <code>clearGroup</code> and <code>addLayersControl</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
stroke	whether to draw stroke along the path (e.g. the borders of polygons or circles)
color	stroke color
weight	stroke width in pixels
opacity	stroke opacity (or layer opacity for tile layers)
fill	whether to fill the path with color (e.g. filling on polygons or circles)
fillColor	fill color
fillOpacity	fill opacity
dashArray	a string that defines the stroke <code>dash pattern</code>
smoothFactor	how much to simplify the polyline on each zoom level (more means better performance and less accurate representation)
noClip	whether to disable polyline clipping
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using <code>htmlEscape()</code> for security reasons)
popupOptions	A Vector of <code>popupOptions</code> to provide popups
label	a character vector of the HTML content for the labels
labelOptions	A Vector of <code>labelOptions</code> to provide label options for each label. Default NULL
options	A named list of options. See <code>arrowheadOptions</code>
highlightOptions	Options for highlighting the shape on mouse over.
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden

Value

A modified leaflet map with a polyline with arrowheads

References

<https://github.com/slutske22/leaflet-arrowheads>

See Also

Other Arrowhead Functions: `arrowheadOptions()`, `clearArrowhead()`, `removeArrowhead()`

Examples

```
library(leaflet)
leaflet() %>%
  addArrowhead(data = atlStorms2005)
```

addContextmenu *Add contextmenu Plugin*

Description

Add a contextmenu to the map or markers/vector layers.

Usage

```
addContextmenu(map)
```

Arguments

map	a map widget object created from leaflet
-----	--

Details

This function is only used to include the required JavaScript and CSS bindings and to set up some Shiny event handlers.

Contextmenu initialization: The contextmenu for

- the **map** must be defined in [leafletOptions](#).
- the **markers/vector layers** must be defined in [markerOptions](#) or [pathOptions](#).

Contextmenu selection: When a contextmenu is selected, a Shiny input with the ID "MAPID_contextmenu_select" is set ('MAPID' refers to the map's id).

If the selected contextmenu item is triggered from:

- the **map**, the returned list contains the text of the item.
- the **markers**, the returned list also contains the layerId, group, lat, lng and label.
- the **vector layers**, the returned list also contains the layerId, group and label.

Value

A leaflet map object

References

<https://github.com/araccliffe/Leaflet.contextmenu>

See Also

Other Contextmenu Functions: [addItemContextMenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextMenu\(\)](#), [removeallItemsContextMenu\(\)](#), [setDisabledContextMenu\(\)](#), [showContextMenu\(\)](#)

Examples

```
library(leaflet)
leaflet(options = leafletOptions(
  contextmenu = TRUE,
  contextmenuWidth = 200,
  contextmenuItems =
    context_mapmenuItems(
      context_menuItem("Zoom Out", "function(e) {this.zoomOut()}", disabled=FALSE),
      "-",
      context_menuItem("Zoom In", "function(e) {this.zoomIn()}"))) %>%
  addTiles(group = "base") %>%
  addContextMenu() %>%
  addMarkers(data = breweries91, label = ~brewery,
    layerId = ~founded, group = "marker",
    options = markerOptions(
      contextmenu = TRUE,
      contextmenuWidth = 200,
      contextmenuItems =
        context_markermenuItems(
          context_menuItem(text = "Show Marker Coords",
            callback = "function(e) {alert(e.latlng);}",
            index = 1)
        )
    )))
  )
```

addEasyprint

Add easyPrint Plugin

Description

Add a control, which allows to print or export a map as .PNG.

Usage

```
addEasyprint(map, options = easyprintOptions())
```

Arguments

map	a map widget object created from leaflet
options	A named list of options. See easyprintOptions

Value

A leaflet map object

References

<https://github.com/rowanwins/leaflet-easyPrint>

See Also

Other EasyPrint Functions: [easyprintMap\(\)](#), [easyprintOptions\(\)](#), [removeEasyprint\(\)](#)

Examples

```
library(leaflet)
leaflet() %>%
  addTiles() %>%
  addEasyprint(options = easyprintOptions(
    title = 'Print map',
    position = 'bottomleft',
    exportOnly = TRUE))
```

addGIBS

Add GIBS Layers

Description

A leaflet plugin for NASA EOSDIS GIBS imagery integration. 154 products are available. The date can be set dynamically for multi-temporal products. No-data pixels of MODIS Multiband Imagery can be made transparent.

Usage

```
addGIBS(
  map,
  layers = NULL,
  group = NULL,
  dates = NULL,
  opacity = 0.5,
  transparent = TRUE
)
```

Arguments

map	a map widget object created from leaflet()
layers	A character vector of GIBS-layers. See gibs_layers
group	the name of the group the newly created layers should belong to (for clearGroup and addLayersControl purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
dates	Date object. If multiple layers are added, you can add a Date vector of the same length
opacity	Numeric value determining the opacity. If multiple layers are added, you can add a numeric vector of the same length
transparent	Should the layer be transparent. If multiple layers are added, you can add a boolean vector of the same length

Value

the new map object

References

<https://github.com/aparshin/leaflet-GIBS>

See Also

Other GIBS Functions: [setDate\(\)](#), [setTransparent\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras2)

layers <- gibs_layers$title[c(35, 128, 185)]

leaflet() %>%
  addTiles() %>%
  setView(9, 50, 4) %>%
  addGIBS(layers = layers,
          dates = Sys.Date() - 1,
          group = layers) %>%
  addLayersControl(overlayGroups = layers)
```

addHeightgraph

Add a Heightgraph layer

Description

Visualize height information and road attributes of linestring segments. The linestrings must be a Simple Feature LINESTRING Z and are transformed to GeoJSON. The function therefore inherits arguments from [addGeoJSON](#).

Usage

```
addHeightgraph(
  map,
  data = NULL,
  columns = NULL,
  layerId = NULL,
  group = NULL,
  color = "#03F",
  weight = 5,
  opacity = 0.5,
  dashArray = NULL,
  smoothFactor = 1,
```

```

    noClip = FALSE,
    pathOpts = leaflet::pathOptions(),
    options = heightgraphOptions()
)

```

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>data</code>	A Simple Feature LINESTRING with Z dimension.
<code>columns</code>	A character vector of the columns you want to include in the heightgraph control
<code>layerId</code>	the layer id
<code>group</code>	the name of the group the newly created layers should belong to (for clearGroup and addLayersControl purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
<code>color</code>	stroke color
<code>weight</code>	stroke width in pixels
<code>opacity</code>	stroke opacity (or layer opacity for tile layers)
<code>dashArray</code>	a string that defines the stroke dash pattern
<code>smoothFactor</code>	how much to simplify the polyline on each zoom level (more means better performance and less accurate representation)
<code>noClip</code>	whether to disable polyline clipping
<code>pathOpts</code>	List of further options for the path. See pathOptions
<code>options</code>	List of further plugin options. See heightgraphOptions

Value

the new map object

Note

When used in Shiny, 3 events update a certain Shiny Input:

1. A click updates `input$MAPID_heightgraph_click`
2. A mouseover updates `input$MAPID_heightgraph_mouseover`
3. A mouseout updates `input$MAPID_heightgraph_mouseout`

If you want to explicitly remove the Heightgraph control, please use [removeControl](#) with the `layerId = "hg_control"`.

References

<https://github.com/GIScience/Leaflet.Heightgraph>

See Also

Other Heightgraph Functions: [heightgraphOptions\(\)](#)

Examples

```
## Not run:
library(leaflet)
library(leaflet.extras2)
library(sf)

data <- st_cast(st_as_sf(leaflet::atlStorms2005[4,]), "LINESTRING")
data <- st_transform(data, 4326)
data <- data.frame(st_coordinates(data))
data$elev <- runif(nrow(data), 10, 500)
data$L1 <- NULL
L1 <- round(seq.int(1, 4, length.out = nrow(data)))
data <- st_as_sf(st_sfc(lapply(split(data, L1), sfg_linestring)))
data <- st_as_sf(st_sfc(lapply(split(data, L1), function(x) {
  st_linestring(as.matrix(x))
})))
data$steepness <- 1:nrow(data)
data$suitability <- nrow(data):1
data$popup <- apply(data, 1, function(x) {
  sprintf("Steepness: %s<br>Suitability: %s", x$steepness, x$suitability)
})

leaflet() %>%
  addTiles(group = "base") %>%
  addHeightgraph(color = "red", columns = c("steepness", "suitability"),
                 opacity = 1, data = data, group = "heightgraph",
                 options = heightgraphOptions(width = 400))

## End(Not run)
```

addHexbin

*Add a Hexbin layer***Description**

Create dynamic hexbin-based heatmaps on Leaflet maps. This plugin leverages the data-binding power of d3 to allow you to dynamically update the data and visualize the transitions.

Usage

```
addHexbin(
  map,
  lng = NULL,
  lat = NULL,
  radius = 20,
```

```

layerId = NULL,
group = NULL,
opacity = 0.5,
options = hexbinOptions(),
data = getMapData(map)
)

```

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>lng</code>	a numeric vector of longitudes, or a one-sided formula of the form $\sim x$ where x is a variable in <code>data</code> ; by default (if not explicitly provided), it will be automatically inferred from <code>data</code> by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
<code>lat</code>	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from <code>data</code>)
<code>radius</code>	Radius of the hexbin layer
<code>layerId</code>	the layer id
<code>group</code>	the name of the group the newly created layers should belong to (for clearGroup and addLayersControl purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
<code>opacity</code>	Opacity of the hexbin layer
<code>options</code>	List of further options. See hexbinOptions
<code>data</code>	the data object from which the argument values are derived; by default, it is the <code>data</code> object provided to <code>leaflet()</code> initially, but can be overridden

Value

the new map object

Note

Currently doesn't respect `layerId` nor `group`.

References

<https://github.com/bluehalo/leaflet-d3#hexbins-api>

See Also

Other Hexbin-D3 Functions: [clearHexbin\(\)](#), [hexbinOptions\(\)](#), [hideHexbin\(\)](#), [showHexbin\(\)](#), [updateHexbin\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras2)

n <- 1000
df <- data.frame(lat = rnorm(n, 42.0285, .01),
                  lng = rnorm(n, -93.65, .01))

leaflet() %>%
  addTiles() %>%
  addHexbin(lng = df$lng, lat = df$lat,
            options = hexbinOptions(
              colorRange = c("red", "yellow", "blue"),
              radiusRange = c(10, 20)
            ))
```

addHistory

Add History Plugin

Description

The plugin enables tracking of map movements in a history similar to a web browser. By default, it is a simple pair of buttons – back and forward.

Usage

```
addHistory(map, layerId = NULL, options = historyOptions())
```

Arguments

map	a map widget object created from leaflet
layerId	the control id
options	A named list of options. See historyOptions

Value

the new map object

References

<https://github.com/cscott530/leaflet-history>

See Also

Other History Functions: [clearFuture\(\)](#), [clearHistory\(\)](#), [goBackHistory\(\)](#), [goForwardHistory\(\)](#), [historyOptions\(\)](#)

Examples

```
library(leaflet)
leaflet() %>%
  addTiles() %>%
  addHistory()
```

addItemContextMenu *addItemContextMenu*

Description

Add a new contextmenu menu item

Usage

```
addItemContextMenu(map, option)
```

Arguments

map	a map widget object created from leaflet
option	new menu item to add

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextMenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextMenu\(\)](#), [removeallItemsContextMenu\(\)](#), [setDisabledContextMenu\(\)](#), [showContextMenu\(\)](#)

addLabelgun *Add addLabelgun Plugin*

Description

The plugin allows to avoid cluttering in marker labels and gives priority to labels of your choice (with higher weight).

Usage

```
addLabelgun(map, group = NULL, weight = NULL, entries = NULL)
```

Arguments

<code>map</code>	A map widget object created from leaflet
<code>group</code>	The group name of the layer/s for which label collisions are to be avoided. To see the effects of this plugin the <code>labelOptions</code> of the markers must be configured with either <code>permanent = TRUE</code> or <code>noHide = TRUE</code> .
<code>weight</code>	An optional weight for markers. If a vector is given, the length should match the number of all markers in the corresponding groups. If a numeric value is specified, it is used for each marker and thus no prioritization of the labels takes place. In all other cases a random integer is calculated.
<code>entries</code>	A numeric value, a higher value relates to faster insertion and slower search, and vice versa. The default is 10

Value

A leaflet map object

Note

It is important to invoke the function after the markers have been added to the map. Otherwise nothing will happen.

References

<https://github.com/Geovation/labelgun>

`addLeafletsync`

Synchronize multiple Leaflet map

Description

The plugin allows you to synchronize and unsynchronize multiple leaflet maps in a Shiny application. You can pass additional options to `leafletsyncOptions`. For more information see [Leaflet.Sync](#)

Usage

```
addLeafletsync(
  map,
  ids = NULL,
  synclist = "all",
  options = leafletsyncOptions()
)
```

Arguments

<code>map</code>	the map
<code>ids</code>	the map ids to be synced. If you use a <code>synclist</code> , you may leave it <code>NULL</code> . The unique names and values of <code>synclist</code> will be used.
<code>synclist</code>	The synchronization list. The default is ' <code>all</code> ', which creates a list of all possible combinations of <code>ids</code> . For a more detailed control, a named list can be passed in this form <code>list(m1 = c("m2", "m3"), m2 = c("m1", "m3"), m3 = c("m1", "m2"))</code> , where the names and values represent map-ids. The names of the lists serve as a basis and the list values are the maps to be kept in sync with the basemap.
<code>options</code>	A named list of options. See leafletsyncOptions . If you want to add different options to multiple maps, you can wrap the options in a named list, with the names being the map-ids. See the example in <code>./inst/examples/offset_continuous.R</code>

Value

A modified leaflet map

Note

If you synchronize multiple maps, a map may not yet be initialized and therefore cannot be used. Make sure to use `addLeafletsync` after all maps have been rendered.

References

<https://github.com/jieter/Leaflet.Sync>

See Also

Other leafletsync Functions: `addLeafletsyncDependency()`, `isSynced()`, `leafletsyncOptions()`, `unsync()`

addLeafletsyncDependency

Add the Leaflet Sync JS dependencies

Description

Sometimes it makes sense to include the Leaflet Sync dependencies already before synchronizing maps. For example, if you want to use the 'L.Sync.offsetHelper'. See the example in `./inst/examples/offsetHelper.R`

Usage

```
addLeafletsyncDependency(map)
```

Arguments

<code>map</code>	the map
------------------	---------

Value

A modified leaflet map

See Also

Other leafletsync Functions: [addLeafletsync\(\)](#), [isSynced\(\)](#), [leafletsyncOptions\(\)](#), [unsync\(\)](#)

addMapkeyMarkers *Add Mapkey Markers*

Description

Add Mapkey Markers

Usage

```
addMapkeyMarkers(  
  map,  
  lng = NULL,  
  lat = NULL,  
  layerId = NULL,  
  group = NULL,  
  icon = NULL,  
  popup = NULL,  
  popupOptions = NULL,  
  label = NULL,  
  labelOptions = NULL,  
  options = leaflet::markerOptions(),  
  clusterOptions = NULL,  
  clusterId = NULL,  
  data = leaflet::getMapData(map)  
)
```

Arguments

map	the map to add mapkey Markers to.
lng	a numeric vector of longitudes, or a one-sided formula of the form $\sim x$ where x is a variable in $data$; by default (if not explicitly provided), it will be automatically inferred from $data$ by looking for a column named lng , $long$, or $longitude$ (case-insensitively)
lat	a vector of latitudes or a formula (similar to the lng argument; the names lat and $latitude$ are used when guessing the latitude column from $data$)
layerId	the layer id

group	the name of the group the newly created layers should belong to (for <code>clearGroup</code> and <code>addLayersControl</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
icon	the icon(s) for markers;
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using <code>htmlEscape()</code> for security reasons)
popupOptions	A Vector of <code>popupOptions</code> to provide popups
label	a character vector of the HTML content for the labels
labelOptions	A Vector of <code>labelOptions</code> to provide label options for each label. Default NULL
options	a list of extra options for markers. See <code>markerOptions</code>
clusterOptions	if not NULL, markers will be clustered using <code>Leaflet.markercluster</code> ; you can use <code>markerClusterOptions()</code> to specify marker cluster options
clusterId	the id for the marker cluster layer
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden

Value

the new map object

References

<https://github.com/mapshakers/leaflet-mapkey-icon>

See Also

Other Mapkey Functions: `[.leaflet_mapkey_icon_set()`, `makeMapkeyIcon()`, `mapkeyIconList()`, `mapkeyIcons()`

Examples

```
library(leaflet)

leaflet() %>%
  addTiles() %>%
  addMapkeyMarkers(data = breweries91,
    icon = makeMapkeyIcon(icon = "mapkey",
                          iconSize = 30,
                          boxShadow = FALSE,
                          background = "transparent"),
    group = "mapkey",
    label = ~state, popup = ~village)
```

addMovingMarker *Add Moving Markers*

Description

The function expects either line or point data as spatial data or as Simple Feature. Alternatively, coordinates can also be passed as numeric vectors.

Usage

```
addMovingMarker(  
  map,  
  lng = NULL,  
  lat = NULL,  
  layerId = NULL,  
  group = NULL,  
  duration = 2000,  
  icon = NULL,  
  popup = NULL,  
  popupOptions = NULL,  
  label = NULL,  
  labelOptions = NULL,  
  movingOptions = movingMarkerOptions(),  
  options = leaflet::markerOptions(),  
  data = leaflet:::getMapData(map)  
)
```

Arguments

map	the map to add moving markers
lng	a numeric vector of longitudes, or a one-sided formula of the form $\sim x$ where x is a variable in <code>data</code> ; by default (if not explicitly provided), it will be automatically inferred from <code>data</code> by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
lat	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from <code>data</code>)
layerId	In order to be able to address the moving markings individually, a <code>layerId</code> is required. If none is specified, one is created that is derived from the current timestamp.
group	the name of the group the newly created layers should belong to (for <code>clearGroup</code> and <code>addLayersControl</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
duration	Duration in milliseconds per line segment between 2 points. Can be a vector or a single number. Default is 1000

icon	the icon(s) for markers;
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using <code>htmlEscape()</code> for security reasons)
popupOptions	A Vector of <code>popupOptions</code> to provide popups
label	a character vector of the HTML content for the labels
labelOptions	A Vector of <code>labelOptions</code> to provide label options for each label. Default NULL
movingOptions	a list of extra options for moving markers. See <code>movingMarkerOptions</code>
options	a list of extra options for markers. See <code>markerOptions</code>
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden

Value

the new map object

References

<https://github.com/ewoken/Leaflet.MovingMarker>

See Also

Other MovingMarker Functions: `movingMarkerOptions()`, `startMoving()`

Examples

```
library(sf)
library(leaflet)
library(leaflet.extras2)

df <- sf::st_as_sf(atlStorms2005)[1,]
leaflet() %>%
  addTiles() %>%
  addPolylines(data = df) %>%
  addMovingMarker(data = df,
                  movingOptions = movingMarkerOptions(autostart = TRUE, loop = TRUE),
                  label="I am a pirate!",
                  popup="Arrr")
```

`addOpenweatherCurrent` *Add current OpenWeatherMap Marker*

Description

Add current OpenWeatherMap Marker

Usage

```
addOpenweatherCurrent(
  map,
  apikey = NULL,
  group = NULL,
  layerId = NULL,
  options = openweatherCurrentOptions()
)
```

Arguments

map	a map widget object created from leaflet()
apikey	a valid Openweathermap-API key. Get one from here .
group	the name of the group the newly created layers should belong to (for clearGroup and addLayersControl purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
layerId	the layer id
options	List of further options. See openweatherCurrentOptions

Value

the new map object

Note

The current weather icons will appear beginning with zoom level 9 and if used in Shiny, a click on an icon will update a Shiny input at `input$MAPID_owm_click`.

References

<https://github.com/trafficonese/leaflet-openweathermap>

See Also

Other Openweathermap Functions: [addOpenweatherTiles\(\)](#), [openweatherCurrentOptions\(\)](#), [openweatherOptions\(\)](#)

Examples

```
## Not run:
library(leaflet)
library(leaflet.extras2)

Sys.setenv("OPENWEATHERMAP" = 'Your_API_Key')

leaflet() %>%
  addTiles() %>% setView(9, 50, 9) %>%
```

```
addOpenweatherCurrent(options = openweatherCurrentOptions(
  lang = "en", popup = TRUE))

## End(Not run)
```

`addOpenweatherTiles` *Add OpenWeatherMap Tiles*

Description

Add OpenWeatherMap Tiles

Usage

```
addOpenweatherTiles(
  map,
  apikey = NULL,
  layers = NULL,
  group = NULL,
  layerId = NULL,
  opacity = 0.5,
  options = openweatherOptions()
)
```

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>apikey</code>	a valid OpenWeatherMap-API key. Get one from here .
<code>layers</code>	character vector of layers you wish to add to the map. The following layers are currently possible <code>c("clouds", "cloudsClassic", "precipitation", "precipitationClassic", "rain", "rainClassic", "snow", "pressure", "pressureContour", "temperature", "wind")</code> .
<code>group</code>	the name of the group the newly created layers should belong to (for clearGroup and addLayersControl purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
<code>layerId</code>	the layer id
<code>opacity</code>	opacity of the layer
<code>options</code>	List of further options. See openweatherOptions

Value

the new map object

Note

Out of the box a legend image is only available for Pressure, Precipitation Classic, Clouds Classic, Rain Classic, Snow, Temperature and Wind Speed. Please add your own images if you need some more.

References

<https://github.com/trafficonese/leaflet-openweathermap>

See Also

Other Openweathermap Functions: [addOpenweatherCurrent\(\)](#), [openweatherCurrentOptions\(\)](#), [openweatherOptions\(\)](#)

Examples

```
## Not run:  
library(leaflet)  
library(leaflet.extras)  
  
Sys.setenv("OPENWEATHERMAP" = 'Your_API_Key')  
  
leaflet() %>%  
  addTiles() %>% setView(9, 50, 6) %>%  
  addOpenweatherTiles(layers = "wind")  
  
## End(Not run)
```

addPlayback

Add Playback to Leaflet

Description

The [LeafletPlayback plugin](#) provides the ability to replay GPS Points in the form of POINT Simple Features. Rather than simply animating a marker along a polyline, the speed of the animation is synchronized to a clock. The playback functionality is similar to a video player; you can start and stop playback or change the playback speed.

Usage

```
addPlayback(  
  map,  
  data,  
  time = "time",  
  icon = NULL,  
  pathOpts = pathOptions(),  
  popup = NULL,  
  label = NULL,
```

```

popupOptions = NULL,
labelOptions = NULL,
options = playbackOptions(),
name = NULL
)

```

Arguments

<code>map</code>	a map widget
<code>data</code>	data must be a POINT Simple Feature or a list of POINT Simple Feature's with a time column.
<code>time</code>	The column name of the time column. Default is "time".
<code>icon</code>	an icon which can be created with makeIcon
<code>pathOpts</code>	style the CircleMarkers with pathOptions
<code>popup</code>	A formula with the column names for the popup content
<code>label</code>	A formula with the column names for the label content
<code>popupOptions</code>	A Vector of popupOptions to provide popups
<code>labelOptions</code>	A Vector of labelOptions to provide label options for each label. Default NULL
<code>options</code>	List of additional options. See playbackOptions
<code>name</code>	A formula with the column names for the feature name

Value

the new `map` object

Note

If used in Shiny, you can listen to 2 events

- 'map-ID'+'_pb_mouseover"
- 'map-ID'+'_pb_click"

References

<https://github.com/hallahan/LeafletPlayback>

See Also

Other Playback Functions: [playbackOptions\(\)](#), [removePlayback\(\)](#)

Examples

```

## Not run:
library(leaflet)
library(leaflet.extras)
library(sf)

```

```

## Single Elements
data <- sf::st_as_sf(leaflet::atlStorms2005[1,])
data <- st_cast(data, "POINT")
data$time = as.POSIXct(
  seq.POSIXt(Sys.time() - 1000, Sys.time(), length.out = nrow(data)))
data$label <- as.character(data$time)

leaflet() %>%
  addTiles() %>%
  addPlayback(data = data, label = ~label,
              popup = ~sprintf("I am a popup for <b>%s</b> and <b>%s</b>",
                               Name, label),
              popupOptions = popupOptions(offset = c(0, -35)),
              options = playbackOptions(radius = 3,
                                         tickLen = 36000,
                                         speed = 50,
                                         maxInterpolationTime = 1000),
              pathOpts = pathOptions(weight = 5))

## Multiple Elements
data <- sf::st_as_sf(leaflet::atlStorms2005[1:5])
data$name <- as.character(data$name)
data <- st_cast(data, "POINT")
data$time <- unlist(lapply(rle(data$name)$lengths, function(x) {
  seq.POSIXt(as.POSIXct(Sys.Date())-2), as.POSIXct(Sys.Date()), length.out = x
}))
data$time <- as.POSIXct(data$time, origin="1970-01-01")
data$label <- paste0("Time: ", data$time)
data$popup = sprintf("<h3>Customized Popup</h3><b>Name</b>: %s<br><b>Time</b>: %s",
                     data$name, data$time)
data <- split(data, f = data$name)

leaflet() %>%
  addTiles() %>%
  addPlayback(data = data,
              popup = ~popup,
              label = ~label,
              popupOptions = popupOptions(offset=c(0,-35)),
              labelOptions = labelOptions(noHide = TRUE),
              options = playbackOptions(radius = 3,
                                         tickLen = 1000000,
                                         speed = 5000,
                                         maxInterpolationTime = 10000,
                                         transitionpopup = FALSE,
                                         transitionlabel = FALSE,
                                         playCommand = "Let's go",
                                         stopCommand = "Stop it!",
                                         color = c("red","green","blue",
                                                   "orange","yellow")),
              pathOpts = pathOptions(weight = 5))

## End(Not run)

```

`addReachability` *Add Isochrones to Leaflet*

Description

A leaflet plugin which shows areas of reachability based on time or distance for different modes of travel using the openrouteservice isochrones API. Based on the [leaflet.reachability](#) plugin

Usage

```
addReachability(map, apikey = NULL, options = reachabilityOptions())
```

Arguments

<code>map</code>	a map widget
<code>apikey</code>	a valid Openrouteservice API-key. Can be obtained from Openrouteservice
<code>options</code>	A list of further options. See reachabilityOptions

Value

the new map object

Note

When used in Shiny, 3 events update a certain shiny Input:

1. `reachability:displayed` updates `input$MAPID_reachability_displayed`
2. `reachability:delete` updates `input$MAPID_reachability_delete`
3. `reachability:error` updates `input$MAPID_reachability_error`

References

<https://github.com/traffordDataLab/leaflet.reachability>

See Also

Other Reachability Functions: [reachabilityOptions\(\)](#), [removeReachability\(\)](#)

Examples

```
## Not run:
library(leaflet)
library(leaflet.extras2)

Sys.setenv("OPRS" = 'Your_API_Key')

leaflet() %>%
  addTiles() %>%
```

```
setView(8, 50, 10) %>%  
addReachability()  
  
## End(Not run)
```

addSidebar*Add a Sidebar Leaflet Control*

Description

The sidebar HTML must be created with `sidebar_tabs` and `sidebar_pane` before `leafletOutput` is called.

Usage

```
addSidebar(map, id = "sidebar", options = list(position = "left"), ns = NULL)
```

Arguments

map	A leaflet map widget
id	Id of the sidebar-div. Must match with the id of <code>sidebar_tabs</code>
options	A named list with the only option position, which should be either left or right.
ns	The namespace function, if used in Shiny modules.

Value

the new map object

References

<https://github.com/Turbo87/sidebar-v2>

See Also

Other Sidebar Functions: `closeSidebar()`, `openSidebar()`, `removeSidebar()`, `sidebar_pane()`, `sidebar_tabs()`

Examples

```
## Not run:  
library(shiny)  
  
# run example app showing a single sidebar  
runApp(paste0(system.file("examples", package = "leaflet.extras2"),  
             "/sidebar_app.R"))  
  
# run example app showing two sidebars
```

```
runApp(paste0(system.file("examples", package = "leaflet.extras2"),
              "/multi_sidebar_app.R"))

## End(Not run)
```

`addSidebyside` *Add Side by Side View*

Description

A Leaflet control to add a split screen to compare two map overlays. The plugin works with Panes, see the example.

Usage

```
addSidebyside(
  map,
  layerId = NULL,
  leftId = NULL,
  rightId = NULL,
  options = list(thumbSize = 42, padding = 0)
)
```

Arguments

<code>map</code>	a map widget
<code>layerId</code>	the layer id, needed for removeSidebyside
<code>leftId</code>	the <code>layerId</code> of the Tile layer that should be visible on the left side
<code>rightId</code>	the <code>layerId</code> of the Tile layer that should be visible on the right side
<code>options</code>	A list of options. Currently only <code>thumbSize</code> and <code>padding</code> can be changed.

Value

the new map object

Note

It is currently not working correctly if the `baseGroups` are defined in [addLayersControl](#).

References

<https://github.com/digidem/leaflet-side-by-side>

See Also

Other Sidebyside Functions: [removeSidebyside\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras2)

leaflet(quakes) %>%
  addMapPane("left", zIndex = 0) %>%
  addMapPane("right", zIndex = 0) %>%
  addTiles(group = "base", layerId = "baseid",
           options = pathOptions(pane = "right")) %>%
  addProviderTiles(providers$CartoDB.DarkMatter, group="carto", layerId = "cartoid",
                   options = pathOptions(pane = "left")) %>%
  addCircleMarkers(data = breweries91[1:15,], color = "blue", group = "blue",
                    options = pathOptions(pane = "left")) %>%
  addCircleMarkers(data = breweries91[15:20,], color = "yellow", group = "yellow") %>%
  addCircleMarkers(data = breweries91[15:30,], color = "red", group = "red",
                    options = pathOptions(pane = "right")) %>%
  addLayersControl(overlayGroups = c("blue", "red", "yellow")) %>%
  addSidebyside(layerId = "sidecontrols",
                 rightId = "baseid",
                 leftId = "cartoid")
```

addSpinner

Add Spin Plugin

Description

Adds an animated loading spinning over the map.

Usage

```
addSpinner(map)

startSpinner(map, options = NULL)

stopSpinner(map)
```

Arguments

map	A map widget object created from leaflet
options	Spin.js options. Named list. See http://spin.js.org

Value

A leaflet map object

References

<https://github.com/makinacorpus/Leaflet.Spin>
<https://github.com/fgnass/spin.js>

Examples

```
library(leaflet)
library(leaflet.extras2)

leaflet(data = quakes) %>%
  addTiles() %>%
  addSpinner() %>%
  startSpinner(options = list("lines" = 7, "length" = 20)) %>%
  addMarkers(~long, ~lat, popup = ~as.character(mag), label = ~as.character(mag)) %>%
  stopSpinner()
```

addTangram

Adds a Tangram layer to a Leaflet map in a Shiny App.

Description

Adds a Tangram layer to a Leaflet map in a Shiny App.

Usage

```
addTangram(map, scene = NULL, layerId = NULL, group = NULL, options = NULL)
```

Arguments

<code>map</code>	A leaflet map widget
<code>scene</code>	Path to a required .yaml or .zip file. If the file is within the /www folder of a Shiny-App, only the filename must be given, otherwise the full path is needed. See the Tangram repository or the Tangram docs for further information on how to edit such a .yaml file.
<code>layerId</code>	A layer ID
<code>group</code>	The name of the group the newly created layer should belong to (for <code>clearGroup</code> and <code>addLayersControl</code> purposes).
<code>options</code>	A list of further options. See the app in the examples/tangram folder or the docs for further information.

Value

the new map object

Note

Only works correctly in a Shiny-App environment.

References

<https://github.com/tangrams/tangram>

Examples

```
## Not run:
library(shiny)
library(leaflet)
library(leaflet.extras2)

## In the /www folder of a ShinyApp. Must contain the Nextzen API-key
scene <- "scene.yaml"

ui <- fluidPage(leafletOutput("map"))

server <- function(input, output, session) {
  output$map <- renderLeaflet({
    leaflet() %>%
      addTiles(group = "base") %>%
      addTangram(scene = scene, group = "tangram") %>%
      addCircleMarkers(data = breweries91, group = "brews") %>%
      setView(11, 49.4, 14) %>%
      addLayersControl(baseGroups = c("tangram", "base"),
                      overlayGroups = c("brews"))
  })
}

shinyApp(ui, server)

## End(Not run)
```

addTimeslider

Add Time Slider to Leaflet

Description

The [LeafletSlider plugin](#) enables you to dynamically add and remove Markers/Lines on a map by using a JQuery UI slider.

Usage

```
addTimeslider(
  map,
  data,
  radius = 10,
  stroke = TRUE,
  color = "#03F",
  weight = 5,
  opacity = 0.5,
  fill = TRUE,
  fillColor = color,
  fillOpacity = 0.2,
```

```

    dashArray = NULL,
    popup = NULL,
    popupOptions = NULL,
    label = NULL,
    labelOptions = NULL,
    ordertime = TRUE,
    options = timesliderOptions()
)

```

Arguments

<code>map</code>	a map widget
<code>data</code>	data must be a Simple Feature collection of type POINT or LINESTRING with a column of class Date or POSIXct.
<code>radius</code>	a numeric vector of radii for the circles; it can also be a one-sided formula, in which case the radius values are derived from the data (units in meters for circles, and pixels for circle markers)
<code>stroke</code>	whether to draw stroke along the path (e.g. the borders of polygons or circles)
<code>color</code>	stroke color
<code>weight</code>	stroke width in pixels
<code>opacity</code>	stroke opacity (or layer opacity for tile layers)
<code>fill</code>	whether to fill the path with color (e.g. filling on polygons or circles)
<code>fillColor</code>	fill color
<code>fillOpacity</code>	fill opacity
<code>dashArray</code>	a string that defines the stroke dash pattern
<code>popup</code>	a character vector of the HTML content for the popups (you are recommended to escape the text using <code>htmlEscape()</code> for security reasons)
<code>popupOptions</code>	A Vector of <code>popupOptions</code> to provide popups
<code>label</code>	a character vector of the HTML content for the labels
<code>labelOptions</code>	A Vector of <code>labelOptions</code> to provide label options for each label. Default NULL
<code>ordertime</code>	boolean value indicating whether to order the data by the time column. The slider will adopt the order of the timestamps. The default is TRUE.
<code>options</code>	List of additional options. See <code>timesliderOptions</code>

Value

the new map object

References

<https://github.com/dwilhelm89/LeafletSlider>

See Also

Other Timeslider Functions: `removeTimeslider()`, `timesliderOptions()`

Examples

```
## Not run:
library(leaflet)
library(leaflet.extras2)
library(sf)
library(geojsonsf)

data <- sf::st_as_sf(leaflet::atlStorms2005[1,])
data <- st_cast(data, "POINT")
data$time = as.POSIXct(
  seq.POSIXt(Sys.time() - 1000, Sys.time(), length.out = nrow(data)))

leaflet() %>%
  addTiles() %>%
  addTimeslider(data = data,
    options = timesliderOptions(
      position = "topright",
      timeAttribute = "time",
      range = TRUE)) %>%
  setView(-72, 22, 4)

## End(Not run)
```

addVelocity

Add Velocity Animation

Description

Add velocity animated data to leaflet. Based on the [leaflet-velocity plugin](#)

Usage

```
addVelocity(
  map,
  layerId = NULL,
  group = NULL,
  content = NULL,
  options = velocityOptions()
)
```

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>layerId</code>	the layer id
<code>group</code>	the name of the group the newly created layers should belong to (for clearGroup and addLayersControl purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.

content	the path or URL to a JSON file representing the velocity data or a data.frame which can be transformed to such a JSON file. Please see the demo files for some example data.
options	List of further options. See velocityOptions

Value

the new map object

References

<https://github.com/onaci/leaflet-velocity>

See Also

Other Velocity Functions: [removeVelocity\(\)](#), [setOptionsVelocity\(\)](#), [velocityOptions\(\)](#)

Examples

```
## Not run:
library(leaflet)
library(leaflet.extras2)
content <- "https://raw.githubusercontent.com/onaci/leaflet-velocity/master/demo/water-gbr.json"
leaflet() %>%
  addTiles(group = "base") %>%
  setView(145, -20, 4) %>%
  addVelocity(content = content, group = "velo", layerId = "veloid") %>%
  addLayersControl(baseGroups = "base", overlayGroups = "velo")

## End(Not run)
```

Description

A Leaflet plugin for working with Web Map services, providing: single-tile/untiled/nontiled layers, shared WMS sources, and **GetFeatureInfo**-powered identify.

You can also use **CQL-Filters** by appending a string to the 'baseUrl'.

Something like 'http://server/wms?cql_filter=attribute=value'

Usage

```
addWMS(
  map,
  baseUrl,
  layerId = NULL,
  group = NULL,
```

```

options = WMSTileOptions(),
attribution = NULL,
layers = NULL,
popupOptions = NULL,
checkempty = FALSE,
data = getMapData(map)
)

```

Arguments

map	a map widget object created from leaflet()
baseUrl	a base URL of the WMS service
layerId	the layer id
group	the name of the group the newly created layers should belong to (for clearGroup and addLayersControl purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
options	a list of extra options for tile layers, popups, paths (circles, rectangles, polygons, ...), or other map elements
attribution	the attribution text of the tile layer (HTML)
layers	comma-separated list of WMS layers to show
popupOptions	List of popup options. See popupOptions . Default is NULL.
checkempty	Should the returned HTML-content be checked for emptiness? If the HTML-body is empty no popup is opened. Default is FALSE
data	the data object from which the argument values are derived; by default, it is the data object provided to leaflet() initially, but can be overridden

Value

the new map object

References

<https://github.com/heigeo/leaflet.wms>

Examples

```

library(leaflet)
library(leaflet.extras2)

leaflet() %>%
  addTiles(group = "base") %>%
  setView(9, 50, 5) %>%
  addWMS(baseUrl = "https://maps.dwd.de/geoserver/dwd/wms",
         layers = "dwd:BRD_1km_winddaten_10m",
         popupOptions = popupOptions(maxWidth = 600),

```

```
checkempty = TRUE,
options = WMSTileOptions(
  transparent = TRUE,
  format = "image/png",
  info_format = "text/html"))
```

antpathOptions*Antpath Options***Description**

Additional list of options for 'ant-path' animated polylines.

Usage

```
antpathOptions(
  delay = 400,
  paused = FALSE,
  reverse = FALSE,
  hardwareAccelerated = FALSE,
  dashArray = c(10, 20),
  pulseColor = "#ffffff",
  lineCap = NULL,
  lineJoin = NULL,
  interactive = TRUE,
  pointerEvents = NULL,
  className = ""
)
```

Arguments

<code>delay</code>	Add a delay to the animation flux. Default is 400
<code>paused</code>	Should the animation be paused. Default is FALSE
<code>reverse</code>	Defines if the flow follows the path order or not. Default is FALSE
<code>hardwareAccelerated</code>	Makes the animation run with hardware acceleration. Default is FALSE
<code>dashArray</code>	The size of the animated dashes. Default is c(10, 20)
<code>pulseColor</code>	Adds a color to the dashed flux. Default is #ffffff
<code>lineCap</code>	a string that defines shape to be used at the end of the stroke
<code>lineJoin</code>	a string that defines shape to be used at the corners of the stroke
<code>interactive</code>	whether the element emits mouse events
<code>pointerEvents</code>	sets the pointer-events attribute on the path if SVG backend is used
<code>className</code>	a CSS class name set on an element

Value

A list of options for addAntpath animated polylines

See Also

Other Antpath Functions: [addAntpath\(\)](#), [clearAntpath\(\)](#), [removeAntpath\(\)](#)

arrowheadOptions *Arrowhead Options*

Description

Additional list of options for polylines with arrowheads. You can also pass options inherited from [L.Path](#)

Usage

```
arrowheadOptions(  
  yawn = 60,  
  size = "15%",  
  frequency = "allvertices",  
  proportionalToTotal = FALSE,  
  offsets = NULL,  
  perArrowheadOptions = NULL,  
  ...  
)
```

Arguments

yawn	Defines the width of the opening of the arrowhead, given in degrees. The larger the angle, the wider the arrowhead.
size	Determines the size of the arrowhead. Accepts three types of values: <ul style="list-style-type: none">• A string with the suffix 'm', i.e. '500m' will set the size of the arrowhead to that number of meters.• A string with the suffix '%', i.e. '15%' will render arrows whose size is that percentage of the size of the parent polyline. If the polyline has multiple segments, it will take the percent of the average size of the segments.• A string the suffix 'px', i.e. '20px' will render an arrowhead whose size stays at a constant pixel value, regardless of zoom level. Will look strange at low zoom levels or for smaller parent vectors. Ideal for larger parent vectors and at higher zoom levels.
frequency	How many arrowheads are rendered on a polyline. <ul style="list-style-type: none">• 'allvertices' renders an arrowhead on each vertex.• 'endonly' renders only one at the end.

- A numeric value renders that number of arrowheads evenly spaced along the polyline.
- A string with suffix 'm', i.e. '100m' will render arrowheads spaced evenly along the polyline with roughly that many meters between each one.
- A string with suffix 'px', i.e. '30px' will render arrowheads spaced evenly with roughly that many pixels between each, regardless of zoom level.

proportionalToTotal

Only relevant when size is given as a percent. Useful when frequency is set to 'endonly'. Will render the arrowheads with a size proportional to the entire length of the multi-segmented polyline, rather than proportional to the average length of all the segments.

offsets

Enables the developer to have the arrowheads start or end at some offset from the start and/or end of the polyline. This option can be a list with 'start' and 'end' names. The values must be strings defining the size of the offset in either meters or pixels, i.e. list('start' = '100m', 'end' = '15px').

perArrowheadOptions

Enables the developer to customize arrowheads on a one-by-one basis. Must be in the form of a function of i, which is the index of the arrowhead as it is rendered in the loop through all arrowheads. Must return an options object. Cannot account for frequency or proportionalToTotal from within the perArrowheadOptions callback. See the example for details.

...

Additional options for arrowheads, inherited from [L.Path](#)

Value

A list of options for addArrowhead polylines

References

<https://github.com/slutske22/leaflet-arrowheads#options>

See Also

Other Arrowhead Functions: [addArrowhead\(\)](#), [clearArrowhead\(\)](#), [removeArrowhead\(\)](#)

[clearAntpath](#)

clearAntpath

Description

Clear all Antpaths

Usage

`clearAntpath(map)`

Arguments

map	a map widget object, possibly created from leaflet() but more likely from leafletProxy()
-----	--

Value

the new map object

See Also

Other Antpath Functions: [addAntpath\(\)](#), [antpathOptions\(\)](#), [removeAntpath\(\)](#)

clearArrowhead

Remove arrowheads from Lines by group

Description

Remove arrowheads from Lines by group

Usage

`clearArrowhead(map, group)`

Arguments

map	the map
group	A group name

Value

A modified leaflet map

See Also

Other Arrowhead Functions: [addArrowhead\(\)](#), [arrowheadOptions\(\)](#), [removeArrowhead\(\)](#)

`clearFuture`*clearFuture***Description**

Resets the stack of future items.

Usage

```
clearFuture(map)
```

Arguments

`map` a map widget object created from [leafletProxy](#)

Value

the new map object

References

<https://github.com/cscott530/leaflet-history>

See Also

Other History Functions: [addHistory\(\)](#), [clearHistory\(\)](#), [goBackHistory\(\)](#), [goForwardHistory\(\)](#), [historyOptions\(\)](#)

`clearHexbin`*clearHexbin***Description**

Clears the data of the hexbinLayer.

Usage

```
clearHexbin(map)
```

Arguments

`map` The map widget

Value

the new map object

See Also

Other Hexbin-D3 Functions: [addHexbin\(\)](#), [hexbinOptions\(\)](#), [hideHexbin\(\)](#), [showHexbin\(\)](#), [updateHexbin\(\)](#)

`clearHistory`

clearHistory

Description

Resets the stack of history items.

Usage

`clearHistory(map)`

Arguments

`map` a map widget object created from [leafletProxy](#)

Value

the new map object

References

<https://github.com/cscott530/leaflet-history>

See Also

Other History Functions: [addHistory\(\)](#), [clearFuture\(\)](#), [goBackHistory\(\)](#), [goForwardHistory\(\)](#), [historyOptions\(\)](#)

`closeSidebar`

Close the Sidebar

Description

Close the Sidebar

Usage

`closeSidebar(map, sidebar_id = NULL)`

Arguments

<code>map</code>	A leaflet map widget
<code>sidebar_id</code>	The id of the sidebar (per sidebar_tabs). Defaults to NULL such that the first sidebar is used.

Value

the new map object

See Also

Other Sidebar Functions: [addSidebar\(\)](#), [openSidebar\(\)](#), [removeSidebar\(\)](#), [sidebar_pane\(\)](#), [sidebar_tabs\(\)](#)

`context_mapmenuItems` *context_mapmenuItems*

Description

`context_mapmenuItems`

Usage

`context_mapmenuItems(...)`

Arguments

`...` contextmenu item/s

Value

A list of `context_menuItem` for the map

See Also

Other Contextmenu Functions: [addContextMenu\(\)](#), [addItemContextMenu\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextMenu\(\)](#), [removeallItemsContextMenu\(\)](#), [setDisabledContextMenu\(\)](#), [showContextMenu\(\)](#)

context_markermenuItems
context_markermenuItems

Description

context_markermenuItems

Usage

```
context_markermenuItems(...)
```

Arguments

... contextmenu item/s

Value

A list of `context_menuItem` for markers

See Also

Other Contextmenu Functions: [addContextMenu\(\)](#), [addItemContextMenu\(\)](#), [context_mapmenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextMenu\(\)](#), [removeallItemsContextMenu\(\)](#), [setDisabledContextMenu\(\)](#), [showContextMenu\(\)](#)

context_menuItem *context_menuItem*

Description

context_menuItem

Usage

```
context_menuItem(text, callback = NULL, ...)
```

Arguments

<code>text</code>	The label to use for the menu item
<code>callback</code>	A callback function to be invoked when the menu item is clicked. The callback is passed an object with properties identifying the location the menu was opened at: <code>latlng</code> , <code>layerPoint</code> and <code>containerPoint</code> . The callback-function must be valid JavaScript and will be wrapped in JS .
...	For further options please visit https://github.com/araccliffe/Leaflet.contextmenu

Value

A contextmenu item list

See Also

Other Contextmenu Functions: [addContextMenu\(\)](#), [addItemContextMenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextMenu\(\)](#), [removeallItemsContextMenu\(\)](#), [setDisabledContextMenu\(\)](#), [showContextMenu\(\)](#)

`disableContextMenu` *disableContextMenu*

Description

Disable the contextmenu

Usage

`disableContextMenu(map)`

Arguments

`map` a map widget object created from [leaflet](#)

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextMenu\(\)](#), [addItemContextMenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextMenu\(\)](#), [removeallItemsContextMenu\(\)](#), [setDisabledContextMenu\(\)](#), [showContextMenu\(\)](#)

easyprintMap

easyprintMap

Description

Print or export a map programmatically (e.g. in a Shiny environment).

Usage

```
easyprintMap(map, sizeModes = "A4Portrait", filename = "map")
```

Arguments

map	the map widget
sizeModes	Must match one of the given sizeMode names in easyprintOptions . The options are: CurrentSize, A4Portrait or A4Landscape. If you want to print the map with a Custom sizeMode you need to pass the Custom className. Default is A4Portrait
filename	Name of the file if exportOnly option is TRUE.

Value

A leaflet map object

See Also

Other EasyPrint Functions: [addEasyprint\(\)](#), [easyprintOptions\(\)](#), [removeEasyprint\(\)](#)

Examples

```
## Only run examples in interactive R sessions
if (interactive()) {
  library(shiny)
  library(leaflet)
  library(leaflet.extras2)

  ui <- fluidPage(
    leafletOutput("map"),
    selectInput("scene", "Select Scene", choices = c("CurrentSize", "A4Landscape", "A4Portrait")),
    actionButton("print", "Print Map")
  )

  server <- function(input, output, session) {
    output$map <- renderLeaflet({
      input$print
      leaflet() %>%
        addTiles() %>%
        setView(10, 50, 9) %>%
    })
  }
}
```

```

    addEasyprint(options = easyprintOptions(
      exportOnly = TRUE
    )))
  })
  observeEvent(input$print, {
    leafletProxy("map") %>%
      easyprintMap(sizeModes = input$scene)
  })
}

shinyApp(ui, server)
}

```

easyprintOptions *easyprintOptions*

Description

Create a list of further options for the easyprint plugin.

Usage

```

easyprintOptions(
  title = "Print map",
  position = "topleft",
  sizeModes = list("A4Portrait", "A4Landscape", "CurrentSize"),
  defaultSizeTitles = NULL,
  exportOnly = FALSE,
  tileLayer = NULL,
  tileWait = 500,
  filename = "map",
  hidden = FALSE,
  hideControlContainer = TRUE,
  hideClasses = NULL,
  customWindowTitle = NULL,
  spinnerBgColor = "#0DC5C1",
  customSpinnerClass = "epLoader"
)

```

Arguments

<code>title</code>	Sets the text which appears as the tooltip of the print/export button
<code>position</code>	Positions the print button
<code>sizeModes</code>	Either a character vector with one of the following options: <code>CurrentSize</code> , <code>A4Portrait</code> , <code>A4Landscape</code> . If you want to include a Custom size mode you need to pass a named list, with <code>width</code> , <code>height</code> , <code>name</code> and <code>className</code> and assign a background-image in CSS. See the example in <code>./inst/examples/easyprint_app.R</code> .

defaultSizeTitles	Button tooltips for the default page sizes
exportOnly	If set to TRUE the map is exported to a .png file
tileLayer	The group name of one tile layer that you can wait for to draw (helpful when resizing)
tileWait	How long to wait for the tiles to draw (helpful when resizing)
filename	Name of the file if exportOnly option is TRUE
hidden	Set to TRUE if you don't want to display the toolbar. Instead you can create your own buttons or fire print events programmatically.
hideControlContainer	Hides the leaflet controls like the zoom buttons and the attribution on the print out
hideClasses	Use a character vector or list of CSS-classes to hide on the output image.
customWindowTitle	A title for the print window which will get added to the printed paper
spinnerBgColor	A valid css colour for the spinner background color
customSpinnerClass	A class for a custom css spinner to use while waiting for the print.

Value

A list of options for the 'easyprint' control

References

<https://github.com/rowanwins/leaflet-easyPrint>

See Also

Other EasyPrint Functions: [addEasyprint\(\)](#), [easyprintMap\(\)](#), [removeEasyprint\(\)](#)

enableContextMenu *enableContextMenu*

Description

Enable the contextmenu

Usage

`enableContextMenu(map)`

Arguments

map	a map widget object created from leaflet
-----	--

Value

A leaflet map object

See Also

Other Contextmenu Functions: `addContextmenu()`, `addItemContextmenu()`, `context_mapmenuItems()`, `context_markermenuItems()`, `context_menuItem()`, `disableContextMenu()`, `hideContextMenu()`, `insertItemContextMenu()`, `mapmenuItems()`, `markermenuItems()`, `menuItem()`, `removeItemContextMenu()`, `removeallItemsContextMenu()`, `setDisabledContextMenu()`, `showContextMenu()`

`gibs_layers`

The available GIBS layers with attributes

Description

The available GIBS layers with attributes

Usage

`gibs_layers`

Format

An object of class `data.frame` with 276 rows and 4 columns.

`goBackHistory`

goBackHistory

Description

If possible, will go to previous map extent. Pushes current extent to the "future" stack.

Usage

`goBackHistory(map)`

Arguments

`map` a map widget object created from `leafletProxy`

Value

the new map object

References

<https://github.com/cscott530/leaflet-history>

See Also

Other History Functions: [addHistory\(\)](#), [clearFuture\(\)](#), [clearHistory\(\)](#), [goForwardHistory\(\)](#), [historyOptions\(\)](#)

goForwardHistory

goForwardHistory

Description

If possible, will go to next map extent. Pushes current extent to the "back" stack.

Usage

`goForwardHistory(map)`

Arguments

`map` a map widget object created from [leafletProxy](#)

Value

the new map object

References

<https://github.com/cscott530/leaflet-history>

See Also

Other History Functions: [addHistory\(\)](#), [clearFuture\(\)](#), [clearHistory\(\)](#), [goBackHistory\(\)](#), [historyOptions\(\)](#)

heightgraphOptions

heightgraphOptions

Description

Customize the heightgraph with the following additional options.

Usage

```
heightgraphOptions(
  position = c("bottomright", "topleft", "topright", "bottomleft"),
  width = 800,
  height = 200,
  margins = list(top = 10, right = 30, bottom = 55, left = 50),
  expand = TRUE,
  expandCallback = NULL,
  mappings = NULL,
  highlightStyle = list(color = "red"),
  translation = NULL,
  xTicks = 3,
  yTicks = 3
)
```

Arguments

<code>position</code>	position of control: "topleft", "topright", "bottomleft", or "bottomright". Default is <code>bottomright</code> .
<code>width</code>	The width of the expanded heightgraph display in pixels. Default is <code>800</code> .
<code>height</code>	The height of the expanded heightgraph display in pixels. Default is <code>200</code> .
<code>margins</code>	The margins define the distance between the border of the heightgraph and the actual graph inside. You are able to specify margins for top, right, bottom and left in pixels. Default is <code>list(top = 10, right = 30, bottom = 55, left = 50)</code> .
<code>expand</code>	Boolean value that defines if the heightgraph should be expanded on creation. Default is <code>200</code> .
<code>expandCallback</code>	Function to be called if the heightgraph is expanded or reduced. The state of the heightgraph is passed as an argument. It is <code>TRUE</code> when expanded and <code>FALSE</code> when reduced. Default is <code>NULL</code> .
<code>mappings</code>	You may add a <code>mappings</code> object to customize the colors and labels in the height graph. Without adding custom mappings the segments and labels within the graph will be displayed in random colors. Each key of the object must correspond to the summary key in properties within the FeatureCollection. Default is <code>NULL</code> .
<code>highlightStyle</code>	You can customize the highlight style when using the horizontal line to find parts of the route above an elevation value. Use any Leaflet Path options as value of the <code>highlightStyle</code> parameter. Default is <code>list(color = "red")</code> .
<code>translation</code>	You can change the labels of the heightgraph info field by passing translations for <code>distance</code> , <code>elevation</code> , <code>segment_length</code> , <code>type</code> and <code>legend</code> . Default is <code>NULL</code> .
<code>xTicks</code>	Specify the tick frequency in the x axis of the graph. Corresponds approximately to 2 to the power of value ticks. Default is 3.
<code>yTicks</code>	Specify the tick frequency in the y axis of the graph. Corresponds approximately to 2 to the power of value ticks. Default is 3.

Value

A list of further options for addHeightgraph

See Also

Other Heightgraph Functions: [addHeightgraph\(\)](#)

hexbinOptions

hexbinOptions

Description

A list of options for customizing the appearance/behavior of the hexbin layer.

Usage

```
hexbinOptions(  
  duration = 200,  
  colorScaleExtent = NULL,  
  radiusScaleExtent = NULL,  
  colorRange = c("#f7fbff", "#08306b"),  
  radiusRange = c(5, 15),  
  pointerEvents = "all",  
  resizetoCount = FALSE,  
  tooltip = "Count"  
)
```

Arguments

duration	Transition duration for the hexbin layer
colorScaleExtent	extent of the color scale for the hexbin layer. This is used to override the derived extent of the color values and is specified as a vector of the form c(min= numeric, max= numeric). Can be a numeric vector or a custom JS array, like (JS("[40, undefined]"))
radiusScaleExtent	This is the same exact configuration option as colorScaleExtent, only applied to the radius extent.
colorRange	Sets the range of the color scale used to fill the hexbins on the layer.
radiusRange	Sets the range of the radius scale used to size the hexbins on the layer.
pointerEvents	This value is passed directly to an element-level css style for pointer-events. You should only modify this config option if you want to change the mouse event behavior on hexbins. This will modify when the events are propagated based on the visibility state and/or part of the hexbin being hovered.

<code>resizetoCount</code>	Resizes the hexbin to the count. Default is FALSE. If set to TRUE it will resize based on the amount of underlying elements. You can also pass a custom JS function.
<code>tooltip</code>	Should tooltips be displayed? If set to TRUE, it will show the amount of underlying elements. If a string is given, it will append the string before the count. To disable tooltips, please pass NULL or FALSE. You can also pass a custom JS function.

Value

A list of hexbin-specific options

See Also

Other Hexbin-D3 Functions: [addHexbin\(\)](#), [clearHexbin\(\)](#), [hideHexbin\(\)](#), [showHexbin\(\)](#), [updateHexbin\(\)](#)

hideContextMenu

hideContextMenu

Description

Hide the contextmenu

Usage

`hideContextMenu(map)`

Arguments

`map` a map widget object created from [leaflet](#)

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextMenu\(\)](#), [addItemContextMenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextMenu\(\)](#), [removeallItemsContextMenu\(\)](#), [setDisabledContextMenu\(\)](#), [showContextMenu\(\)](#)

hideHexbin

hideHexbin

Description

Hide the hexbinLayer.

Usage

```
hideHexbin(map)
```

Arguments

map	The map widget
-----	----------------

Value

the new map object

See Also

Other Hexbin-D3 Functions: [addHexbin\(\)](#), [clearHexbin\(\)](#), [hexbinOptions\(\)](#), [showHexbin\(\)](#), [updateHexbin\(\)](#)

historyOptions

History Options

Description

History Options

Usage

```
historyOptions(  
  position = c("topright", "topleft", "bottomleft", "bottomright"),  
  maxMovesToSave = 10,  
  backImage = "fa fa-caret-left",  
  forwardImage = "fa fa-caret-right",  
  backText = "",  
  forwardText = "",  
  backTooltip = "Go to Previous Extent",  
  forwardTooltip = "Go to Next Extent",  
  backImageBeforeText = TRUE,  
  forwardImageBeforeText = FALSE,  
  orientation = c("horizontal", "vertical"),  
  shouldSaveMoveInHistory = NULL  
)
```

Arguments

<code>position</code>	Set the position of the History control. Default is <code>topright</code> .
<code>maxMovesToSave</code>	Number of moves in the history to save before clearing out the oldest. Default value is 10, use 0 or a negative number to make unlimited.
<code>backImage</code>	The class for the ‘back’ button icon. Default is “fa fa-caret-left”.
<code>forwardImage</code>	The class for the ‘forward’ button icon. Default is “fa fa-caret-right”.
<code>backText</code>	The text in the buttons. Default is “”.
<code>forwardText</code>	The text in the buttons. Default is “”.
<code>backTooltip</code>	Tooltip content. Default is “Go to Previous Extent”.
<code>forwardTooltip</code>	Tooltip content. Default is “Go to Next Extent”.
<code>backImageBeforeText</code>	When both text and image are present, whether to show the image first or the text first (left to right). Default is TRUE
<code>forwardImageBeforeText</code>	When both text and image are present, whether to show the image first or the text first (left to right). Default is FALSE
<code>orientation</code>	Whether to position the buttons on top of one another or side-by-side. Default is <code>horizontal</code>
<code>shouldSaveMoveInHistory</code>	A JS callback you can provide that gets called with every move. return false to not save a move.

Value

A list of further options for `addHistory`

References

<https://github.com/cscott530/leaflet-history>

See Also

Other History Functions: `addHistory()`, `clearFuture()`, `clearHistory()`, `goBackHistory()`, `goForwardHistory()`

Examples

```
library(leaflet)
leaflet() %>%
  addTiles() %>%
  addHistory(options = historyOptions(position = "bottomright",
    maxMovesToSave = 20,
    backText = "Go back",
    forwardText = "Go forward",
    orientation = "vertical"
  ))
```

```
insertItemContextmenu  insertItemContextmenu
```

Description

Insert a new contextmenu menu item at a specific index

Usage

```
insertItemContextmenu(map, option, index)
```

Arguments

map	a map widget object created from leaflet
option	new menu item to add
index	Index of the contextmenu. (NOTE: Since the index is passed to JavaScript, it is zero-based)

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextMenu\(\)](#), [addItemContextMenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextMenu\(\)](#), [removeallItemsContextMenu\(\)](#), [setDisabledContextMenu\(\)](#), [showContextMenu\(\)](#)

isSynced	<i>Is a map synchronized?</i>
----------	-------------------------------

Description

Is a map synchronized with any or a specific map? Invoking this method sets a Shiny input that returns TRUE when the map is synchronized with another map. If syncwith is set, TRUE is returned if the map is synchronized exactly with that other map.

Usage

```
isSynced(map, id = NULL, syncwith = NULL)
```

Arguments

<code>map</code>	the map
<code>id</code>	The map id
<code>syncwith</code>	Is the map synchronized with one of these maps?

Details

The Siny input name is combined of the map-id and "_synced". For a map with id `map1` the input can be retrieved with `input$map1_synced`.

Value

A map

See Also

Other leafletsync Functions: [addLeafletsyncDependency\(\)](#), [addLeafletsync\(\)](#), [leafletsyncOptions\(\)](#), [unsync\(\)](#)

`leaflet.extras2`

leaflet.extras2: Extra Functionality for 'leaflet' Package.

Description

This package serves as an add-on to the 'leaflet' package by providing extra functionality via 'leaflet' plugins.

`leafletsyncOptions`

leafletsync Options

Description

Additional list of options.

Usage

```
leafletsyncOptions(
  noInitialSync = FALSE,
  syncCursor = TRUE,
  offsetFn = JS("function (center, zoom, refMap, tgtMap) { return center; }")
)
```

Arguments

noInitialSync	Setting to TRUE disables initial synchronization of the maps. The default is FALSE.
syncCursor	The default TRUE adds a circle marker on the synced map.
offsetFn	A JavaScript-function to compute an offset for the center.

Value

A list of options for addLeafletsync

See Also

Other leafletsync Functions: [addLeafletsyncDependency\(\)](#), [addLeafletsync\(\)](#), [isSynced\(\)](#), [unsync\(\)](#)

makeMapkeyIcon

Make Mapkey Icon

Description

Make Mapkey Icon

Usage

```
makeMapkeyIcon(  
    icon = "mapkey",  
    color = "#ff0000",  
    iconSize = 12,  
    background = "#1F7499",  
    borderRadius = "100%",  
    hoverScale = 1.4,  
    hoverEffect = TRUE,  
    additionalCSS = NULL,  
    hoverCSS = NULL,  
    htmlCode = NULL,  
    boxShadow = TRUE  
)
```

Arguments

icon	ID of the mapkey Icon you want to use.
color	Any CSS color (e.g. 'red', 'rgba(20,160,90,0.5)', '#686868', ...)
iconSize	Size of Icon in Pixels. Default is 12
background	Any CSS color or false for no background
borderRadius	Any number (for circle size/2, for square 0.001)

<code>hoverScale</code>	Any real number (best result in range 1 - 2, use 1 for no effect)
<code>hoverEffect</code>	Switch on/off effect on hover
<code>additionalCSS</code>	CSS code (e.g. "border:4px solid #aa3838;")
<code>hoverCSS</code>	CSS code (e.g. "background-color:#992b00 !important; color:#99defc !important;")
<code>htmlCode</code>	e.g. ''.
<code>boxShadow</code>	Should a shadow be visible

Value

A list of mapkey-icon data that can be passed to the argument `icon`

References

<https://github.com/mapshakers/leaflet-mapkey-icon>

See Also

Other Mapkey Functions: [.leaflet_mapkey_icon_set\(\)](#), [addMapkeyMarkers\(\)](#), [mapkeyIconList\(\)](#), [mapkeyIcons\(\)](#)

Examples

```
makeMapkeyIcon(icon = "traffic_signal",
               color = "#0000ff",
               iconSize = 12,
               boxShadow = FALSE,
               background="transparent")
```

`mapkeyIconList` *Make Mapkey-icon set*

Description

Make Mapkey-icon set

Usage

```
mapkeyIconList(...)
```

Arguments

... icons created from [makeMapkeyIcon\(\)](#)

Value

A list of class "leaflet_mapkey_icon_set"

References

<https://github.com/mapshakers/leaflet-mapkey-icon>

See Also

Other Mapkey Functions: [.leaflet_mapkey_icon_set\(\)](#), [addMapkeyMarkers\(\)](#), [makeMapkeyIcon\(\)](#), [mapkeyIcons\(\)](#)

Examples

```
iconSet = mapkeyIconList(  
  red = makeMapkeyIcon(color = "#ff0000"),  
  blue = makeMapkeyIcon(color = "#0000ff")  
)  
iconSet[c("red", "blue")]
```

mapkeyIcons

Create a list of Mapkey icon data

Description

An icon can be represented as a list of the form `list(color, iconSize, ...)`. This function is vectorized over its arguments to create a list of icon data. Shorter argument values will be re-cycled. NULL values for these arguments will be ignored.

Usage

```
mapkeyIcons(  
  icon = "mapkey",  
  color = "#ff0000",  
  iconSize = 12,  
  background = "#1F7499",  
  borderRadius = "100%",  
  hoverScale = 1.4,  
  hoverEffect = TRUE,  
  hoverCSS = NULL,  
  additionalCSS = NULL,  
  htmlCode = NULL,  
  boxShadow = TRUE  
)
```

Arguments

icon	ID of the mapkey Icon you want to use.
color	Any CSS color (e.g. 'red', 'rgba(20,160,90,0.5)', '#686868', ...)
iconSize	Size of Icon in Pixels. Default is 12
background	Any CSS color or false for no background

<code>borderRadius</code>	Any number (for circle size/2, for square 0.001)
<code>hoverScale</code>	Any real number (best result in range 1 - 2, use 1 for no effect)
<code>hoverEffect</code>	Switch on/off effect on hover
<code>hoverCSS</code>	CSS code (e.g. "background-color:#992b00 !important; color:#99defc !important;")
<code>additionalCSS</code>	CSS code (e.g. "border:4px solid #aa3838;")
<code>htmlCode</code>	e.g. ''.
<code>boxShadow</code>	Should a shadow be visible

Value

A list of mapkey-icon data that can be passed to the argument `icon`

References

<https://github.com/mapshakers/leaflet-mapkey-icon>

See Also

Other Mapkey Functions: [.leaflet_mapkey_icon_set\(\)](#), [addMapkeyMarkers\(\)](#), [makeMapkeyIcon\(\)](#), [mapkeyIconList\(\)](#)

Examples

```
## Not run:
library(leaflet)
leaflet() %>%
  addMapkeyMarkers(data = breweries91,
    icon = mapkeyIcons(
      color = "red",
      borderRadius = 0,
      iconSize = 25))

## End(Not run)
```

Description

`mapmenuItems`

Usage

`mapmenuItems(...)`

Arguments

... contextmenu item/s

Value

A list of menuItem for the map

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextMenu\(\)](#), [removeallItemsContextMenu\(\)](#), [setDisabledContextMenu\(\)](#), [showContextMenu\(\)](#)

markermenuItems

markermenuItems

Description

markermenuItems

Usage

markermenuItems(...)

Arguments

... contextmenu item/s

Value

A list of menuItem for markers

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [mapmenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextMenu\(\)](#), [removeallItemsContextMenu\(\)](#), [setDisabledContextMenu\(\)](#), [showContextMenu\(\)](#)

menuItem*menuItem*

Description

menuItem

Usage

```
menuItem(text, callback = NULL, ...)
```

Arguments

<code>text</code>	The label to use for the menu item
<code>callback</code>	A callback function to be invoked when the menu item is clicked. The callback is passed an object with properties identifying the location the menu was opened at: <code>latlng</code> , <code>layerPoint</code> and <code>containerPoint</code> . The callback-function must be valid JavaScript and will be wrapped in JS .
<code>...</code>	For further options please visit https://github.com/aratchiffe/Leaflet.contextmenu

Value

A contextmenu item list

See Also

Other Contextmenu Functions: [addContextMenu\(\)](#), [addItemContextMenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [removeItemContextMenu\(\)](#), [removeallItemsContextMenu\(\)](#), [setDisabledContextMenu\(\)](#), [showContextMenu\(\)](#)

movingMarkerOptions *Set options for Moving Markers*

Description

Set options for Moving Markers

Usage

```
movingMarkerOptions(autostart = FALSE, loop = FALSE, pauseOnZoom = FALSE)
```

Arguments

autostart	If TRUE the marker will start automatically after it is added to map. Default is FALSE
loop	if TRUE the marker will start automatically at the beginning of the polyline when it arrives at the end. Default is FALSE
pauseOnZoom	Pause the marker while zooming. While this improves the animation, it is not recommended because the animation time is lost and the marker will not appear at the correct time at the next station. Default is FALSE

Value

A list of extra options for moving markers

References

<https://github.com/ewoken/Leaflet.MovingMarker>

See Also

Other MovingMarker Functions: [addMovingMarker\(\)](#), [startMoving\(\)](#)

openSidebar

Open the Sidebar by ID

Description

Open the Sidebar by ID

Usage

```
openSidebar(map, id, sidebar_id = NULL, ns = NULL)
```

Arguments

map	A leaflet map widget
id	The id of the sidebar_pane to open.
sidebar_id	The id of the sidebar (per sidebar_tabs). Defaults to NULL such that the first sidebar is used.
ns	The namespace function, if used in Shiny modules.

Value

the new map object

See Also

Other Sidebar Functions: [addSidebar\(\)](#), [closeSidebar\(\)](#), [removeSidebar\(\)](#), [sidebar_pane\(\)](#), [sidebar_tabs\(\)](#)

`openweatherCurrentOptions`

openweatherCurrentOptions

Description

`openweatherCurrentOptions`

Usage

```
openweatherCurrentOptions(lang = "en", minZoom = 7, interval = 10, ...)
```

Arguments

<code>lang</code>	'en', 'de', 'ru', 'fr', 'es', 'ca'. Language of popup texts. Note: not every translation is finished yet.
<code>minZoom</code>	Number (7). Minimal zoom level for fetching city data. Use smaller values only at your own risk.
<code>interval</code>	Number (0). Time in minutes to reload city data. Please do not use less than 10 minutes.
...	Further options passed to <code>L.OWM.current</code> . See the full list of options

Value

A list of options for `addOpenweatherCurrent`

See Also

Other Openweathermap Functions: [addOpenweatherCurrent\(\)](#), [addOpenweatherTiles\(\)](#), [openweatherOptions\(\)](#)

`openweatherOptions`

OpenWeatherMap Options

Description

OpenWeatherMap Options

Usage

```
openweatherOptions(
  showLegend = TRUE,
  legendImagePath = NULL,
  legendPosition = c("bottomleft", "bottomright", "topleft", "topright")
)
```

Arguments

showLegend	If TRUE and option legendImagePath is set there will be a legend image on the map
legendImagePath	A URL (is set to a default image for some layers, null for others, see below). URL or relative path to an image which is a legend to this layer
legendPosition	Position of the legend images on the map. Must be one of 'bottomleft', 'bottomright', 'topleft', 'topright'

Value

A list of options for `addOpenweatherTiles`

See Also

Other Openweathermap Functions: [addOpenweatherCurrent\(\)](#), [addOpenweatherTiles\(\)](#), [openweatherCurrentOptions](#)

playbackOptions *playbackOptions*

Description

A list of options for `addPlayback`. For a full list please visit the [plugin repository](#).

Usage

```
playbackOptions(  
  color = "blue",  
  radius = 5,  
  tickLen = 250,  
  speed = 50,  
  maxInterpolationTime = 5 * 60 * 1000,  
  tracksLayer = TRUE,  
  playControl = TRUE,  
  dateControl = TRUE,  
  sliderControl = TRUE,  
  orientIcons = FALSE,  
  staleTime = 60 * 60 * 1000,  
  transitionpopup = TRUE,  
  transitionlabel = TRUE,  
  ...  
)
```

Arguments

<code>color</code>	colors of the CircleMarkers.
<code>radius</code>	a numeric value for the radius of the CircleMarkers.
<code>tickLen</code>	Set tick length in milliseconds. Increasing this value, may improve performance, at the cost of animation smoothness. Default is 250
<code>speed</code>	Set float multiplier for default animation speed. Default is 50
<code>maxInterpolationTime</code>	Set max interpolation time in seconds. Default is 5*60*1000 (5 minutes).
<code>tracksLayer</code>	Set TRUE if you want to show layer control on the map. Default is TRUE
<code>playControl</code>	Set TRUE if play button is needed. Default is TRUE
<code>dateControl</code>	Set TRUE if date label is needed. Default is TRUE
<code>sliderControl</code>	Set TRUE if slider control is needed. Default is TRUE
<code>orientIcons</code>	Set TRUE if you want icons to orient themselves on each tick based on the bearing towards their next location. Default: FALSE
<code>staleTime</code>	Set time before a track is considered stale and faded out. Default is 60*60*1000 (1 hour)
<code>transitionpopup</code>	Should the position of the popup move smoothly, like the marker icon? Default: TRUE
<code>transitionlabel</code>	Should the position of the label move smoothly, like the marker icon? Default: TRUE
<code>...</code>	Further arguments passed to ‘L.Playback‘

Value

A list of options for addPlayback

References

<https://github.com/hallahan/LeafletPlayback>

See Also

Other Playback Functions: [addPlayback\(\)](#), [removePlayback\(\)](#)

```
reachabilityOptions      reachabilityOptions
```

Description

Add extra options. For a full list please visit the [plugin repository](#).

Usage

```
reachabilityOptions(  
  collapsed = TRUE,  
  pane = "overlayPane",  
  position = "topleft",  
  ...  
)
```

Arguments

collapsed	Should the control widget start in a collapsed mode. Default is TRUE
pane	Leaflet pane to add the isolines GeoJSON to. Default is overlayPane
position	Leaflet control pane position. Default is topleft
...	Further arguments passed to 'L.Control.Reachability'

Value

A list of options for `addReachability`

References

<https://github.com/traffordDataLab/leaflet.reachability>

See Also

Other Reachability Functions: [addReachability\(\)](#), [removeReachability\(\)](#)

```
removeallItemsContextmenu  
removeallItemsContextmenu
```

Description

Remove all contextmenu items from the map.

Usage

```
removeallItemsContextmenu(map)
```

Arguments

`map` a map widget object created from [leaflet](#)

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextMenu\(\)](#), [addItemContextMenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextMenu\(\)](#), [setDisabledContextMenu\(\)](#), [showContextMenu\(\)](#)

`removeAntpath` *removeAntpath*

Description

Remove one or more Antpaths from a map, identified by `layerId`.

Usage

```
removeAntpath(map, layerId = NULL)
```

Arguments

`map` a map widget object, possibly created from [leaflet\(\)](#) but more likely from [leafletProxy\(\)](#)

`layerId` character vector; the layer id(s) of the item to remove

Value

the new map object

See Also

Other Antpath Functions: [addAntpath\(\)](#), [antpathOptions\(\)](#), [clearAntpath\(\)](#)

removeArrowhead	<i>Remove arrowheads from Lines by layerId</i>
-----------------	--

Description

Remove arrowheads from Lines by layerId

Usage

```
removeArrowhead(map, layerId)
```

Arguments

map	the map
layerId	A single layerId or a vector of layerId's

Value

A modified leaflet map

See Also

Other Arrowhead Functions: [addArrowhead\(\)](#), [arrowheadOptions\(\)](#), [clearArrowhead\(\)](#)

removeEasyprint	<i>removeEasyprint</i>
-----------------	------------------------

Description

Removes the easyprint control from the map.

Usage

```
removeEasyprint(map)
```

Arguments

map	the map widget
-----	----------------

Value

A leaflet map object

See Also

Other EasyPrint Functions: [addEasyprint\(\)](#), [easyprintMap\(\)](#), [easyprintOptions\(\)](#)

`removeItemContextmenu` *removeItemContextmenu*

Description

Remove a contextmenu item by index.

Usage

`removeItemContextmenu(map, index)`

Arguments

<code>map</code>	a map widget object created from leaflet
<code>index</code>	Index of the contextmenu. (NOTE: Since the index is passed to JavaScript, it is zero-based)

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextMenu\(\)](#), [addItemContextMenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeallItemsContextMenu\(\)](#), [setDisabledContextMenu\(\)](#), [showContextMenu\(\)](#)

`removePlayback` *removePlayback*

Description

Remove the Playback controls and markers.

Usage

`removePlayback(map)`

Arguments

<code>map</code>	the map widget
------------------	----------------

Value

the new map object

See Also

Other Playback Functions: [addPlayback\(\)](#), [playbackOptions\(\)](#)

`removeReachability` *removeReachability*

Description

Remove the reachability controls.

Usage

```
removeReachability(map)
```

Arguments

`map` the map widget.

Value

the new map object

See Also

Other Reachability Functions: [addReachability\(\)](#), [reachabilityOptions\(\)](#)

`removeSidebar` *Remove the Sidebar*

Description

Remove the Sidebar

Usage

```
removeSidebar(map, sidebar_id = NULL)
```

Arguments

`map` A leaflet map widget

`sidebar_id` The id of the sidebar (per [sidebar_tabs](#)). Defaults to NULL such that the first sidebar is removed.

Value

the new map object

See Also

Other Sidebar Functions: [addSidebar\(\)](#), [closeSidebar\(\)](#), [openSidebar\(\)](#), [sidebar_pane\(\)](#), [sidebar_tabs\(\)](#)

`removeSidebyside` *removeSidebyside*

Description

`removeSidebyside`

Usage

```
removeSidebyside(map, layerId = NULL)
```

Arguments

<code>map</code>	a map widget
<code>layerId</code>	the layer id of the addSidebyside layer

Value

the new map object

See Also

Other Sidebyside Functions: [addSidebyside\(\)](#)

`removeTimeslider` *removeTimeslider*

Description

Remove the Timeslider controls and markers.

Usage

```
removeTimeslider(map)
```

Arguments

<code>map</code>	the map widget
------------------	----------------

Value

the new map object

See Also

Other Timeslider Functions: [addTimeslider\(\)](#), [timesliderOptions\(\)](#)

`removeVelocity` *removeVelocity*

Description

`removeVelocity`

Usage

`removeVelocity(map, group)`

Arguments

<code>map</code>	the map widget
<code>group</code>	the group to remove

Value

the new map object

See Also

Other Velocity Functions: [addVelocity\(\)](#), [setOptionsVelocity\(\)](#), [velocityOptions\(\)](#)

`setDate` *Set Date for GIBS Layers*

Description

Set a new date for multi-temporal layers.

Usage

`setDate(map, layers = NULL, dates = NULL)`

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>layers</code>	A character vector of GIBS-layers. See gibs_layers
<code>dates</code>	Date object. If multiple <code>layers</code> are added, you can add a Date vector of the same length

Value

the new map object

See Also

Other GIBS Functions: [addGIBS\(\)](#), [setTransparent\(\)](#)

`setDisabledContextmenu`

setDisabledContextmenu

Description

Enable/Disable a contextmenu item by index.

Usage

```
setDisabledContextMenu(map, index, disabled = TRUE)
```

Arguments

<code>map</code>	a leaflet map widget object created from leaflet
<code>index</code>	Index of the contextmenu. (NOTE: Since the index is passed to JavaScript, it is zero-based)
<code>disabled</code>	Set to TRUE to disable the element and FALSE to enable it. Default is TRUE

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextMenu\(\)](#), [addItemContextMenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [mapmenuItems\(\)](#), [markerMenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextMenu\(\)](#), [removeallItemsContextMenu\(\)](#), [showContextMenu\(\)](#)

setOptionsVelocity *setOptionsVelocity*

Description

setOptionsVelocity

Usage

`setOptionsVelocity(map, layerId, options)`

Arguments

map	the map widget
layerId	the layer id
options	see velocityOptions

Value

the new map object

See Also

Other Velocity Functions: [addVelocity\(\)](#), [removeVelocity\(\)](#), [velocityOptions\(\)](#)

setTransparent *Set Transparency for GIBS Layers*

Description

Change the transparency for no-data pixels.

Usage

`setTransparent(map, layers = NULL, transparent = TRUE)`

Arguments

map	a map widget object created from leaflet()
layers	A character vector of GIBS-layers. See gibs_layers
transparent	Should the layer be transparent. If multiple layers are added, you can add a boolean vector of the same length

Value

the new map object

See Also

Other GIBS Functions: [addGIBS\(\)](#), [setDate\(\)](#)

[showContextmenu](#)

showContextmenu

Description

Open the contextmenu at certain lat/lng-coordinates

Usage

```
showContextmenu(map, lat = NULL, lng = NULL, data = leaflet::getMapData(map))
```

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>lat</code>	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from <code>data</code>)
<code>lng</code>	a numeric vector of longitudes, or a one-sided formula of the form <code>~x</code> where <code>x</code> is a variable in <code>data</code> ; by default (if not explicitly provided), it will be automatically inferred from <code>data</code> by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
<code>data</code>	the data object from which the argument values are derived; by default, it is the <code>data</code> object provided to <code>leaflet()</code> initially, but can be overridden

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextMenu\(\)](#), [addItemContextMenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextMenu\(\)](#), [enableContextMenu\(\)](#), [hideContextMenu\(\)](#), [insertItemContextMenu\(\)](#), [mapmenuItems\(\)](#), [markerMenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextMenu\(\)](#), [removeallItemsContextMenu\(\)](#), [setDisabledContextMenu\(\)](#)

showHexbin

showHexbin

Description

Show the hexbinLayer.

Usage

```
showHexbin(map)
```

Arguments

map The map widget

Value

the new map object

See Also

Other Hexbin-D3 Functions: [addHexbin\(\)](#), [clearHexbin\(\)](#), [hexbinOptions\(\)](#), [hideHexbin\(\)](#), [updateHexbin\(\)](#)

sidebar_pane

Create a Sidebar Pane

Description

Create a Sidebar Pane

Usage

```
sidebar_pane(  
  title = "Sidebar Title",  
  id = NULL,  
  icon = icon("caret-right"),  
  ...  
)
```

Arguments

title	A title for the sidebar panel
id	An id for the sidebar panel
icon	An icon for the sidebar panel
...	List of elements to include in the panel

Value

A shiny.tag with sidebar-specific HTML classes

References

<https://github.com/Turbo87/sidebar-v2>, <https://github.com/Turbo87/sidebar-v2/blob/master/doc/usage.md>

See Also

Other Sidebar Functions: `addSidebar()`, `closeSidebar()`, `openSidebar()`, `removeSidebar()`, `sidebar_tabs()`

Examples

```
## Not run:
library(shiny)
sidebar_pane(id = "id", icon = icon("cars"), tags$div())

## End(Not run)
```

sidebar_tabs

Create a Sidebar

Description

Create a Sidebar

Usage

```
sidebar_tabs(id = "sidebar", iconList = NULL, ...)
```

Arguments

<code>id</code>	The id of the sidebar, which must match the id of <code>addSidebar</code> . Default is "sidebar"
<code>iconList</code>	A list of icons to be shown, when the sidebar is collapsed. The list is required and must match the amount of <code>sidebar_pane</code> .
<code>...</code>	The individual <code>sidebar_pane</code> 's.

Value

A shiny.tag with individual sidebar panes

References

<https://github.com/Turbo87/sidebar-v2>, <https://github.com/Turbo87/sidebar-v2/blob/master/doc/usage.md>

See Also

Other Sidebar Functions: [addSidebar\(\)](#), [closeSidebar\(\)](#), [openSidebar\(\)](#), [removeSidebar\(\)](#), [sidebar_pane\(\)](#)

Examples

```
## Not run:  
library(shiny)  
  
# run example app showing a single sidebar  
runApp(paste0(system.file("examples", package = "leaflet.extras2"),  
              "/sidebar_app.R"))  
  
# run example app showing two sidebars  
runApp(paste0(system.file("examples", package = "leaflet.extras2"),  
              "/multi_sidebar_app.R"))  
  
## End(Not run)
```

startMoving

Interact with the moving markers

Description

The marker begins its path or resumes if it is paused.

Usage

```
startMoving(map, layerId = NULL)  
  
stopMoving(map, layerId = NULL)  
  
pauseMoving(map, layerId = NULL)  
  
resumeMoving(map, layerId = NULL)  
  
addLatLngMoving(map, layerId = NULL, latlng, duration)  
  
moveToMoving(map, layerId = NULL, latlng, duration)  
  
addStationMoving(map, layerId = NULL, pointIndex, duration)
```

Arguments

map	The leafletProxy object
layerId	You can pass a string or a vector of strings for the moving markers that you want to address. If none is specified, the action will be applied to all moving markers.

<code>latlng</code>	Coordinates as list (e.g.: <code>list(33, -67)</code> or <code>list(lng=-65, lat=33)</code>)
<code>duration</code>	Duration in milliseconds
<code>pointIndex</code>	Index of a certain point

Value

the new map object

Functions

- `stopMoving`: Manually stops the marker, if you call `start` after, the marker starts again the polyline at the beginning.
- `pauseMoving`: Pauses the marker
- `resumeMoving`: The marker resumes its animation
- `addLatLngMoving`: Adds a point to the polyline. Useful, if we have to set the path one by one.
- `moveToMoving`: Stop the current animation and make the marker move to `latlng` in `duration` ms.
- `addStationMoving`: The marker will stop at the `pointIndex` point of the polyline for `duration` milliseconds. You can't add a station at the first or last point of the polyline.

References

<https://github.com/ewoken/Leaflet.MovingMarker>

See Also

Other MovingMarker Functions: [addMovingMarker\(\)](#), [movingMarkerOptions\(\)](#)

`timesliderOptions` *timesliderOptions*

Description

A list of options for [addTimeslider](#).

Usage

```
timesliderOptions(
  position = c("topright", "bottomleft", "bottomright", "topleft"),
  timeAttribute = "time",
  isEpoch = FALSE,
  startTimeIdx = 0,
  timeStrLength = 19,
  maxValue = -1,
  minValue = 0,
  showAllOnStart = FALSE,
```

```

range = FALSE,
follow = FALSE,
alwaysShowDate = FALSE,
rezoom = NULL,
sameDate = FALSE
)

```

Arguments

position	position of control: "topleft", "topright", "bottomleft", or "bottomright". Default is topright.
timeAttribute	The column name of the time property. Default is "time"
isEpoch	whether the time attribute is seconds elapsed from epoch. Default is FALSE
startTimeIdx	where to start looking for a timestamp Default is 0
timeStrLength	the size of yyyy-mm-dd hh:mm:ss - if milliseconds are present this will be larger. Default is 19
maxValue	Set the maximum value of the slider. Default is -1
minValue	Set the minimum value of the slider. Default is 0
showAllOnStart	Specify whether all markers should be initially visible. Default is FALSE
range	To use a range-slider, set to TRUE . Default is FALSE Default is FALSE
follow	To display only the markers at the specific timestamp specified by the slider. Specify a value of 1 (or true) to display only a single data point at a time, and a value of null (or false) to display the current marker and all previous markers. The range property overrides the follow property. Default is FALSE
alwaysShowDate	Should the Date always be visible. Default is FALSE
rezoom	Use the rezoom property to ensure the markers being displayed remain in view. Default is NULL
sameDate	Show only data with the current selected time. Default is FALSE

Value

A list of options for addTimeslider

References

<https://github.com/dwilhelm89/LeafletSlider>

See Also

Other Timeslider Functions: [addTimeslider\(\)](#), [removeTimeslider\(\)](#)

to_jsonformat*to_jsonformat* Transform object to JSON expected format**Description**

to_jsonformat Transform object to JSON expected format

Usage`to_jsonformat(data, time, popup = NULL, label = NULL, name = NULL)`**Arguments**

<code>data</code>	The data
<code>time</code>	Name of the time column.
<code>popup</code>	Name of the popup column.
<code>label</code>	Name of the label column.
<code>name</code>	Name of the name column.

Value

A list that is transformed to the expected JSON format

to_ms*to_ms* Change POSIX or Date to milliseconds**Description**

to_ms Change POSIX or Date to milliseconds

Usage`to_ms(data, time)`**Arguments**

<code>data</code>	The data
<code>time</code>	Name of the time column.

Value

A data.frame with the time column in milliseconds

unsync	<i>Removes synchronization.</i>
--------	---------------------------------

Description

Removes the synchronization of multiple maps from a specific map.

Usage

```
unsync(map, id = NULL, unsyncids = NULL)
```

Arguments

map	the map
id	The map id from which to unsynchronize the maps in unsyncids
unsyncids	Unsyncronize the maps with the following IDs

Value

A map

See Also

Other leafletsync Functions: [addLeafletsyncDependency\(\)](#), [addLeafletsync\(\)](#), [isSynced\(\)](#), [leafletsyncOptions\(\)](#)

updateHexbin	<i>updateHexbin</i>
--------------	---------------------

Description

Dynamically change the data and/or the colorRange.

Usage

```
updateHexbin(map, data = NULL, lng = NULL, lat = NULL, colorRange = NULL)
```

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>data</code>	the data object from which the argument values are derived; by default, it is the <code>data</code> object provided to <code>leaflet()</code> initially, but can be overridden
<code>lng</code>	a numeric vector of longitudes, or a one-sided formula of the form <code>~x</code> where <code>x</code> is a variable in <code>data</code> ; by default (if not explicitly provided), it will be automatically inferred from <code>data</code> by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
<code>lat</code>	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from <code>data</code>)
<code>colorRange</code>	The range of the color scale used to fill the hexbins

Value

the new map object

See Also

Other Hexbin-D3 Functions: [addHexbin\(\)](#), [clearHexbin\(\)](#), [hexbinOptions\(\)](#), [hideHexbin\(\)](#), [showHexbin\(\)](#)

`velocityOptions`

velocityOptions

Description

Define further options for the velocity layer.

Usage

```
velocityOptions(
  speedUnit = c("m/s", "k/h", "kt"),
  minVelocity = 0,
  maxVelocity = 10,
  velocityScale = 0.005,
  colorScale = NULL,
  ...
)
```

Arguments

<code>speedUnit</code>	Could be 'm/s' for meter per second, 'k/h' for kilometer per hour or 'kt' for knots
<code>minVelocity</code>	velocity at which particle intensity is minimum
<code>maxVelocity</code>	velocity at which particle intensity is maximum

velocityScale scale for wind velocity
colorScale A vector of hex colors or an RGB matrix
... Further arguments passed to the Velocity layer and Windy.js. For more information, please visit [leaflet-velocity plugin](#)

Value

A list of further options for addVelocity

See Also

Other Velocity Functions: [addVelocity\(\)](#), [removeVelocity\(\)](#), [setOptionsVelocity\(\)](#)

[.leaflet_mapkey_icon_set
 leaflet_mapkey_icon_set

Description

leaflet_mapkey_icon_set

Usage

```
## S3 method for class 'leaflet_mapkey_icon_set'  
x[i]
```

Arguments

x	icons
i	offset

See Also

Other Mapkey Functions: [addMapkeyMarkers\(\)](#), [makeMapkeyIcon\(\)](#), [mapkeyIconList\(\)](#), [mapkeyIcons\(\)](#)

Index

* Antpath Functions

addAntpath, 4
antpathOptions, 38
clearAntpath, 40
removeAntpath, 70

* Arrowhead Functions

addArrowhead, 6
arrowheadOptions, 39
clearArrowhead, 41
removeArrowhead, 71

* Contextmenu Functions

addContextmenu, 8
addItemContextmenu, 16
context_mapmenuItems, 44
context_markermenuItems, 45
context_menuItem, 45
disableContextmenu, 46
enableContextmenu, 49
hideContextmenu, 54
insertItemContextmenu, 57
mapmenuItems, 62
markermenuItems, 63
menuItem, 64
removeallItemsContextmenu, 69
removeItemContextmenu, 72
setDisabledContextmenu, 76
showContextmenu, 78

* EasyPrint Functions

addEasyprint, 9
easyprintMap, 47
easyprintOptions, 48
removeEasyprint, 71

* GIBS Functions

addGIBS, 10
 setDate, 75
 setTransparent, 77

* Heightgraph Functions

addHeightgraph, 11
heightgraphOptions, 51

* Hexbin-D3 Functions

addHexbin, 13
clearHexbin, 42
hexbinOptions, 53
hideHexbin, 55
showHexbin, 79
updateHexbin, 85

* History Functions

addHistory, 15
clearFuture, 42
clearHistory, 43
goBackHistory, 50
goForwardHistory, 51
historyOptions, 55

* Mapkey Functions

[.leaflet_mapkey_icon_set, 87
addMapkeyMarkers, 19
makeMapkeyIcon, 59
mapkeyIconList, 60
mapkeyIcons, 61

* MovingMarker Functions

addMovingMarker, 21
movingMarkerOptions, 64
startMoving, 81

* Openweathermap Functions

addOpenweatherCurrent, 22
addOpenweatherTiles, 24
openweatherCurrentOptions, 66
openweatherOptions, 66

* Playback Functions

addPlayback, 25
playbackOptions, 67
removePlayback, 72

* Reachability Functions

addReachability, 28
reachabilityOptions, 69
removeReachability, 73

* Sidebar Functions

addSidebar, 29

closeSidebar, 43
openSidebar, 65
removeSidebar, 73
sidebar_pane, 79
sidebar_tabs, 80
*** Sidebar Functions**
addSidebyside, 30
removeSidebyside, 74
*** Tangram Functions**
addTangram, 32
*** Timeslider Functions**
addTimeslider, 33
removeTimeslider, 74
timesliderOptions, 82
*** Velocity Functions**
addVelocity, 35
removeVelocity, 75
setOptionsVelocity, 77
velocityOptions, 86
*** WMS Functions**
addWMS, 36
*** datasets**
gibs_layers, 50
*** leafletsync Functions**
addLeafletsync, 17
addLeafletsyncDependency, 18
isSynced, 57
leafletSyncOptions, 58
unsync, 85
.leaflet_mapkey_icon_set, 20, 60–62, 87

addAntpath, 4, 39, 41, 70
addArrowhead, 6, 40, 41, 71
addContextmenu, 8, 16, 44–46, 50, 54, 57, 63, 64, 70, 72, 76, 78
addEasyprint, 9, 47, 49, 71
addGeoJSON, 11
addGIBS, 10, 76, 78
addHeightgraph, 11, 53
addHexbin, 13, 43, 54, 55, 79, 86
addHistory, 15, 42, 43, 51, 56
addItemContextmenu, 8, 16, 44–46, 50, 54, 57, 63, 64, 70, 72, 76, 78
addLabelgun, 16
addLatLangMoving (startMoving), 81
addLayersControl, 5, 7, 10, 12, 14, 20, 21, 23, 24, 30, 32, 35, 37
addLeafletSync, 17, 19, 58, 59, 85

addLeafletSyncDependency, 18, 18, 58, 59, 85
addMapkeyMarkers, 19, 60–62, 87
addMovingMarker, 21, 65, 82
addOpenweatherCurrent, 22, 25, 66, 67
addOpenweatherTiles, 23, 24, 66, 67
addPlayback, 25, 67, 68, 73
addReachability, 28, 69, 73
addSidebar, 29, 44, 65, 74, 80, 81
addSidebyside, 30, 74
addSpinner, 31
addStationMoving (startMoving), 81
addTangram, 32
addTimeslider, 33, 75, 82, 83
addVelocity, 35, 75, 77, 87
addWMS, 36
antpathOptions, 4, 5, 38, 41, 70
arrowheadOptions, 6, 7, 39, 41, 71

clearAntpath, 5, 39, 40, 70
clearArrowhead, 7, 40, 41, 71
clearFuture, 15, 42, 43, 51, 56
clearGroup, 5, 7, 10, 12, 14, 20, 21, 23, 24, 32, 35, 37
clearHexbin, 14, 42, 54, 55, 79, 86
clearHistory, 15, 42, 43, 51, 56
closeSidebar, 29, 43, 65, 74, 80, 81
context_mapmenuItems, 8, 16, 44, 45, 46, 50, 54, 57, 63, 64, 70, 72, 76, 78
context_markermenuItems, 8, 16, 44, 45, 46, 50, 54, 57, 63, 64, 70, 72, 76, 78
context_menuItem, 8, 16, 44, 45, 46, 50, 54, 57, 63, 64, 70, 72, 76, 78

disableContextmenu, 8, 16, 44–46, 46, 50, 54, 57, 63, 64, 70, 72, 76, 78

easyprintMap, 10, 47, 49, 71
easyprintOptions, 9, 10, 47, 48, 71
enableContextmenu, 8, 16, 44–46, 49, 54, 57, 63, 64, 70, 72, 76, 78

gibs_layers, 10, 50, 75, 77
goBackHistory, 15, 42, 43, 50, 51, 56
goForwardHistory, 15, 42, 43, 51, 51, 56

heightgraphOptions, 12, 13, 51
hexbinOptions, 14, 43, 53, 55, 79, 86
hideContextmenu, 8, 16, 44–46, 50, 54, 57, 63, 64, 70, 72, 76, 78

hideHexbin, 14, 43, 54, 55, 79, 86
 historyOptions, 15, 42, 43, 51, 55
 htmlEscape, 5, 7, 20, 22, 34
 insertItemContextMenu, 8, 16, 44–46, 50, 54, 57, 63, 64, 70, 72, 76, 78
 isSynced, 18, 19, 57, 59, 85
 JS, 45, 53, 54, 64
 labelOptions, 5, 7, 20, 22, 26, 34
 leaflet, 4, 6, 8–10, 12, 14–17, 23, 24, 31, 35, 37, 41, 46, 49, 54, 57, 70, 72, 75–78, 86
 leaflet.extras2, 58
 leafletOptions, 8
 leafletOutput, 29
 leafletProxy, 41–43, 50, 51, 70
 leafletsyncOptions, 17–19, 58, 58, 85
 makeIcon, 26
 makeMapkeyIcon, 20, 59, 60–62, 87
 mapkeyIconList, 20, 60, 60, 62, 87
 mapkeyIcons, 20, 60, 61, 61, 87
 mapmenuItems, 8, 16, 44–46, 50, 54, 57, 62, 63, 64, 70, 72, 76, 78
 markerClusterOptions, 20
 markermenuItems, 8, 16, 44–46, 50, 54, 57, 63, 63, 64, 70, 72, 76, 78
 markerOptions, 8, 20, 22
 menuItem, 8, 16, 44–46, 50, 54, 57, 63, 64, 70, 72, 76, 78
 moveToMoving (startMoving), 81
 movingMarkerOptions, 22, 64, 82
 openSidebar, 29, 44, 65, 74, 80, 81
 openweatherCurrentOptions, 23, 25, 66, 67
 openweatherOptions, 23–25, 66, 66
 pathOptions, 8, 12, 26
 pauseMoving (startMoving), 81
 playbackOptions, 26, 67, 73
 popupOptions, 5, 7, 20, 22, 26, 34, 37
 reachabilityOptions, 28, 69, 73
 removeallItemsContextMenu, 8, 16, 44–46, 50, 54, 57, 63, 64, 69, 72, 76, 78
 removeAntpath, 5, 39, 41, 70
 removeArrowhead, 7, 40, 41, 71
 removeControl, 12
 removeEasyprint, 10, 47, 49, 71
 removeItemContextMenu, 8, 16, 44–46, 50, 54, 57, 63, 64, 70, 72, 76, 78
 removePlayback, 26, 68, 72
 removeReachability, 28, 69, 73
 removeSidebar, 29, 44, 65, 73, 80, 81
 removeSidebyside, 30, 74
 removeTimeslider, 34, 74, 83
 removeVelocity, 36, 75, 77, 87
 resumeMoving (startMoving), 81
 setDate, 11, 75, 78
 setDisabledContextMenu, 8, 16, 44–46, 50, 54, 57, 63, 64, 70, 72, 76, 78
 setOptionsVelocity, 36, 75, 77, 87
 setTransparent, 11, 76, 77
 showContextMenu, 8, 16, 44–46, 50, 54, 57, 63, 64, 70, 72, 76, 78
 showHexbin, 14, 43, 54, 55, 79, 86
 sidebar_pane, 29, 44, 65, 74, 79, 80, 81
 sidebar_tabs, 29, 44, 65, 73, 74, 80, 80
 startMoving, 22, 65, 81
 startSpinner (addSpinner), 31
 stopMoving (startMoving), 81
 stopSpinner (addSpinner), 31
 timesliderOptions, 34, 75, 82
 to_jsonformat, 84
 to_ms, 84
 unsync, 18, 19, 58, 59, 85
 updateHexbin, 14, 43, 54, 55, 79, 85
 velocityOptions, 36, 75, 77, 86