

Package ‘CAMERA’

October 12, 2016

Version 1.28.0

Date 2016-03-23

Title Collection of annotation related methods for mass spectrometry data

Author Carsten Kuhl, Ralf Tautenhahn, Steffen Neumann {ckuhllsneumann}@ipb-halle.de, rtautenh@scripps.edu

Maintainer Steffen Neumann <sneumann@ipb-halle.de>

Depends R (>= 2.1.0), methods, Biobase, xcms (>= 1.13.5)

Imports methods, xcms, RBGL, graph, graphics, grDevices, stats, utils, Hmisc, igraph

Suggests faahKO, RUnit, BiocGenerics

Enhances Rmpi, snow

Description Annotation of peaklists generated by xcms, rule based annotation of isotopes and adducts, EIC correlation based tagging of unknown adducts and fragments

License GPL (>= 2)

ByteCompile TRUE

URL <http://msbi.ipb-halle.de/msbi/CAMERA/>

BugReports <https://github.com/sneumann/CAMERA/issues/new>

biocViews MassSpectrometry, Metabolomics

NeedsCompilation yes

R topics documented:

annotate-methods	2
annotateDiffreport	4
calcCaS-methods	6
calcCiS-methods	7
calcIsotopes-methods	8
calcPC-methods	9

calcPC.hcs	10
calcPC.lpc	10
cleanParallel	11
combinexsAnnos	12
findAdducts-methods	13
findIsotopes	14
findKendrickMasses	15
findNeutralLoss	16
findNeutralLossSpecs	17
getAllPeakEICs	18
getIsotopeCluster	19
getPeaklist	20
getpspectra	21
groupCorr	22
groupDen	24
groupFWHM	25
mm14	26
plotEICs-methods	27
plotPsSpectrum-methods	28
psDist-methods	29
pspec2metfrag	30
ruleSet	31
xsAnnotate	32
xsAnnotate-class	33
Index	35

annotate-methods *Automatic deconvolution/annotation of LC/ESI-MS data*

Description

Wrapper skript for automatic annotation of isotope peaks, adducts and fragments for a (grouped) xcmsSet xs. The function returns an xsAnnotate object.

Usage

```
annotate(object, sample=NA, nSlaves=1, sigma=6, perfw hm=0.6,
  cor_eic_th=0.75, graphMethod="hcs", pval=0.05, calcCiS=TRUE,
  calcIso=FALSE, calcCaS=FALSE, maxcharge=3, maxiso=4, minfrac=0.5,
  ppm=5, mzabs=0.015, quick=FALSE, psg_list=NULL, rules=NULL,
  polarity="positive", multiplier=3, max_peaks=100 ,intval="into")
```

Arguments

object	xcmsSet with peak group assignments
sample	xsAnnotate: Sample selection for grouped xcmsSet, see xsAnnotate-class
nSlaves	xsAnnotate: Use parallel CAMERA mode, require Rmpi
sigma	groupFWHM: multiplier of the standard deviation
perfwHM	groupFWHM: percentage of FWHM width
cor_eic_th	groupCorr: correlation threshold (0..1)
graphMethod	groupCorr: Method selection for grouping peaks after correlation analysis into pseudospectra
pval	groupCorr: significant correlation threshold
calcCiS	groupCorr: Use correlation inside samples for peak grouping
calcIso	groupCorr: Use isotopic relationship for peak grouping
calcCaS	groupCorr: Use correlation across samples for peak grouping
maxcharge	findIsotopes: max. ion charge
maxiso	findIsotopes: max. number of expected isotopes
minfrac	findIsotopes: The percentage number of samples, which must satisfy the C12/C13 rule for isotope annotation
ppm	General ppm error
mzabs	General absolut error in m/z
quick	Use only groupFWHM and findIsotopes
psg_list	Calculation will only be done for the selected groups
rules	findAdducts: User defined ruleset
polarity	findAdducts: Which polarity mode was used for measuring of the ms sample
multiplier	findAdducts: If no ruleset is provided, calculate ruleset with max. number n of [nM+x] clusterions
max_peaks	How much peaks will be calculated in every thread using the parallel mode
intval	General used intensity value (into, maxo, intb)

Details

Batch script for annotation of an (grouped) xcmsSet *xs*. Generates an xsAnnotate object by calling all involved functions for the annotation step. Function list: 1: groupFWHM(), 2: findIsotopes(), 3: groupCorr(), 4: findAdducts() Return the xsAnnotate object, which inherits all annotations. For more information about the parameters see the specific function manpages.

Value

annotate returns an xsAnnotate object. For more information about the xsAnnotate object see [xsAnnotate-class](#).

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```
library(CAMERA)
file <- system.file('mzdata/MM14.mzdata', package = "CAMERA")
xs <- xcmsSet(file, method="centWave", ppm=30, peakwidth=c(5,10))
xsa <- annotate(xs)
```

annotateDiffreport *Automatic deconvolution/annotation of LC/ESI-MS data*

Description

Wrapper function for the xcms diffreport and the annotate function. Returns a diffreport within the annotation results.

Usage

```
annotateDiffreport(object, sample=NA, nSlaves=1, sigma=6, perfwhm=0.6,
  cor_eic_th=0.75, cor_exp_th = 0.75, graphMethod="hcs", pval=0.05, calcCiS=TRUE,
  calcIso=FALSE, calcCaS=FALSE, maxcharge=3, maxiso=4, minfrac=0.5,
  ppm=5, mzabs=0.015, quick=FALSE, psg_list=NULL, rules=NULL,
  polarity="positive", multiplier=3, max_peaks=100, intval="into",
  pval_th = NULL, fc_th = NULL, sortpval=TRUE, ...)
```

Arguments

object	xcmsSet with peak group assignments
sample	xsAnnotate: Sample selection for grouped xcmsSet, see xsAnnotate-class
nSlaves	xsAnnotate: Use parallel CAMERA mode, require Rmpi
sigma	groupFWHM: multiplier of the standard deviation
perfwhm	groupFWHM: percentage of FWHM width
cor_eic_th	groupCorr: Correlation threshold for EIC correlation (0..1)
cor_exp_th	groupCorr: Threshold for intensity correlations across samples (0..1)
graphMethod	groupCorr: Method selection for grouping peaks after correlation analysis into pseudospectra
pval	groupCorr: significant correlation threshold
calcCiS	groupCorr: Use correlation inside samples for peak grouping
calcIso	groupCorr: Use isotopic relationship for peak grouping
calcCaS	groupCorr: Use correlation across samples for peak grouping
maxcharge	findIsotopes: max. ion charge
maxiso	findIsotopes: max. number of expected isotopes
minfrac	findIsotopes: The percentage number of samples, which must satisfy the C12/C13 rule for isotope annotation

ppm	General ppm error
mzabs	General absolut error in m/z
quick	Use only groupFWHM and findIsotopes
psg_list	Calculation will only be done for the selected groups
rules	findAdducts: User defined ruleset
polarity	findAdducts: Which polarity mode was used for measuring of the ms sample
multiplier	findAdducts: If no ruleset is provided, calculate ruleset with max. number n of [nM+x] clusterions
max_peaks	How much peaks will be calculated in every thread using the parallel mode
intval	General used intensity value (into, maxo, intb)
pval_th	pval threshold. Creates a new psg_list. A pseudospectra is selected if it contains peaks, with pval < pval_th
fc_th	Same as pval. Select those groups with contains peaks with fold-change > fc_th. Pval_th and fc_th can be combined
sortpval	Sort diffreport after pvalues
...	Diffreport parameters see diffreport

Details

Batch script wrapper for combining the annotation and the diffreport for a (grouped) xcmsSet xs. Function list: 1: diffreport(), 2: groupFWHM(), 3: findIsotopes(), 4: groupCorr(), 5: findAdducts() For a speedup calculation users can create a quick run, with quick = TRUE to preselect pseudospectra of interest. The indices of those pseudospectra are set with psg_list in a second run. On the other hand, a automatic selection with pval_th and/or fc_th can be performed. Returns the normal xcms diffreport table, with the additional CAMERA slots

Value

annotateDiffreport returns an diffreport, see [diffreport](#), within additional columns containing the annotation results.

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```
#Multiple sample
library(CAMERA)
library(faahKO)
xs.grp    <- group(faahko)
xs.fill   <- fillPeaks(xs.grp)

#fast preselection
# diffreport <- annotateDiffreport(xs.fill,quick=TRUE)
# index <- c(1,18,35,45,56) #Make only for those grps a adduct annotation
```

```
# diffreport2 <- annotateDiffreport(xs.fill,psg_list=index,metlin = TRUE)

#automatic selection for groups with peaks p-val < 0.05 and fold-change > 3
# diffreport <- annotateDiffreport(xs.fill,pval_th=0.05,fc=3)
```

calcCaS-methods

EIC correlation grouping of LC/ESI-MS data

Description

Calculate the correlation across samples. Filtering correlation with specific parameters and returns a correlation matrix.

Usage

```
calcCaS(object,corval=0.75, pval=0.05, intval="into")
```

Arguments

object	The xsAnnotate object
corval	Correlation threshold for positive hits
pval	P-Value threshold for significance level of correlation
intval	Selection of the intensity values that should be used in the correlation analysis. Can be into, maxo or intb.

Details

Calculate pearson correlation between the peak intensities over all samples. Afterwards use cor.test for returning only significant correlation. Returns only those correlation, which are above both threshold. Set corval and pval to 0 to get the unfiltered correlation matrix. If the object is pregrouped with groupFWHM, then the correlation is only calculated between peaks within a pseudospectrum. Otherwise between all peaks.

Value

A matrix with 4 columns:

x	peak index according to peaktable
y	peak index according to peaktable
cor	correlation value between peak x and peak y
ps	pseudospektrum index for both peaks

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

See Also[calcCiS groupCorr xsAnnotate-class](#)**Examples**

```
library(CAMERA)
#Multiple sample
library(faahKO)
xs.grp      <- group(faahko)
#create xsAnnotate object
xsa        <- xsAnnotate(xs.grp)
#generate pseudospectra
xsa.group  <- groupFWHM(xsa)
#calculate correlation
correlationMatrix <- calcCaS(xsa.group)
```

`calcCiS-methods`*Calculate peak distance matrix after EIC correlation*

Description

Processing an `xsAnnotate` object and correlates peak EIC curves from one pseudospectrum, using a precalculated EIC matrix ([getAllPeakEICs](#)). It return a weighted edge list as distance matrix between peaks according to the correlation analysis. The edge value is the pearson correlation coefficient. The list can be used as input for [calcPC](#).

Usage

```
calcCiS(object, EIC=EIC, corval=0.75, pval=0.05, psg_list=NULL)
```

Arguments

<code>object</code>	The <code>xsAnnotate</code> object
<code>EIC</code>	EIC Matrix
<code>corval</code>	Correlation threshold for the EIC correlation
<code>pval</code>	pvalue for testing correlation of significance
<code>psg_list</code>	Vector of pseudospectra indices. The correlation analysis will be only done for those groups

Details

The algorithm correlates the EIC of a every peak with all others, to find the peaks that belong to one substance. LC/MS data should grouped with `groupFWHM` first. This step reduce the runtime a lot and increased the number of correct classifications. Only correlation with a higher value than the correlation threshold and significant p-values will be returned.

Value

A matrix with 4 columns:

x	peak index
y	peak index
cor	correlation value
ps	pseudospectrum index, which contains x and y

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

See Also

[calcCaS](#) [groupCorr](#) [getAllPeakEICs](#) [xsAnnotate-class](#)

calcIsotopes-methods *Calculate isotope distance matrix from xsAnnotate object*

Description

Processing an xsAnnotate object with annotated isotopes ([findIsotopes](#)). It return a weighted edge list as distance matrix between peaks according to the isotope annotation. The edge value for recognized isotopes is 1 for all cases. The list can be used as input for [calcPC](#).

Arguments

object xsAnnotate object

Value

A matrix with 4 columns:

x	peak index
y	peak index
cor	edge value, always 1
ps	pseudospectrum index, which contains x and y

Methods

object = "xsAnnotate" calcIsotopes(object)

Author(s)

Carsten Kuhl, <ckuhl@ipb-halle.de>

See Also

[calcPC](#) [xsAnnotate-class](#)

Description

A number of clustering methods exist in CAMERA. calcPC is the generic method.

Usage

```
calcPC(object, method, ...)
```

Arguments

object	xsAnnotate-class object
method	Method to use for clustering. See details.
...	Optional arguments to be passed along

Details

This algorithms cluster peaks from a xsAnnotate object into pseudospectra according to a provided distance matrix. Therefore all peaks are transformend into a graph, with peaks as nodes and the value from the distance matrix as edges. Afterwards a graph separation algorithm is applied, which searches in the graph for clusters. See the manpages of the specific clustering algorithms for more information.

If the xsAnnotate is pregrouped, for example [groupFWHM](#), only the already existing groups will be further processed.

The different algorithms that can be used by specifying them with the method argument. For example to use the highly connected subgraphs approach by E. Hartuv, R. Shamir, (1999), one would use: `calcPC(object, method="hcs")`. This is also the default, see [calcPC.hcs](#).

Further arguments given by ... are passed through to the function implementing the method, which are most likely `ajc`. The parameter `ajc` is the peak distance matrix.

`getOption("BioC")$CAMERA$findPeaks.methods` returns a character vector of *nicknames* for the algorithms available.

The function returns a xsAnnotate object with grouping information, as list of peak indices. They are stored as `object@pspectra`.

See Also

[calcPC.lpc](#) [calcPC.hcs](#) [xsAnnotate-class](#)

calcPC.hcs	<i>Peakclustering into pseudospectra with the highly connected sub-graphs approach</i>
------------	--

Description

Cluster peaks from an xsAnnotate object into pseudospectra

Arguments

object	xsAnnotate object
ajc	Weighted symbolic edge list as four column matrix ("x","y","cor","ps"). Columns x,y are peak indices, cor the edge value and ps the pseudospectrum index, where both peaks occur.
psg_list	additional vector ps pseudospectra indices, which are used in the clustering. If set to NULL all pseudospectra will be processed.

Details

In some cases, is the peak grouping after retentiontime with [groupFWHM](#) not enough to separate co-elution compounds. Therefore [groupCorr](#) use additional correlation analysis to achieve a separation. calcPC is part of this approach, which takes the calculated weighted edge list and performs the graph clustering. It returns an xsAnnotate object with further separated pseudospectra.

Methods

```
object = "xsAnnotate"      calcPC.hcs(object, ajc=NULL, psg_list=NULL)
```

Author(s)

Carsten Kuhl, <ckuhl@ipb-halle.de>

See Also

[calcPC](#) [groupCorr](#) [highlyConnSG](#) [xsAnnotate-class](#)

calcPC.lpc	<i>Peakclustering into pseudospectra with the label-propagation-community algorithm</i>
------------	---

Description

Cluster peaks from an xsAnnotate object into pseudospectra

Arguments

object	xsAnnotate object
ajc	Weighted symbolic edge list as four column matrix ("x","y","cor","ps"). Columns x,y are peak indices, cor the edge value and ps the pseudospectrum index, where both peaks occur.
psg_list	additional vector ps pseudospectra indices, which are used in the clustering. If set to NULL all pseudospectra will be processed.

Details

In some cases, is the peak grouping after retentiontime with [groupFWHM](#) not enough to separate co-elution compounds. Therefore [groupCorr](#) use additional correlation analysis to achieve a separation. `calcPC` is part of this approach, which takes the calculated weighted edge list and performs the graph clustering. It returns an `xsAnnotate` object with further separated pseudospectra.

Methods

```
object = "xsAnnotate"      calcPC.lpc(object, ajc=NULL, psg_list=NULL)
```

Author(s)

Carsten Kuhl, <ckuhl@ipb-halle.de>

See Also

[calcPC](#) [groupCorr](#) [xsAnnotate-class](#) [label.propagation.community](#)

cleanParallel	<i>Cleans up with spawned slave processes after use</i>
---------------	---

Description

The spawned slaves processes, which are created within the parallel mode, are closed explicit.

Usage

```
cleanParallel(object)
```

Arguments

object	xsAnnotate object
--------	-------------------

Details

The function needs a `xsAnnotate` object after `groupCorr` or `groupFWHM`. The resulting object is a artificial `xcmsSet`, where the peaks with the specific neutral loss are stored in `xcmsSet@peaks`.

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```
## Not run:  library(CAMERA)
file <- system.file('mzdata/MM14.mzdata', package = "CAMERA")
xs <- xcmsSet(file, method="centWave", ppm=30, peakwidth=c(5,10))
an <- xsAnnotate(xs, polarity="positive", nSlaves=2)
an <- groupFWHM(an)
an <- findAdducts(an)
cleanParallel(an)

## End(Not run)
```

combinexsAnnos	<i>Check CAMERA ion species annotation due to matching with opposite ion mode</i>
----------------	---

Description

This function check annotations of ion species with the help of a sample from opposite ion mode. As first step it searches for pseudospectra from the positive and the negative sample within a retention time window. For every result the m/z differences between both samples are matched against specific rules, which are combinations from pos. and neg. ion species. As example M+H and M-H with a m/z difference of 2.014552. If two ions matches such a difference, the ion annotations are changed (previous annotation is wrong), confirmed or added. Returns the peaklist from one ion mode with recalculated annotations.

Usage

```
combinexsAnnos(xsa.pos, xsa.neg, pos=TRUE, tol=2, ruleset=NULL)
```

Arguments

xsa.pos	xsAnnotate object with positive ion mode
xsa.neg	xsAnnotate object with neagtive ion mode
pos	If TRUE the peaklist from the positive mode is returned, if FALSE the negative
tol	Retention time window in seconds
ruleset	Matrix of matching rules, see example

Details

Both xsAnnotate object should be full processed (grouping and annotation). Without previous annotation the resulting peaklist only includes annotation with matches peaks from both mode according to the rule(s). With ruleset=NULL the function only looks for M+H/M-H pairs. The ruleset is a two column matrix with includes rule indices from the rule table of both xsAnnotate objects. ruleset <- cbind(1,1) would create the M+H/M-H rule, since the first rule of xsa.pos@ruleset and xsa.neg@ruleset is M+H respectively M-H. Only rules with identical charge can be combined!

Value

Returns a (normal) CAMERA peaklist with a additional column neg. Mode or pos. Mode, where matching peaks from the opposite mode are noted.

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```
## Not run:
#Searches for M+H/M-H combinations within a retention time window of 2 seconds
peaklist.pos <- combinexsAnnos(xsa.pos, xsa.neg, tol=2)

## End(Not run)
```

findAdducts-methods *Calculate Adducts and Annotate LC/ESI-MS Spectra*

Description

Annotate adducts (and fragments) for a xsAnnotate object. Returns a xsAnnotate object with annotated pseudospectra.

Usage

```
findAdducts(object, ppm=5, mzabs=0.015, multiplier=3,
polarity=NULL, rules=NULL, max_peaks=100, psg_list=NULL)
```

Arguments

object	the xsAnnotate object
ppm	ppm error for the search
mzabs	allowed variance for the search
multiplier	highest number(n) of allowed clusterion [nM+ion]
polarity	Which polarity mode was used for measuring of the ms sample
rules	personal ruleset or with NULL standard ruleset will be calculated
max_peaks	If run in parralel mode, this number defines how much peaks will be calculated in every thread
psg_list	Vector of pseudospectra indices. The correlation analysis will be only done for those groups

Details

Adducts (and fragments) are annotated for a xsAnnotate object. For every pseudospectra group, generated bei groupFWHM and groupCorr, all possible Adducts are calculated and mapped to the peaks. If at least two adducts match, a possible molecule-mass for the group can be calculated. After the annotation every masshypothese is checked against the charge of the calculated isotopes. It is recommend to call findIsotopes() before the annotation step.

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```
library(CAMERA)
file <- system.file('mzdata/MM14.mzdata', package = "CAMERA")
xs <- xcmsSet(file, method="centWave", ppm=30, peakwidth=c(5,10))
an <- xsAnnotate(xs)
an <- groupFWHM(an)
an <- findIsotopes(an) # optional but recommended.
#an <- groupCorr(an) # optional but very recommended step
an <- findAdducts(an,polarity="positive")
peaklist <- getPeaklist(an) # get the annotated peak list
```

findIsotopes

Deconvolute/Annotate LC/ESI-MS data

Description

Annotate isotope peaks for a xsAnnotate object. Returns a xsAnnotate object with annotated isotopes.

Usage

```
findIsotopes(object, maxcharge=3, maxiso=4, ppm=5, mzabs=0.01, intval=c("maxo","into","intb"), minfrac=0.5)
```

Arguments

object	the xsAnnotate object
maxcharge	max. number of the isotope charge
maxiso	max. number of the isotope peaks
ppm	ppm error for the search
mzabs	allowed variance for the search
intval	choose intensity values for C12/C13 check. Allowed values are into, maxo, intb
minfrac	in case of multiple samples, percentaged value of samples, which have to contain the correct C12/C13 ratio and are not NA
isotopeMatrix	four column m/z-diff and ratio Matrix, for matching isotopic peaks.
filter	Should C12/C13 filter be applied

Details

Isotope peaks are annotated for a `xsAnnotate` object according to given rules (`maxcharge`, `maxiso`). The algorithm benefits from a earlier grouping of the data, with `groupFWHM`. Generates a list of all possible isotopes, which is stored in `object@isotopes`. Those isotope information will be used in the `groupCorr` function. The intensity of the C13 isotope peak is checked against the C12 of proper ratio. In the case of multiple sample, all samples will be tested. `Minfrac` describe the minimal percentage of samples, which must passed the test. If peaks are NA, then this sample is skipped and the ratio is (found correct C12/C13 ratio) / (samples containing C12 and C13 peak).

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```
library(CAMERA)
file <- system.file('mzdata/MM14.mzdata', package = "CAMERA")
xs <- xcmsSet(file, method="centWave", ppm=30, peakwidth=c(5,10))
an <- xsAnnotate(xs)
an <- groupFWHM(an)
an <- findIsotopes(an)
```

findKendrickMasses *Find specific mass defects using Kendrick mass scales*

Description

Todo

Usage

```
findKendrickMasses(object, masses=c(14, 14.01565),
maxHomologue=4, error=0.002, time=60, intval="maxo",
plot=FALSE)
```

Arguments

<code>object</code>	<code>xsAnnotate</code> object
<code>masses</code>	nominal mass and exact mass
<code>error</code>	allowed mass difference in Da for matching Kendrick mass defect
<code>maxHomologue</code>	max number of homologue
<code>time</code>	allowed retention time difference between homologues
<code>intval</code>	intensity value (allowed values: <code>maxo</code> , <code>into</code> or <code>intb</code>)
<code>plot</code>	plot hits

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```
library(CAMERA)
library(faahKO)
xs <- group(faahko)

#With specific selected sample
xsa <- xsAnnotate(xs)
#Screen for substance with CH2 differences
findKendrickMasses(xsa, masses=c(14, 14.01565), plot=TRUE)
```

findNeutralLoss

Find pseudospectra that contains a specific neutral loss

Description

The method searches in every pseudospectra for a distance between two ions matching a provided mass difference. It returns a xcmsSet object containing the matching peaks.

Usage

```
findNeutralLoss(object, mzdiff=NULL, mzabs=0, mzppm=10)
```

Arguments

object	xsAnnotate object
mzdiff	neutral loss in Dalton
mzabs	absolut allowed mass difference
mzppm	relative allowed mass difference

Details

The function needs a xsAnnotate object after groupCorr or groupFWHM. The resulting object is a artificial xcmsSet, where the peaks with the specific neutral loss are stored in xcmsSet@peaks.

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```
library(CAMERA)
file <- system.file('mzdata/MM14.mzdata', package = "CAMERA")
xs <- xcmsSet(file, method="centWave", ppm=30, peakwidth=c(5,10))
an <- xsAnnotate(xs)
an <- groupFWHM(an)
#Searches for Peaks with water loss
xs.pseudo <- findNeutralLoss(an,mzdiff=18.01,mzabs=0.01)
xs.pseudo@peaks #show Hits
```

findNeutralLossSpecs *Find pseudospectra that contains a specific neutral loss*

Description

The method searches in every pseudospectra for a distance between two ions matching a provided mass difference. It returns a boolean vector with the length equals to the number of pseudospectra, where a hit is marked with TRUE.

Usage

```
findNeutralLossSpecs(object, mzdiff=NULL, mzabs=0, mzppm=10)
```

Arguments

object	xsAnnotate object
mzdiff	neutral loss in Dalton
mzabs	absolut allowed mass difference
mzppm	relative allowed mass difference

Details

The function needs a xsAnnotate object after groupCorr or groupFWHM.

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```
library(CAMERA)
file <- system.file('mzdata/MM14.mzdata', package = "CAMERA")
xs <- xcmsSet(file, method="centWave", ppm=30, peakwidth=c(5,10))
an <- xsAnnotate(xs)
an <- groupFWHM(an)
#Searches for Pseudospectra with water loss
hits <- findNeutralLossSpecs(an, mzdiff=18.01, mzabs=0.01)
```

getAllPeakEICs	<i>Generate EIC information from raw data</i>
----------------	---

Description

Generate EIC data out of the raw data, according to the peak peaker information.

Usage

```
getAllPeakEICs(object, index)
```

Arguments

object	The xsAnnotate object
index	Sample index vector, with the same length as the number of peaks. Encoding from with sample the peak should be extracted. If all peaks should be generated from the same sample set index = rep(sample index, peak count)

Details

The function extract from the raw data the EIC curves. Therefore all .netcdf, .mzdata etc. files must be accessible. It returns a list with two item.

Value

A list with items:

EIC	EIC Matrix with rows = number of peaks and columns = maxscans. It contains mostly NA values and only in that part, where a peak had been found, the intensity information.
scantimes	Scantimes of each sample

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

See Also

[xsAnnotate-class](#)

Examples

```
library(CAMERA)
#Multiple sample
library(faahKO)
xs.grp      <- group(faahko)

#create xsAnnotate object
```

```
xsa          <- xsAnnotate(xs.grp)
#generate pseudospectra
xsa.group    <- groupFWHM(xsa)

#calculate correlation
tmp <- getAllPeakEICs(xsa.group, index=rep(1, nrow(xsa.group@groupInfo)))
#extract EIC matrix
EIC.matrix <- tmp$EIC;
```

getIsotopeCluster *Retrieve the annotated isotopes*

Description

Extract all annotated isotope cluster. Returns a list with one element per cluster. A element contains the charge of the molecule and a peakmatrix with mz and intensity value.

Usage

```
getIsotopeCluster(object, number=NULL, value="maxo", sampleIndex=NULL)
```

Arguments

object	xsAnnotate object
number	Set to NULL extract all isotope cluster or to specific chosen ones
value	Which intensity values should be extracted. Allowed values are: maxo, into, intb
sampleIndex	Selection vector with indexes to select from which sample(s) the intensity values should be retrieved. If set to NULL the sample is selected, which has been chosen for the pseudospectra in the grouping step

Details

This method extract the isotope annotation from a xsAnnotate object. The order of the resulting list is the same as the one in the peaklist, see [getPeaklist](#).

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```
#single sample
library(CAMERA)
file <- system.file('mzdata/MM14.mzdata', package = "CAMERA")
xs   <- xcmsSet(file, method="centWave", ppm=30, peakwidth=c(5,10))
an   <- xsAnnotate(xs)
an   <- groupFWHM(an)
```

```

an <- findIsotopes(an)
isolist <- getIsotopeCluster(an)
isolist[[10]] #get IsotopeCluster 10

#multiple sample
library(faahKO)
xs <- group(faahko)
xs <- fillPeaks(xs)
an <- xsAnnotate(xs)
an <- groupFWHM(an)
an <- findIsotopes(an)
isolist <- getIsotopeCluster(an)

#Select from multiple samples

isolist <- getIsotopeCluster(an, sampleIndex=c(1,2,5))

##Interaction with Rdisop
## Not run:
library(Rdisop)
isotopes.decomposed <- lapply(isolist,function(x) {
  decomposeIsotopes(x$peaks[,1],x$peaks[,2],z=x$charge);
}) #decomposed isotope cluster, filter steps are recommended

## End(Not run)

```

getPeaklist

Generate the annotated peaklist

Description

Extract all information from an xsAnnotate object. Returns a peaklist with annotated peaks.

Usage

```
getPeaklist(object, intval="into")
```

Arguments

object	xsAnnotate object
intval	Choose intensity values. Allowed values are into, maxo, intb

Details

This function extract the peaktable from an xsAnnotate object, containing three additional columns (isotopes, adducts, pseudospectrum) with represents the annotation results. For a grouped xcmsSet it returns the grouped peaktable.

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```
library(CAMERA)
file <- system.file('mzdata/MM14.mzdata', package = "CAMERA")
xs <- xcmsSet(file, method="centWave", ppm=30, peakwidth=c(5,10))
an <- xsAnnotate(xs)
an <- groupFWHM(an)
an <- findIsotopes(an)
an <- findAdducts(an,polarity="positive")
peaklist <- getPeaklist(an)
```

getpspectra

Retrieve a peaklist of one or more pseudospectra

Description

Extract group(s) from a xsAnnotate object. Returns a peaklist as matrix with annotated peaks.

Usage

```
getpspectra(object, grp)
```

Arguments

object	xsAnnotate object
grp	index of pseudo-spectra-group

Details

xsAnnotate groups LC/MS Peaklist after there EIC correlation and FWHM. These function extract one or more of these so called "pseudo spectra groups" with include the peaklist with there annotations. The annotation depends on a before called findAdducts() (and findIsotopes()). Important: The indices for the isotopes, are those from the whole peaklist. See getPeaklist().

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```

library(CAMERA)
file <- system.file('mzdata/MM14.mzdata', package = "CAMERA")
xs <- xcmsSet(c(file), method="centWave", ppm=30, peakwidth=c(5,10))
an <- xsAnnotate(xs)
an <- groupFWHM(an)
#For one group
peaklist <- getpspectra(an, 1)
#For two groups
peaklist <- getpspectra(an, c(1,2))

```

groupCorr

EIC correlation grouping of LC/ESI-MS data

Description

Peak grouping after correlation information into pseudospectrum groups for an xsAnnotate object. Return an xsAnnotate object with grouping information.

Usage

```

groupCorr(object, cor_eic_th=0.75, pval=0.05, graphMethod="hcs",
  calcIso = FALSE, calcCiS = TRUE, calcCaS = FALSE, psg_list=NULL, xraw=NULL,
  cor_exp_th=0.75, ...)

```

Arguments

object	The xsAnnotate object
cor_eic_th	Correlation threshold for EIC correlation
pval	p-value threshold for testing correlation of significance
graphMethod	Clustering method for resulting correlation graph. See calcPC for more details.
calcIso	Include isotope detection information for graph clustering
calcCiS	Calculate correlation inside samples
calcCaS	Calculate correlation accross samples
psg_list	Vector of pseudospectra indices. The correlation analysis will be only done for those groups
xraw	Optional xcmsRaw object, which should be used for raw data extraction
cor_exp_th	Threshold for intensity correlations across samples
...	Additional parameter

Details

The algorithm calculates different informations for group peaks into so called pseudospectra. This pseudospectra contains peaks, with have a high correlation between each other. So far three different kind of information are available. Correlation of intensities across samples (need more than 3 samples), EIC correlation between peaks inside a sample and additional the informationen about recognized isotope cluster can be included. After calculation of all these informations, they are combined as edge value into a graph object. A following graph clustering algorithm separate the peaks (nodes in the graph) into the pseudospectra.

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

See Also

[calcCiS](#) [calcCaS](#) [calcPC](#) [xsAnnotate-class](#)

Examples

```
library(CAMERA)
file      <- system.file('mzdata/MM14.mzdata', package = "CAMERA");
xs        <- xcmsSet(file, method="centWave", ppm=30, peakwidth=c(5, 10));
an        <- xsAnnotate(xs);
an.group  <- groupFWHM(an);
an.iso    <- findIsotopes(an.group); #optional step for using isotope information
an.grp.corr <- groupCorr(an.iso, calcIso=TRUE);

#For csv output
# write.csv(file="peaklist_with_isotopes.csv",getPeaklist(an))

#Multiple sample
library(faahKO)
xs.grp    <- group(faahko)

#With selected sample
xsa       <- xsAnnotate(xs.grp, sample=1)
xsa.group <- groupFWHM(xsa)
xsa.iso   <- findIsotopes(xsa.group) #optional step
xsa.grp.corr <- groupCorr(xsa.iso, calcIso=TRUE)

#With automatic selection
xsa.auto  <- xsAnnotate(xs.grp)
xsa.grp   <- groupFWHM(xsa.auto)
xsa.iso   <- findIsotopes(xsa.grp) #optional step
index     <- c(1,4) #Only group one and four will be calculate
#We use also correlation across sample
xsa.grp.corr <- groupCorr(xsa.iso, psg_list=index, calcIso=TRUE, calcCaS=TRUE)
#Note: Group 1 and 4 have no subgroups
```

groupDen

Density-Grouping of LC/ESI-MS data

Description

Group peaks of a `xsAnnotate` object according to peak distributions in chromatographic time into pseudospectra-groups. Works analogous as the `group.density` method of `xcms`. Returns `xsAnnotate` object with pseudospectra informations.

Usage

```
groupDen(object, bw = 5 , ...)
```

Arguments

<code>object</code>	the <code>xsAnnotate</code> object
<code>bw</code>	bandwidth (standard deviation or half width at half maximum) of gaussian smoothing kernel to apply to the peak density chromatogram
<code>...</code>	Further Arguments, NYI

Details

The grouping strongly depends on the `bw` parameter. For an UPLC a good starting point is smaller or around 1.

Value

Returns a grouped `xsAnnotate` object.

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```
library(CAMERA)
#Single sample
file <- system.file('mzdata/MM14.mzdata', package = "CAMERA")
xs  <- xcmsSet(file, method="centWave", ppm=30, peakwidth=c(5,10))
xsa <- xsAnnotate(xs)
xsa.grp <- groupDen(xsa, bw=0.5)

#Multiple sample
library(faahKO)
xs  <- group(faahko)

#With specific selected sample
xsa <- xsAnnotate(xs, sample=1)
```



```
xsa.grp <- groupDen(xsa)

#With automatic selection
xsa.auto <- xsAnnotate(xs)
xsa.grp.auto <- groupDen(xsa.auto)
```

groupFWHM

FWHM-Grouping of LC/ESI-MS data

Description

Group peaks of a `xsAnnotate` object according to their retention time into pseudospectra-groups. Uses the peak FWHMs as grouping borders. Returns `xsAnnotate` object with pseudospectra information.

Usage

```
groupFWHM(object, sigma = 6 , perfwhm = 0.6, intval = "maxo")
```

Arguments

<code>object</code>	the <code>xsAnnotate</code> object
<code>sigma</code>	the multiplier of the standard deviation
<code>perfwhm</code>	percentage of the width of the FWHM
<code>intval</code>	intensity values for ordering. Allowed values are <code>into</code> , <code>maxo</code> , <code>intb</code>

Details

Every peak who eluate at the same time-point as a selected peak, will be part of the group. Same time-point is defined about the $Rt_{med} \pm FWHM * perfwhm$. For a single sample `xcmsSet` the selection of peaks starts at the most abundant and goes down to the smaller ones. With a multiple sample set the automatic selection uses the most abundant peak as an representative for every feature group, according to the `xcms` grouping. With the `xsAnnotate` sample parameter a sample selection can be defined to use only specific samples. See [xsAnnotate-class](#) for further information. The FWHM (full width at half maximum) of a peak is estimated as $FWHM = SD * 2.35$. For the calculation of the SD, the peak is assumed as normal distributed.

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```

library(CAMERA)
#Single sample
file <- system.file('mzdata/MM14.mzdata', package = "CAMERA")
xs <- xcmsSet(file, method="centWave", ppm=30, peakwidth=c(5,10))
an <- xsAnnotate(xs)
an <- groupFWHM(an)

#Multiple sample
library(faahKO)
xs <- group(faahko)

#With specific selected sample
xs.anno <- xsAnnotate(xs, sample=1)
xs.group <- groupFWHM(xs.anno)

#With automatic selection
xs.anno.auto <- xsAnnotate(xs)
xs.group.auto <- groupFWHM(xs.anno.auto)

```

mm14

*Extract of marker mixture 14 LC/MS data***Description**

xcmsSet object containing quantitated LC/MS peaks from a marker mixture. The data is a centroided subset from 117-650 m/z and 271-302 seconds with 134 peaks. Positive ionization mode data in mzData file format.

Usage

```
data(mm14)
```

Format

The format is:

```

Formal class 'xcmsSet' [package "xcms"] with 8 slots
  @ peaks      : num [1:83, 1:11] 117 117 118 119 136
  .. ..- attr(*, "dimnames")=List of 2
  .. .. ..$ : NULL
  .. .. ..$ : chr [1:11] "mz" "mzmin" "mzmax" "rt"
  ..@ groups   : logi[0 , 0 ]
  ..@ groupidx : list()
  ..@ phenoData:'data.frame': 1 obs. of 1 variable:
  .. ..$ class: Factor w/ 1 level "mzdata": 1
  ..@ rt       :List of 2
  .. ..$ raw    :List of 1

```

```

.. .. ..$ : num [1:112] 270 271 271 271 272 ...
.. ..$ corrected:List of 1
.. .. ..$ : num [1:112] 270 271 271 271 272 ...
..@ filepaths: chr "mzdata/MM14.mzdata"
..@ profinfo :List of 2
.. ..$ method: chr "bin"
.. ..$ step : num 0.1
..@ polarity : chr(0)

```

Details

The corresponding raw mzData files are located in the mzData subdirectory of this package.

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Source

<http://doi:10.1186/1471-2105-9-504>

References

Data originally reported in "Highly sensitive feature detection for high resolution LC/MS" BMC Bioinformatics; 2008; 9:504.

plotEICs-methods *Plot extracted ion chromatograms from (multiple) Pseudospectra*

Description

Batch plot a list of extracted ion chromatograms to the current graphics device.

Arguments

object	the xsAnnotate object
xraw	xcmsRaw object underlying the the xsAnnotate
maxlabel	How many m/z labels to print
sleep	seconds to pause between plotting EICs
...	other graphical parameters

Value

None.

Methods

object = "xsAnnotate" plotEICs(object, xraw, pspec=1:length(object@pspectra), maxlabel=0, s

Author(s)

Steffen Neumann, <sneumann@ipb-halle.de>

See Also

[xsAnnotate-class](#), [png](#), [pdf](#), [postscript](#),

plotPsSpectrum-methods

Plot a Pseudospectrum

Description

Plot a pseudospectrum, with the most intense peaks labelled, to the current graphics device.

Usage

```
plotPsSpectrum(object, pspec=1:length(object@pspectra), log=FALSE, value="into", maxlabel=0, title=
```

Arguments

object	the xsAnnotate object
pspec	ID of the pseudospectrum to print
log	Boolean, whether the log(intensity) should be shown
value	Which of a peak's intensities should be used
maxlabel	How many m/z labels to print
title	Main title of the Plot
mzrange	Which m/z range should plotted
sleep	Time (in seconds) to wait between successive Spectra, if multiple pspec are requested.
cexMulti	Cex multiplier for peak labels
...	Additional parameter for function plot

Value

None.

Methods

signature(object = "xsAnnotate") object deriving from class "xsAnnotate"

Author(s)

Steffen Neumann, <sneumann@ipb-halle.de>

See Also

[xsAnnotate-class](#), [png](#), [pdf](#), [postscript](#),

psDist-methods *Distance methods for xsAnnotate*

Description

The package xcms contains several methods for calculating a distance between two sets of peaks. the CAMERA method psDist is the generic wrapper to use these methods for processing two pseudospectra from two different xsAnnotate objects.

Arguments

object1	a xsAnnotate object with pseudospectra
object2	a xsAnnotate object with pseudospectra
PSpec1	index of pseudospectrum in object1
PSpec2	index of pseudospectrum in object2
method	method to use for distance calculation. See details.
...	mzabs, mzppm and parameters for the distance function.

Details

Different algorithms can be used by specifying them with the method argument. For example to use the "meanMZmatch" approach one would use: specDist(object1, object2, pspectrum1, pspectrum2, method="meanMZmatch"). This is also the default.

Further arguments given by ... are passed through to the function implementing the method.

A character vector of *nicknames* for all the algorithms which are available is returned by getOption("BioC")\$xcms\$specDist. If the nickname of a method is called "meanMZmatch", the help page for that specific method can be accessed with ?specDist.meanMZmatch.

Value

mzabs	maximum absolute deviation for two matching peaks
mzppm	relative deviations in ppm for two matching peaks
symmetric	use symmetric pairwise m/z-matches only, or each match

Methods

object1 = "xsAnnotate" specDist(object1, object2, pspectrum1, pspectrum2, method,...)

Author(s)

Joachim Kutzera, <jkutzer@ipb-halle.de>

pspec2metfrag

Export the putative fragments as MetFrag query files

Description

MetFrag is an in-silico metabolite identification system, which aims to putatively identify compounds from fragmentation MS data, especially from tandem-MS, but also in-source fragments might give additional hints on top of the accurate mass of the precursor alone.

Usage

```
pspec2metfrag(object, pspecidx=NULL, filedir=NULL)
pspec2metfusion(object, pspecidx=NULL, filedir=NULL)
```

Arguments

object	an xsAnnotate object
pspecidx	Index of pspectra to export, if NULL then all are exported.
filedir	Directory for placement of batch query files

Details

For each spectrum in pspecidx (or all in the xsAnnotate object), for each [M] mass hypothesis, remove all non-fragment peaks (isotopes, clusters, adducts) and pass them to MetFrag and MetFusion batch query files.

Value

Returns a list

Author(s)

Carsten Kuhl <ckuhl@ipb-halle.de>

Examples

```
library(CAMERA)
file      <- system.file('mzdata/MM14.mzdata', package = "CAMERA");
xs        <- xcmsSet(file, method="centWave", ppm=30, peakwidth=c(5, 10));
an        <- xsAnnotate(xs);
an        <- groupFWHM(an);
an        <- findIsotopes(an); #optional step
an        <- findAdducts(an, polarity="positive")

pspec2metfrag(an, pspecidx=c(1))
```

ruleSet	<i>Class ruleSet</i>
---------	----------------------

Description

The class ruleSet is used to read lists of ions, adducts and neutral losses, and compile the dynamic ruleSet from those. This makes it possible to modify the default rules for certain analytical settings.

Slots

ionlistfile: File of known charged ions, an example is found in CAMERA/lists/ions.csv .
 neutrallossfile: File of known neutral losses, an example is found in CAMERA/lists/neutralloss.csv.
 neutraladditionfile: File of known adducts, an example is found in CAMERA/lists/lists/neutraladdition.csv .
 .
 ionlist: Known charged ions.
 neutralloss: Known neutral losses.
 neutraladdition: Known adducts.
 maxcharge: .
 mol : .
 nion : .
 nnloss : .
 nnadd : .
 nh : .
 polarity : Polarity of the ruleSet.
 rules: data.frame of resulting mass differences, this is the dynamic ruleSet.
 lib.loc Path to local R library

Extends

Class "[Versioned](#)", directly.

Methods

Methods implemented for ruleSet

setDefaultLists signature(object = "ruleSet"): Set filenames for the lists shipped with CAMERA.

readLists signature(object = "ruleSet"): Read and parse the lists from the files.

setDefaultParams signature(object = "ruleSet"): Set the default parameters for rule generation.

setParams signature(object = "ruleSet"): Set the parameters for rule generation.

generateRules signature(object = "ruleSet"): Create the rules in ruleSet@rules .

Author(s)

Steffen Neumann and Carsten Kuhl

Examples

```
r <- new("ruleSet");
r2 <- setDefaultLists(r) ;
r3 <- readLists(r2) ;
r4 <- setDefaultParams(r3) ;
r5 <- generateRules(r4)
dim(r5@rules)
```

`xsAnnotate`*xsAnnotate constructor for an provided xcmsSet object*

Description

This function deals with the construction of an `xsAnnotate` object. It extracts the peaktable from a provided `xcmsSet`, which is used for all further analysis. The `xcmsSet` can be a single sample or multiple sample experiment. Since some functions needs the raw data a selection algorithm must be chosen in the case of a multiple sample. CAMERA includes two different strategies: A defined selection of samples (`sample = indices of samples`) or the default automatic solution (`sample = NA`). The automatic solution chooses the best sample for a specific groups called pseudospectrum, see [groupFWHM](#) and [groupCorr](#). It returns a `xsAnnotate` object, see [xsAnnotate-class](#).

Usage

```
xsAnnotate(xs = NULL, sample=NA, nSlaves = 1, polarity = NULL)
```

Arguments

<code>xs</code>	a <code>xcmsSet</code> object
<code>sample</code>	Indices of the group <code>xcmsSet</code> sample, that are used for the EIC correlation step. For automatic selection don't set a value. For use all samples simply define <code>sample = c(1:n)</code> , with <code>n = number of samples</code> .
<code>nSlaves</code>	For parallel mode set <code>nSlaves</code> higher than 1, but not higher than the number of cpu cores.
<code>polarity</code>	Set polarity mode: "positive" or "negative"

Value

A `xsAnnotate` object.

Author(s)

Carsten Kuhl, <ckuhl@ipb-halle.de>

See Also[xsAnnotate-class](#)**Examples**

```
library(faahKO)
xs <- group(faahko)
xsa <- xsAnnotate(xs, sample=c(1:12))

#With automatic selection
xsa.autoselect <- xsAnnotate(xs)
```

xsAnnotate-class	<i>Class xsAnnotate, a class for annotated peak data</i>
------------------	--

Description

This class transforms a [xcmsSet](#) object with peaks from multiple LC/MS or GC/MS samples into a set of annotation results. It contains searching algorithms for isotopes and adducts, peak grouping algorithms to find connected peak, which originate from the same molecule.

Objects from the Class

Objects can be created with the [xsAnnotate](#) constructor which include the peaktable from a provided [xcmsSet](#). Objects can also be created by calls of the form `new("xsAnnotate", ...)`.

Slots

annoGrp: Assignment of mass hypotheses to correlation groups
annoID: The assignemnt of peaks to the mass difference rule used
derivativeIons: List with annotation result for every peak
formula: Matrix containing putative sum formula (intended for future use)
isoID: Matrix containing IDs and additional of all annotated isotope peaks
groupInfo: (grouped) Peaktable with "into" values
isotopes: List with annotated isotopid results for every peak
polarity: A single string with the polarity mode of the peaks
pspectra: List contains all pseudospectra with there peak IDs
psSamples: List containing information with sample was sample was selecteted as representative (automatic selection)
ruleset: A dataframe describing the mass difference rules used for the annotation
runParallel: Flag if CAMERA runs in serial or parallel mode
sample: Number of the used xcmsSet sample (beforehand sample selection)
xcmsSet: The embedded xcmsSet

Methods

groupFWHM signature(object = "xsAnnotate"): group the peak data after the FWHM of the retention time

groupCorr signature(object = "xsAnnotate"): group the peak data after the correlation of the EICs

findIsotopes signature(object = "xsAnnotate"): search for possible isotopes in the spectra

findAdducts signature(object = "xsAnnotate"): search for possible adducts in the spectra

plotEICs signature(object = "xsAnnotate"): plot EICs of pseudospectra

Note

No notes yet.

Author(s)

Carsten Kuhl, <ckuhl@ipb-halle.de>

See Also

[xsAnnotate](#)

Index

- *Topic **classes**
 - ruleSet, 31
 - xsAnnotate-class, 33
- *Topic **datasets**
 - mm14, 26
- *Topic **file**
 - xsAnnotate, 32
- *Topic **hplot**
 - plotEICs-methods, 27
 - plotPsSpectrum-methods, 28
- *Topic **methods**
 - annotate-methods, 2
 - annotateDiffreport, 4
 - calcCaS-methods, 6
 - calcCiS-methods, 7
 - calcIsotopes-methods, 8
 - calcPC-methods, 9
 - calcPC.hcs, 10
 - calcPC.lpc, 10
 - cleanParallel, 11
 - combinexsAnnos, 12
 - findAdducts-methods, 13
 - findIsotopes, 14
 - findKendrickMasses, 15
 - findNeutralLoss, 16
 - findNeutralLossSpecs, 17
 - getAllPeakEICs, 18
 - getIsotopeCluster, 19
 - getPeaklist, 20
 - getpspectra, 21
 - groupCorr, 22
 - groupDen, 24
 - groupFWHM, 25
 - plotEICs-methods, 27
 - plotPsSpectrum-methods, 28
 - psDist-methods, 29
 - pspec2metfrag, 30
 - annotate, xcmsSet-method (annotate-methods), 2
 - annotate-methods, 2
 - annotateDiffreport, 4
 - annotateDiffreport, xsAnnotate-methods (annotateDiffreport), 4
 - calcCaS, 8, 23
 - calcCaS (calcCaS-methods), 6
 - calcCaS, xsAnnotate-method (calcCaS-methods), 6
 - calcCaS-methods, 6
 - calcCiS, 7, 23
 - calcCiS (calcCiS-methods), 7
 - calcCiS, xsAnnotate-method (calcCiS-methods), 7
 - calcCiS-methods, 7
 - calcIsotopes (calcIsotopes-methods), 8
 - calcIsotopes, xsAnnotate-method (calcIsotopes-methods), 8
 - calcIsotopes-methods, 8
 - calcPC, 7, 8, 10, 11, 22, 23
 - calcPC (calcPC-methods), 9
 - calcPC, calcPC-method (calcPC-methods), 9
 - calcPC, xsAnnotate-method (calcPC-methods), 9
 - calcPC-methods, 9
 - calcPC.hcs, 9, 10
 - calcPC.hcs, xsAnnotate-method (calcPC.hcs), 10
 - calcPC.lpc, 9, 10
 - calcPC.lpc, xsAnnotate-method (calcPC.lpc), 10
 - class:ruleSet (ruleSet), 31
 - cleanParallel, 11
 - combinexsAnnos, 12
 - diffreport, 5
 - findAdducts, 34

findAdducts (findAdducts-methods), 13
findAdducts, xsAnnotate-method
 (findAdducts-methods), 13
findAdducts-methods, 13
findIsotopes, 8, 14, 34
findIsotopes, xsAnnotate-method
 (findIsotopes), 14
findKendrickMasses, 15
findNeutralLoss, 16
findNeutralLossSpecs, 17

generateRules (ruleSet), 31
generateRules, ruleSet-method (ruleSet),
 31
getAllPeakEICs, 7, 8, 18
getAllPeakEICs, xsAnnotate-method
 (getAllPeakEICs), 18
getIsotopeCluster, 19
getPeaklist, 19, 20
getPeaklist, xsAnnotate-method
 (getPeaklist), 20
getpspectra, 21
groupCorr, 7, 8, 10, 11, 22, 32, 34
groupCorr, xsAnnotate-method
 (groupCorr), 22
groupDen, 24
groupDen, xsAnnotate-method (groupDen),
 24
groupFWHM, 9–11, 25, 32, 34
groupFWHM, xsAnnotate-method
 (groupFWHM), 25

highlyConnSG, 10

label.propagation.community, 11

mm14, 26

pdf, 28, 29
plotEICs, 34
plotEICs (plotEICs-methods), 27
plotEICs, xsAnnotate-method
 (plotEICs-methods), 27
plotEICs-methods, 27
plotEICs.xsAnnotate (plotEICs-methods),
 27
plotPsSpectrum
 (plotPsSpectrum-methods), 28
plotPsSpectrum, xsAnnotate-method
 (plotPsSpectrum-methods), 28

plotPsSpectrum-methods, 28
plotPsSpectrum.xsAnnotate
 (plotPsSpectrum-methods), 28
png, 28, 29
postscript, 28, 29
psDist (psDist-methods), 29
psDist, CAMERA-method (psDist-methods),
 29
psDist-methods, 29
pspec2metfrag, 30
pspec2metfusion (pspec2metfrag), 30

readLists (ruleSet), 31
readLists, ruleSet-method (ruleSet), 31
ruleSet, 31
ruleSet-class (ruleSet), 31

setDefaultLists (ruleSet), 31
setDefaultLists, ruleSet-method
 (ruleSet), 31
setDefaultParams (ruleSet), 31
setDefaultParams, ruleSet-method
 (ruleSet), 31
setParams (ruleSet), 31
setParams, ruleSet, numeric, numeric, numeric, numeric, numeric,
 (ruleSet), 31
show, ruleSet-method (ruleSet), 31
show, xsAnnotate-method
 (xsAnnotate-class), 33

Versioned, 31

xcmsSet, 33
xsAnnotate, 32, 33, 34
xsAnnotate-class, 3, 4, 32, 33