

Package ‘scone’

April 12, 2018

Version 1.2.0

Title Single Cell Overview of Normalized Expression data

Description SCONE is an R package for comparing and ranking the performance of different normalization schemes for single-cell RNA-seq and other high-throughput analyses.

Author Michael Cole [aut, cre, cph], Davide Risso [aut, cph]

Maintainer Michael Cole <mbe1oc@gmail.com>

License Artistic-2.0

Depends R (>= 3.4), methods, SummarizedExperiment

Imports graphics, stats, utils, aroma.light, BiocParallel, class, cluster, compositions, diptest, edgeR, fpc, gplots, grDevices, hexbin, limma, matrixStats, mixtools, RColorBrewer, boot, rhdf5, RUVSeq, rARPACK

Suggests BiocStyle, DT, ggplot2, knitr, miniUI, NMF, plotly, reshape2, rmarkdown, scran, scRNAseq, shiny, testthat, visNetwork

VignetteBuilder knitr

LazyLoad yes

biocViews Normalization, Preprocessing, QualityControl, GeneExpression, RNASeq, Software, Transcriptomics, Sequencing, SingleCell, Coverage

BugReports <https://github.com/YosefLab/scone/issues>

RoxygenNote 6.0.1

NeedsCompilation no

R topics documented:

biplot_color	2
biplot_interactive	3
CLR_FN	4
control_genes	4
DESEQ_FN	5
estimate_ziber	6
factor_sample_filter	7
fast_estimate_ziber	8
FQ_FN	10

get_bio	10
get_design	11
get_negconruv	12
get_normalized	13
get_params	15
get_qc	15
get_scores	16
impute_expectation	17
impute_null	18
lm_adjust	18
make_design	19
metric_sample_filter	20
scone	22
SconeExperiment-class	25
sconeReport	27
scone_easybake	28
score_matrix	31
SCRAN_FN	33
select_methods	33
simple_FNR_params	34
SUM_FN	35
TMM_FN	36
UQ_FN	36

Index 38

biplot_color	<i>Function for biplotting with no point labels and with points color-coded according to a quantitative variable. For example: the rank of normalization performance.</i>
--------------	---

Description

This function implements biplot for [prcomp](#) objects.

Usage

```
biplot_color(x, y, rank = TRUE, ties_method = c("max", "min", "first",
"last", "random"), choices = 1:2, expand = 1, ...)
```

Arguments

x	prcomp object.
y	numeric. Quantitative values used to color the points. If rank is FALSE, all values must be positive integers and less than or equal to the length of y.
rank	logical. If TRUE (default) y will be transformed by the rank() function
ties_method	character. ties.method used by the rank() function
choices	numeric. 2 principal components to plot. Default to first two PCs.
expand	numeric. value used to adjust the spread of the arrows relative to the points.
...	arguments passed to plot.

Value

Invisibly returns scaled point coordinates used in plot.

Examples

```
mat <- matrix(rnorm(1000), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")

pc <- prcomp(mat)

biplot_color(pc, rank(pc$x[,1]))
```

biplot_interactive	<i>Interactive biplot</i>
--------------------	---------------------------

Description

This is a wrapper around [biplot_color](#), creating a shiny gadget to allow the user to select specific points in the graph.

Usage

```
biplot_interactive(x, ...)
```

Arguments

x	a SconeExperiment object.
...	passed to biplot_color .

Details

Since this is based on the shiny gadget feature, it will not work in static documents, such as vignettes or markdown / knitr documents. See [biplot_color](#) for more details on the internals.

Value

A [SconeExperiment](#) object representing selected methods.

Examples

```
mat <- matrix(rpois(1000, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
obj <- SconeExperiment(mat)
res <- scone(obj, scaling=list(none=identity,
  uq=UQ_FN, deseq=DESEQ_FN, fq=FQT_FN),
  evaluate=TRUE, k_ruv=0, k_qc=0, eval_kclust=2,
  bpparam = BiocParallel::SerialParam())
## Not run:
biplot_interactive(res)

## End(Not run)
```

CLR_FN	<i>Centered log-ratio (CLR) normalization wrapper function</i>
--------	--

Description

Centered log-ratio (CLR) normalization wrapper function

Usage

```
CLR_FN(ei)
```

Arguments

ei Numerical matrix. (rows = genes, cols = samples).

Details

SCONE scaling wrapper for [clr](#).

Value

CLR normalized matrix.

Examples

```
ei <- matrix(0:20,nrow = 7)
eo <- CLR_FN(ei)
```

control_genes	<i>Data: Positive and Negative Control Genes</i>
---------------	--

Description

Sets of "positive" and "negative" control genes, useful arguments for [scone](#).

Details

These gene sets can be used as negative or positive controls, either for RUV factor normalization or for evaluation and ranking of the normalization workflows.

Gene set datasets are in the form of `data.frame`, with the first column containing the gene symbols and an (optional) second column containing additional information (such as cortical layer or cell cycle phase).

Note that the gene symbols follow the mouse conventions (i.e. capitalized) or the human conventions (i.e. all upper-case), based on the original publication. One can use the [toupper](#), [tolower](#), and [toTitleCase](#) functions to alter symbol conventions.

Mouse gene symbols in `cortical_markers` are transcribed from Figure 3 of Molyneaux et al. (2007): "laminar-specific expression of 66 genes within the neocortex."

Human gene symbols in `housekeeping` are derived from the list of "housekeeping" genes from the cDNA microarray analysis of Eisenberg and Levanon (2003): "[HK genes] belong to the class of genes that are EXPRESSED in all tissues." "... from 47 different human tissues and cell lines."

Human gene symbols in `housekeeping_revised` from Eisenberg and Levanon (2013): "This list provided ... is based on analysis of next-generation sequencing (RNA-seq) data. At least one variant of these genes is expressed in all tissues uniformly... The RefSeq transcript according to which we deemed the gene 'housekeeping' is given." Housekeeping exons satisfy "(i) expression observed in all tissues; (ii) low variance over tissues: standard-deviation $[\log_2(\text{RPKM})] < 1$; and (iii) no exceptional expression in any single tissue; that is, no log-expression value differed from the averaged $\log_2(\text{RPKM})$ by two (fourfold) or more." "We define a housekeeping gene as a gene for which at least one RefSeq transcript has more than half of its exons meeting the previous criteria (thus being housekeeping exons)."

Human gene symbols in `cellcycle_genes` from Macosko et al. (2015) and represent a set of genes marking G1/S, S, G2/M, M, and M/G1 phases.

References

Molyneaux, B.J., Arlotta, P., Menezes, J.R. and Macklis, J.D.. Neuronal subtype specification in the cerebral cortex. *Nature Reviews Neuroscience*, 2007, 8(6):427-437.

Eisenberg E, Levanon EY. Human housekeeping genes are compact. *Trends in Genetics*, 2003, 19(7):362-5.

Eisenberg E, Levanon EY. Human housekeeping genes, revisited. *Trends in Genetics*, 2013, 29(10):569-74.

Macosko, E. Z., et al. Highly parallel genome-wide expression profiling of individual cells using nanoliter droplets. *Cell*, 2015, 161.5:1202-1214.

Examples

```
data(housekeeping)
data(housekeeping_revised)
data(cellcycle_genes)
data(cortical_markers)
```

DESEQ_FN

Relative log-expression (RLE; DESeq) scaling normalization wrapper function

Description

Relative log-expression (RLE; DESeq) scaling normalization wrapper function

Usage

```
DESEQ_FN(ei)
```

Arguments

`ei` Numerical matrix. (rows = genes, cols = samples).

Details

SCONE scaling wrapper for `calcNormFactors`).

Value

RLE normalized matrix.

Examples

```
ei <- matrix(0:20,nrow = 7)
eo <- DESEQ_FN(ei)
```

estimate_ziber

Parameter estimation of zero-inflated bernoulli model

Description

This function implements an expectation-maximization algorithm for a zero-inflated bernoulli model of transcript detection, modeling gene expression state (off of on) as a bernoulli draw on a gene-specific expression rate (Z in $0,1$). Detection conditioned on expression is a logistic function of gene-level features. The bernoulli model is modeled numerically by a logistic model with an intercept.

Usage

```
estimate_ziber(x, fp_tresh = 0, gfeatM = NULL, bulk_model = FALSE,
  pos_controls = NULL, em_tol = 0.01, maxiter = 100, verbose = FALSE)
```

Arguments

<code>x</code>	matrix. An expression data matrix (genes in rows, cells in columns)
<code>fp_tresh</code>	numeric. Threshold for calling a positive detection ($D = 1$). Default 0.
<code>gfeatM</code>	matrix. Numeric gene level determinants of drop-out (genes in rows, features in columns)
<code>bulk_model</code>	logical. Use median log-expression of gene in detected fraction as sole gene-level feature. Default FALSE. Ignored if <code>gfeatM</code> is specified.
<code>pos_controls</code>	logical. TRUE for all genes that are known to be expressed in all cells.
<code>em_tol</code>	numeric. Convergence threshold on log-likelihood.
<code>maxiter</code>	numeric. The maximum number of iterations. Default 100.
<code>verbose</code>	logical. Whether or not to print the value of the likelihood at each iteration.

Value

a list with the following elements:

- W coefficients of sample-specific logistic drop-out model
- Alpha intercept and gene-level parameter matrix
- X intercept
- Beta coefficient of gene-specific logistic expression model
- fnr_character the probability, per gene, of $P(D=0|E=1)$
- p_nodrop 1 - the probability $P(\text{drop}|Y)$, useful as weights in weighted PCA
- expected_state the expected value $E[Z]$ (1 = "on")
- loglik the log-likelihood
- convergence 0 if the algorithm converged and 1 if maxiter was reached

Examples

```
mat <- matrix(rpois(1000, lambda = 3), ncol=10)
mat = mat * matrix(1-rbinom(1000, size = 1, prob = .01), ncol=10)
ziber_out = suppressWarnings(estimate_ziber(mat,
  bulk_model = TRUE,
  pos_controls = 1:10))
```

factor_sample_filter *Factor-based Sample Filtering: Function to filter single-cell RNA-Seq libraries.*

Description

This function returns a sample-filtering report for each cell in the input expression matrix, describing whether it passed filtering by factor-based filtering, using PCA of quality metrics.

Usage

```
factor_sample_filter(expr, qual, gene_filter = NULL, max_exp_pcs = 5,
  qual_select_q_thresh = 0.01, force_metrics = NULL, good_metrics = NULL,
  min_qual_variance = 0.7, zcut = 1, mixture = TRUE, dip_thresh = 0.01,
  plot = FALSE, hist_breaks = 20)
```

Arguments

expr	matrix	The data matrix (genes in rows, cells in columns).
qual	matrix	Quality metric data matrix (cells in rows, metrics in columns).
gene_filter	Logical vector	indexing genes that will be used for PCA. If NULL, all genes are used.
max_exp_pcs	numeric	number of expression PCs used in quality metric selection. Default 5.
qual_select_q_thresh	numeric.	q-value threshold for quality/expression correlation significance tests. Default 0.01

force_metrics	logical. If not NULL, indexes quality metric to be forcefully included in quality PCA.
good_metrics	logical. If not NULL, indexes quality metric that indicate better quality when of higher value.
min_qual_variance	numeric. Minimum proportion of selected quality variance addressed in filtering. Default 0.70
zcut	A numeric value determining threshold Z-score for sd, mad, and mixture sub-criteria. Default 1.
mixture	A logical value determining whether mixture modeling sub-criterion will be applied per primary criterion (quality score). If true, a dip test will be applied to each quality score. If a metric is multimodal, it is fit to a two-component normal mixture model. Samples deviating zcut sd's from optimal mean (in the inferior direction), have failed this sub-criterion.
dip_thresh	A numeric value determining dip test p-value threshold. Default 0.05.
plot	logical. Should a plot be produced?
hist_breaks	hist() breaks argument. Ignored if 'plot=FALSE'.

Details

None

Value

A logical, representing samples passing factor-based filter.

Examples

```
mat <- matrix(rpois(1000, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
qc = as.matrix(cbind(colSums(mat), colSums(mat > 0)))
rownames(qc) = colnames(mat)
colnames(qc) = c("NCOUNTS", "NGENES")
mfilt = factor_sample_filter(expr = mat,
  qc, plot = TRUE, qual_select_q_thresh = 1)
```

fast_estimate_ziber *Fast parameter estimation of zero-inflated bernoulli model*

Description

This function implements Newton's method for solving zero of Expectation-Maximization equation at the limit of parameter convergence: a zero-inflated bernoulli model of transcript detection, modeling gene expression state (off of on) as a bernoulli draw on a gene-specific expression rate (Z in $0,1$). Detection conditioned on expression is a logistic function of gene-level features. The bernoulli model is modeled numerically by a logistic model with an intercept.

Usage

```
fast_estimate_ziber(x, fp_tresh = 0, gfeatM = NULL, bulk_model = FALSE,
  pos_controls = NULL, rate_tol = 0.01, maxiter = 100, verbose = FALSE)
```

Arguments

x	matrix. An expression data matrix (genes in rows, cells in columns)
fp_tresh	numeric. Threshold for calling a positive detection ($D = 1$). Default 0.
gfeatM	matrix. Numeric gene level determinants of drop-out (genes in rows, features in columns)
bulk_model	logical. Use median log-expression of gene in detected fraction as sole gene-level feature. Default FALSE. Ignored if gfeatM is specified.
pos_controls	logical. TRUE for all genes that are known to be expressed in all cells.
rate_tol	numeric. Convergence threshold on expression rates (0-1).
maxiter	numeric. The maximum number of steps per gene. Default 100.
verbose	logical. Whether or not to print the value of the likelihood at each iteration.

Value

a list with the following elements:

- W coefficients of sample-specific logistic drop-out model
- Alpha intercept and gene-level parameter matrix
- X intercept
- Beta coefficient of gene-specific logistic expression model
- fnr_character the probability, per gene, of $P(D=0|E=1)$
- p_nodrop 1 - the probability $P(\text{drop}|Y)$, useful as weights in weighted PCA
- expected_state the expected value $E[Z]$ (1 = "on")
- loglik the log-likelihood
- convergencefor all genes, 0 if the algorithm converged and 1 if maxiter was reached

Examples

```
mat <- matrix(rpois(1000, lambda = 3), ncol=10)
mat = mat * matrix(1-rbinom(1000, size = 1, prob = .01), ncol=10)
ziber_out = suppressWarnings(fast_estimate_ziber(mat,
  bulk_model = TRUE,
  pos_controls = 1:10))
```

FQ_FN	<i>Full-quantile normalization wrapper function</i>
-------	---

Description

Full-quantile normalization wrapper function

Usage

```
FQ_FN(ei)
```

```
FQT_FN(ei)
```

Arguments

ei Numerical matrix. (rows = genes, cols = samples).

Details

SCONE "scaling" wrapper for [normalizeQuantileRank.matrix](#)).

Unlike FQ_FN, FQT_FN handles ties carefully (see [normalizeQuantiles](#) for details).

Value

Full-quantile normalized matrix.

Examples

```
ei <- matrix(0:20,nrow = 7)
eo <- FQ_FN(ei)
```

```
ei <- matrix(0:20,nrow = 7)
eo <- FQT_FN(ei)
```

get_bio	<i>Get Factor of Biological Conditions and Batch</i>
---------	--

Description

Get Factor of Biological Conditions and Batch

Usage

```

get_bio(x)

get_batch(x)

## S4 method for signature 'SconeExperiment'
get_bio(x)

## S4 method for signature 'SconeExperiment'
get_batch(x)

```

Arguments

x an object of class [SconeExperiment](#).

Value

NULL or a factor containing bio or batch covariate.

Examples

```

set.seed(42)
mat <- matrix(rpois(500, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
obj <- SconeExperiment(mat, bio = factor(rep(c(1,2),each = 5)),
                       batch = factor(rep(c(1,2),times = 5)))
bio = get_bio(obj)
batch = get_batch(obj)

```

get_design

Retrieve Design Matrix

Description

Given a `SconeExperiment` object created by a call to `scone`, it will return the design matrix of the selected method.

Usage

```

get_design(x, method)

## S4 method for signature 'SconeExperiment,character'
get_design(x, method)

## S4 method for signature 'SconeExperiment,numeric'
get_design(x, method)

```

Arguments

x	a <code>SconeExperiment</code> object containing the results of <code>scone</code> .
method	character or numeric. Either a string identifying the normalization scheme to be retrieved, or a numeric index with the rank of the normalization method to retrieve (according to <code>scone</code> ranking of normalizations).

Details

The numeric method will always return the design matrix corresponding to row method of the `scone_params` slot. This means that if `scone` was run with `eval=TRUE`, `get_design(x, 1)` will return the top ranked method. If `scone` was run with `eval=FALSE`, `get_design(x, 1)` will return the first normalization in the order saved by `scone`.

Value

The design matrix.

Methods (by class)

- `x = SconeExperiment, method = character`: If `method` is a character, it will return the design matrix corresponding to the normalization scheme specified by the character string. The string must be one of the `row.names` of the slot `scone_params`.
- `x = SconeExperiment, method = numeric`: If `method` is a numeric, it will return the design matrix according to the `scone` ranking.

Examples

```
set.seed(42)
mat <- matrix(rpois(500, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
obj <- SconeExperiment(mat, bio = factor(rep(c(1,2),each = 5)),
  batch = factor(rep(c(1,2),times = 5)))
res <- scone(obj, scaling=list(none=identity, uq=UQ_FN),
  evaluate=TRUE, k_ruv=0, k_qc=0,
  adjust_batch = "yes", adjust_bio = "yes",
  eval_kclust=2, bpparam = BiocParallel::SerialParam())
design_top = get_design(res,1)
```

get_negconruv

Get Negative and Positive Controls

Description

Get Negative and Positive Controls

Usage

```

get_negconruv(x)

get_negconeval(x)

get_poscon(x)

## S4 method for signature 'SconeExperiment'
get_negconruv(x)

## S4 method for signature 'SconeExperiment'
get_negconeval(x)

## S4 method for signature 'SconeExperiment'
get_poscon(x)

```

Arguments

x an object of class `SconeExperiment`.

Value

NULL or a logical vector.

For `get_negconruv` the returned vector indicates which genes are negative controls to be used for RUV.

For `get_negconeval` the returned vector indicates which genes are negative controls to be used for evaluation.

For `get_poscon` the returned vector indicates which genes are positive controls to be used for evaluation.

Examples

```

set.seed(42)
mat <- matrix(rpois(500, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
obj <- SconeExperiment(mat, negcon_ruv = 1:50 %in% 1:10,
                      negcon_eval = 1:50 %in% 11:20,
                      poscon = 1:50 %in% 21:30)
negcon_ruv = get_negconruv(obj)
negcon_eval = get_negconeval(obj)
poscon = get_poscon(obj)

```

get_normalized

Retrieve Normalized Matrix

Description

Given a `SconeExperiment` object created by a call to `scone`, it will return a matrix of normalized counts (in log scale if `log=TRUE`).

Usage

```
get_normalized(x, method, ...)

## S4 method for signature 'SconeExperiment,character'
get_normalized(x, method, log = FALSE)

## S4 method for signature 'SconeExperiment,numeric'
get_normalized(x, method, log = FALSE)
```

Arguments

x	a SconeExperiment object containing the results of scone .
method	character or numeric. Either a string identifying the normalization scheme to be retrieved, or a numeric index with the rank of the normalization method to retrieve (according to scone ranking of normalizations).
...	additional arguments for specific methods.
log	logical. Should the data be returned in log-scale

Details

If [scone](#) was run with `return_norm="in_memory"`, this function simply retrieves the normalized data from the assays slot of object.

If [scone](#) was run with `return_norm="hdf5"`, this function will read the normalized matrix from the specified hdf5 file.

If [scone](#) was run with `return_norm="no"`, this function will compute the normalized matrix on the fly.

The numeric method will always return the normalization corresponding to row method of the `scone_params` slot. This means that if [scone](#) was run with `eval=TRUE`, `get_normalized(x, 1)` will return the top ranked method. If [scone](#) was run with `eval=FALSE`, `get_normalized(x, 1)` will return the first normalization in the order saved by [scone](#).

Value

A matrix of normalized counts in log-scale.

Methods (by class)

- `x = SconeExperiment, method = character`: If method is a character, it will return the normalized matrix corresponding to the normalization scheme specified by the character string. The string must be one of the row.names of the slot `scone_params`.
- `x = SconeExperiment, method = numeric`: If method is a numeric, it will return the normalized matrix according to the [scone](#) ranking.

Examples

```
set.seed(42)
mat <- matrix(rpois(500, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
obj <- SconeExperiment(mat)
res <- scone(obj, scaling=list(none=identity, uq=UQ_FN),
             evaluate=TRUE, k_ruv=0, k_qc=0,
```

```

      eval_kclust=2, bpparam = BiocParallel::SerialParam())
top_norm = get_normalized(res,1)

```

get_params

Extract scone parameters

Description

Extract scone parameters

Usage

```

get_params(x)

## S4 method for signature 'SconeExperiment'
get_params(x)

```

Arguments

x an object of class [SconeExperiment](#).

Value

A data.frame containing workflow parameters for each scone workflow.

Examples

```

set.seed(42)
mat <- matrix(rpois(500, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
obj <- SconeExperiment(mat)
res <- scone(obj, scaling=list(none=identity, uq=UQ_FN),
            run = FALSE, k_ruv=0, k_qc=0, eval_kclust=2)
params = get_params(res)

```

get_qc

Get Quality Control Matrix

Description

Get Quality Control Matrix

Usage

```

get_qc(x)

## S4 method for signature 'SconeExperiment'
get_qc(x)

```

Arguments

x an object of class `SconeExperiment`.

Value

NULL or the quality control (QC) metric matrix.

Examples

```
set.seed(42)
mat <- matrix(rpois(500, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
obj <- SconeExperiment(mat,
  qc = cbind(colSums(mat), colSums(mat > 0)))
qc = get_qc(obj)
```

`get_scores`*Extract scone scores*

Description

Extract scone scores

Usage

```
get_scores(x)
```

```
get_score_ranks(x)
```

```
## S4 method for signature 'SconeExperiment'
get_scores(x)
```

```
## S4 method for signature 'SconeExperiment'
get_score_ranks(x)
```

Arguments

x an object of class `SconeExperiment`.

Value

`get_scores` returns a matrix with all (non-missing) scone scores, ordered by average score rank.

`get_score_ranks` returns a vector of average score ranks.

Examples

```

set.seed(42)
mat <- matrix(rpois(500, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
obj <- SconeExperiment(mat)
res <- scone(obj, scaling=list(none=identity, uq=UQ_FN),
             evaluate=TRUE, k_ruv=0, k_qc=0,
             eval_kclust=2, bpparam = BiocParallel::SerialParam())
scores = get_scores(res)
score_ranks = get_score_ranks(res)

```

impute_expectation	<i>Imputation of zero abundance based on general zero-inflated model</i>
--------------------	--

Description

This function is used to impute the data, weighted by probability of data coming from the zero-inflation part of the distribution.

Usage

```
impute_expectation(expression, impute_args)
```

Arguments

expression	the data matrix (genes in rows, cells in columns)
impute_args	arguments for imputation (see details)

Details

The imputation is carried out with the following formula: $y_{ij}^* = y_{ij} * \Pr(\text{No Drop} | y_{ij}) + \mu_i * \Pr(\text{Drop} | y_{ij})$.

impute_args must contain 2 elements: 1) p_nodrop = posterior probability of data not having resulted from drop-out (genes in rows, cells in columns) 2) mu = expected expression of dropped data (genes in rows, cells in columns)

Value

the imputed expression matrix.

Examples

```

mat <- matrix(rpois(1000, lambda = 3), ncol=10)
mat = mat * matrix(1-rbinom(1000, size = 1, prob = .01), ncol=10)

mu = matrix(rep(3/ppois(0,lambda = 3,lower.tail = FALSE),1000),ncol = 10)

p_false = 1 / ( 1 + ppois(0, lambda = 3, lower.tail = TRUE ) /
              (0.01 * ppois(0, lambda = 3, lower.tail = FALSE) ) )

p_nodrop = matrix(rep(1-p_false,1000),ncol = 10)

```

```

p_nodrop[mat > 0] = 1

impute_args = list()
impute_args = list(mu = mu, p_nodrop = p_nodrop)

imat = impute_expectation(mat, impute_args = impute_args)

```

impute_null	<i>Null or no-op imputation</i>
-------------	---------------------------------

Description

Null or no-op imputation

Usage

```
impute_null(expression, impute_args)
```

Arguments

expression	the data matrix (genes in rows, cells in columns)
impute_args	arguments for imputation (not used)

Value

the imputed expression matrix.

Examples

```

mat <- matrix(rpois(1000, lambda = 5), ncol=10)
imat = impute_null(mat)

```

lm_adjust	<i>Linear Adjustment Normalization</i>
-----------	--

Description

Given a matrix with log expression values and a design matrix, this function fits a linear model and removes the effects of the batch factor as well as of the linear variables encoded in W.

Usage

```
lm_adjust(log_expr, design_mat, batch = NULL, weights = NULL)
```

Arguments

log_expr	matrix. The log gene expression (genes in row, samples in columns).
design_mat	matrix. The design matrix (usually the result of make_design).
batch	factor. A factor with the batch information, identifying batch effect to be removed.
weights	matrix. A matrix of weights.

Details

The function assumes that the columns of the design matrix corresponding to the variable for which expression needs to be adjusted, start with either the word "batch" or the letter "W" (case sensitive). Any other covariate (including the intercept) is kept.

Value

The corrected log gene expression.

Examples

```
set.seed(141)
bio = as.factor(rep(c(1,2),each = 2))
batch = as.factor(rep(c(1,2),2))
design_mat = make_design(bio,batch, W = NULL)

log_expr = matrix(rnorm(20),ncol = 4)
adjusted_log_expr = lm_adjust(log_expr = log_expr,
  design_mat = design_mat,
  batch = batch)
```

make_design

Make a Design Matrix

Description

This function builds a design matrix for the Adjustment Normalization Step, in which covariates are two (possibly nested) categorical factors and one or more continuous variables.

Usage

```
make_design(bio, batch, W, nested = FALSE)
```

Arguments

bio	factor. The biological covariate.
batch	factor. The batch covariate.
W	numeric. Either a vector or matrix containing one or more continuous covariates (e.g. RUVg factors).
nested	logical. Whether or not to consider a nested design (see details).

Details

If nested=TRUE a nested design is used, i.e. the batch variable is assumed to be nested within the bio variable. Here, nested means that each batch is composed of samples from only *one* level of bio, while each level of bio may contain multiple batches.

Value

The design matrix.

Examples

```
bio = as.factor(rep(c(1,2),each = 2))
batch = as.factor(rep(c(1,2),2))
design_mat = make_design(bio,batch, W = NULL)
```

metric_sample_filter *Metric-based Sample Filtering: Function to filter single-cell RNA-Seq libraries.*

Description

This function returns a sample-filtering report for each cell in the input expression matrix, describing which filtering criteria are satisfied.

Usage

```
metric_sample_filter(expr, nreads = colSums(expr), ralign = NULL,
  gene_filter = NULL, pos_controls = NULL, scale. = FALSE, glen = NULL,
  AUC_range = c(0, 15), zcut = 1, mixture = TRUE, dip_thresh = 0.05,
  hard_nreads = 25000, hard_ralign = 15, hard_breadth = 0.2,
  hard_auc = 10, suff_nreads = NULL, suff_ralign = NULL,
  suff_breadth = NULL, suff_auc = NULL, plot = FALSE, hist_breaks = 10,
  ...)
```

Arguments

expr	matrix The data matrix (genes in rows, cells in columns).
nreads	A numeric vector representing number of reads in each library. Default to 'colSums' of 'expr'.
ralign	A numeric vector representing the proportion of reads aligned to the reference genome in each library. If NULL, filtered_ralign will be returned NA.
gene_filter	A logical vector indexing genes that will be used to compute library transcriptome breadth. If NULL, filtered_breadth will be returned NA.
pos_controls	A logical, numeric, or character vector indicating positive control genes that will be used to compute false-negative rate characteristics. If NULL, filtered_fnr will be returned NA.
scale.	logical. Will expression be scaled by total expression for FNR computation? Default = FALSE

glen	Gene lengths for gene-length normalization (normalized data used in FNR computation).
AUC_range	An array of two values, representing range over which FNR AUC will be computed (log(expr_units)). Default c(0,15)
zcut	A numeric value determining threshold Z-score for sd, mad, and mixture sub-criteria. Default 1. If NULL, only hard threshold sub-criteria will be applied.
mixture	A logical value determining whether mixture modeling sub-criterion will be applied per primary criterion (metric). If true, a dip test will be applied to each metric. If a metric is multimodal, it is fit to a two-component normal mixture model. Samples deviating zcut sd's from optimal mean (in the inferior direction), have failed this sub-criterion.
dip_thresh	A numeric value determining dip test p-value threshold. Default 0.05.
hard_nreads	numeric. Hard (lower bound on) nreads threshold. Default 25000.
hard_ralign	numeric. Hard (lower bound on) ralign threshold. Default 15.
hard_breadth	numeric. Hard (lower bound on) breadth threshold. Default 0.2.
hard_auc	numeric. Hard (upper bound on) fnr auc threshold. Default 10.
suff_nreads	numeric. If not null, serves as an overriding upper bound on nreads threshold.
suff_ralign	numeric. If not null, serves as an overriding upper bound on ralign threshold.
suff_breadth	numeric. If not null, serves as an overriding upper bound on breadth threshold.
suff_auc	numeric. If not null, serves as an overriding lower bound on fnr auc threshold.
plot	logical. Should a plot be produced?
hist_breaks	hist() breaks argument. Ignored if 'plot=FALSE'.
...	Arguments to be passed to methods.

Details

For each primary criterion (metric), a sample is evaluated based on 4 sub-criteria: 1) Hard (encoded threshold) 2) Adaptive thresholding via sd's from the mean 3) Adaptive thresholding via mad's from the median 4) Adaptive thresholding via sd's from the mean (after mixture modeling) A sample must pass all sub-criteria to pass the primary criterion.

Value

A list with the following elements:

- filtered_nreads Logical. Sample has too few reads.
- filtered_ralign Logical. Sample has too few reads aligned.
- filtered_breadth Logical. Samples has too few genes detected (low breadth).
- filtered_fnr Logical. Sample has a high FNR AUC.

Examples

```
mat <- matrix(rpois(1000, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
qc = as.matrix(cbind(colSums(mat), colSums(mat > 0)))
rownames(qc) = colnames(mat)
colnames(qc) = c("NCOUNTS", "NGENES")
mfilt = metric_sample_filter(expr = mat, nreads = qc[, "NCOUNTS"],
  plot = TRUE, hard_nreads = 0)
```

Description

This function applies and evaluates a variety of normalization schemes with respect to a specified `SconeExperiment` containing scRNA-Seq data. Each normalization consists of three main steps:

- **Impute:** Replace observations of zeroes with expected expression values.
- **Scale:** Match sample-specific expression scales or quantiles.
- **Adjust:** Adjust for sample-level batch factors / unwanted variation.

Following completion of each step, the normalized expression matrix is scored based on SCONE's data-driven evaluation criteria.

Usage

```
scone(x, ...)
```

```
## S4 method for signature 'SconeExperiment'
scone(x, imputation = list(none = impute_null),
      impute_args = NULL, zero = c("none", "preadjust", "postadjust", "strong"),
      scaling, k_ruv = 5, k_qc = 5, adjust_bio = c("no", "yes", "force"),
      adjust_batch = c("no", "yes", "force"), run = TRUE, evaluate = TRUE,
      eval_pcs = 3, eval_proj = NULL, eval_proj_args = NULL,
      eval_kclust = 2:10, verbose = FALSE, stratified_pam = FALSE,
      stratified_cor = FALSE, stratified_rle = FALSE, return_norm = c("no",
      "in_memory", "hdf5"), hdf5file, bpparam = BiocParallel::bpparam())
```

Arguments

<code>x</code>	a <code>SconeExperiment</code> object.
<code>...</code>	see specific S4 methods for additional arguments.
<code>imputation</code>	list or function. (A list of) function(s) to be used for imputation. By default only <code>scone::impute_null</code> is included.
<code>impute_args</code>	arguments passed to all imputation functions.
<code>zero</code>	character. Zero-handling option, see Details.
<code>scaling</code>	list or function. (A list of) function(s) to be used for scaling normalization step.
<code>k_ruv</code>	numeric. The maximum number of factors of unwanted variation. Adjustment step models will include a range of 1 to <code>k_ruv</code> factors of unwanted variation. If 0, RUV adjustment will not be performed.
<code>k_qc</code>	numeric. The maximum number of quality metric PCs. Adjustment step models will include a range of 1 to <code>k_qc</code> quality metric PCs. If 0, QC factor adjustment will not be performed.
<code>adjust_bio</code>	character. If 'no', bio will not be included in Adjustment step models; if 'yes', both models with and without 'bio' will be run; if 'force', only models with 'bio' will be run.

adjust_batch	character. If 'no', batch will not be included in Adjustment step models; if 'yes', both models with and without 'batch' will be run; if 'force', only models with 'batch' will be run.
run	logical. If FALSE the normalization and evaluation are not run, but normalization parameters are returned in the output object for inspection by the user.
evaluate	logical. If FALSE the normalization methods will not be evaluated.
eval_pcs	numeric. The number of principal components to use for evaluation. Ignored if evaluate=FALSE.
eval_proj	function. Projection function for evaluation (see score_matrix for details). If NULL, PCA is used for projection.
eval_proj_args	list. List of arguments passed to projection function as eval_proj_args.
eval_kclust	numeric. The number of clusters (> 1) to be used for pam tightness evaluation. If an array of integers, largest average silhouette width (tightness) will be reported. If NULL, tightness will be returned NA.
verbose	logical. If TRUE some messages are printed.
stratified_pam	logical. If TRUE then maximum ASW for PAM_SIL is separately computed for each biological-cross-batch stratum (accepting NAs), and a weighted average is returned as PAM_SIL.
stratified_cor	logical. If TRUE then cor metrics are separately computed for each biological-cross-batch stratum (accepts NAs), and weighted averages are returned for EXP_QC_COR, EXP_UV_COR, & EXP_WV_COR. Default FALSE.
stratified_rle	logical. If TRUE then rle metrics are separately computed for each biological-cross-batch stratum (accepts NAs), and weighted averages are returned for RLE_MED & RLE_IQR. Default FALSE.
return_norm	character. If "no" the normalized values will not be returned with the output object. This will create a much smaller object and may be useful for large datasets and/or when many combinations are compared. If "in_memory" the normalized values will be returned as part of the output. If "hdf5" they will be written on file using the rhdf5 package.
hdf5file	character. If return_norm="hdf5", the name of the file onto which to save the normalized matrices.
bpparam	object of class bpparamClass that specifies the back-end to be used for computations. See bpparam for details.

Details

If run=FALSE only the scone_params slot of the output object is populated with a data.frame, each row corresponding to a set of normalization parameters.

If x has a non-empty scone_params slot, only the subset of normalizations specified in scone_params are performed and evaluated.

The zero arguments supports 3 zero-handling options:

- none: Default. No special zero-handling.
- preadjust: Restore prior zero observations to zero following Impute and Scale steps.
- postadjust: Set prior zero observations and all negative expression values to zero following the Adjust Step.
- strong: Apply both preadjust and postadjust options.

Evaluation metrics are defined in `score_matrix`. Each metric is assigned a +/- signature for conversion to scores: Positive- signature metrics increase with improving performance, including `BIO_SIL`, `PAM_SIL`, and `EXP_WV_COR`. Negative-signature metrics decrease with improving performance, including `BATCH_SIL`, `EXP_QC_COR`, `EXP_UV_COR`, `RLE_MED`, and `RLE_IQR`. Scores are computed so that higher-performing methods are assigned higher scores.

Note that if one wants to include the unnormalized data in the final comparison of normalized matrices, the identity function must be included in the scaling list argument. Analogously, if one wants to include non-imputed data in the comparison, the `scone::impute_null` function must be included.

If `return_norm="hdf5"`, the normalized matrices will be written to the `hdf5file` file. This must be a string specifying (a path to) a new file. If the file already exists, it will return error. In this case, the `SconeExperiment` object will not contain the normalized counts.

If `return_norm="no"` the normalized matrices are computed to compute the scores and then discarded.

In all cases, the normalized matrices can be retrieved via the `get_normalized` function.

Value

A `SconeExperiment` object with the log-scaled normalized data matrix as elements of the assays slot, if `return_norm` is "in_memory", and with the performance metrics and scores.

See Also

`get_normalized`, `get_design`

Examples

```
mat <- matrix(rpois(1000, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
obj <- SconeExperiment(mat)
no_results <- scone(obj, scaling=list(none=identity,
  uq=UQ_FN, deseq=DESEQ_FN),
  run=FALSE, k_ruv=0, k_qc=0, eval_kclust=2)

results <- scone(obj, scaling=list(none=identity,
  uq=UQ_FN, deseq=DESEQ_FN),
  run=TRUE, k_ruv=0, k_qc=0, eval_kclust=2,
  bpparam = BiocParallel::SerialParam())

results_in_memory <- scone(obj, scaling=list(none=identity,
  uq=UQ_FN, deseq=DESEQ_FN),
  k_ruv=0, k_qc=0, eval_kclust=2,
  return_norm = "in_memory",
  bpparam = BiocParallel::SerialParam())
```

SconeExperiment-class *Class SconeExperiment*

Description

Objects of this class store, at minimum, a gene expression matrix and a set of covariates (sample metadata) useful for running `scone`. These include, the quality control (QC) metrics, batch information, and biological classes of interest (if available).

The typical way of creating `SconeExperiment` objects is via a call to the `SconeExperiment` function or to the `scone` function. If the object is a result to a `scone` call, it will contain the results, e.g., the performance metrics, scores, and normalization workflow comparisons. (See Slots for a full list).

This object extends the `SummarizedExperiment` class.

The constructor `SconeExperiment` creates an object of the class `SconeExperiment`.

Usage

```
SconeExperiment(object, ...)
```

```
## S4 method for signature 'SummarizedExperiment'
SconeExperiment(object, which_qc = integer(),
  which_bio = integer(), which_batch = integer(),
  which_negconruv = integer(), which_negconeval = integer(),
  which_poscon = integer(), is_log = FALSE)
```

```
## S4 method for signature 'matrix'
SconeExperiment(object, qc, bio, batch, negcon_ruv = NULL,
  negcon_eval = negcon_ruv, poscon = NULL, is_log = FALSE)
```

Arguments

<code>object</code>	Either a matrix or a <code>SummarizedExperiment</code> containing the raw gene expression.
<code>...</code>	see specific S4 methods for additional arguments.
<code>which_qc</code>	index that specifies which columns of 'colData' correspond to QC measures.
<code>which_bio</code>	index that specifies which column of 'colData' corresponds to 'bio'.
<code>which_batch</code>	index that specifies which column of 'colData' corresponds to 'batch'.
<code>which_negconruv</code>	index that specifies which column of 'rowData' has information on negative controls for RUV.
<code>which_negconeval</code>	index that specifies which column of 'rowData' has information on negative controls for evaluation.
<code>which_poscon</code>	index that specifies which column of 'rowData' has information on positive controls.
<code>is_log</code>	are the expression data in log scale?
<code>qc</code>	numeric matrix with the QC measures.

bio	factor with the biological class of interest.
batch	factor with the batch information.
negcon_ruv	a logical vector indicating which genes to use as negative controls for RUV.
negcon_eval	a logical vector indicating which genes to use as negative controls for evaluation.
poscon	a logical vector indicating which genes to use as positive controls.

Details

The QC matrix, biological class, and batch information are stored as elements of the 'colData' of the object.

The positive and negative control genes are stored as elements of the 'rowData' of the object.

Value

A [SconeExperiment](#) object.

Slots

which_qc	integer. Index of columns of 'colData' that contain the QC metrics.
which_bio	integer. Index of the column of 'colData' that contains the biological classes information (it must be a factor).
which_batch	integer. Index of the column of 'colData' that contains the batch information (it must be a factor).
which_negconruv	integer. Index of the column of 'rowData' that contains a logical vector indicating which genes to use as negative controls to infer the factors of unwanted variation in RUV.
which_negconeval	integer. Index of the column of 'rowData' that contains a logical vector indicating which genes to use as negative controls to evaluate the performance of the normalizations.
which_poscon	integer. Index of the column of 'rowData' that contains a logical vector indicating which genes to use as positive controls to evaluate the performance of the normalizations.
hdf5_pointer	character. A string specifying to which file to write / read the normalized data.
imputation_fn	list of functions used by scone for the imputation step.
scaling_fn	list of functions used by scone for the scaling step.
scone_metrics	matrix. Matrix containing the "raw" performance metrics. See scone for a description of each metric.
scone_scores	matrix. Matrix containing the performance scores (transformed metrics). See scone for a discussion on the difference between scores and metrics.
scone_params	data.frame. A data frame containing the normalization schemes applied to the data and compared.
scone_run	character. Whether scone was run and in which mode ("no", "in_memory", "hdf5").
is_log	logical. Are the expression data in log scale?
nested	logical. Is batch nested within bio? (Automatically set by scone).
rezero	logical. TRUE if scone was run with zero="preadjust" or zero="strong".
fixzero	logical. TRUE if scone was run with zero="postadjust" or zero="strong".
impute_args	list. Arguments passed to all imputation functions.

See Also

[get_normalized](#), [get_params](#), [get_batch](#), [get_bio](#), [get_design](#), [get_negconeval](#), [get_negconruv](#), [get_poscon](#), [get_qc](#), [get_scores](#), and [get_score_ranks](#) to access internal fields, [select_methods](#) for subsetting by method, and [scone](#) for running scone workflows.

Examples

```
set.seed(42)
nrows <- 200
ncols <- 6
counts <- matrix(rpois(nrows * ncols, lambda=10), nrows)
rowdata <- data.frame(poscon=c(rep(TRUE, 10), rep(FALSE, nrows-10)))
coldata <- data.frame(bio=gl(2, 3))
se <- SummarizedExperiment(assays=SimpleList(counts=counts),
                          rowData=rowdata, colData=coldata)

scone1 <- SconeExperiment(assay(se), bio=coldata$bio, poscon=rowdata$poscon)

scone2 <- SconeExperiment(se, which_bio=1L, which_poscon=1L)
```

sconeReport

SCONE Report Browser: Browse Evaluation of Normalization Performance

Description

This function opens a shiny application session for visualizing performance of a variety of normalization schemes.

Usage

```
sconeReport(x, methods, qc, bio = NULL, batch = NULL,
            poscon = character(), negcon = character(), eval_proj = NULL,
            eval_proj_args = NULL)
```

Arguments

x	a SconeExperiment object
methods	character specifying the normalizations to report.
qc	matrix. QC metrics to be used for QC evaluation report. Required.
bio	factor. A biological condition (variation to be preserved). Default NULL.
batch	factor. A known batch variable (variation to be removed). Default NULL.
poscon	character. Genes to be used as positive controls for evaluation. These genes should be expected to change according to the biological phenomenon of interest. Default empty character.
negcon	character. Genes to be used as negative controls for evaluation. These genes should be expected not to change according to the biological phenomenon of interest. Default empty character.

- `eval_proj` function. Projection function for evaluation (see [score_matrix](#) for details). If NULL, PCA is used for projection.
- `eval_proj_args` list. List of args passed to projection function as `eval_proj_args`.

Value

An object that represents the SCONE report app.

Examples

```
set.seed(101)
mat <- matrix(rpois(1000, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
obj <- SconeExperiment(mat)
res <- scone(obj, scaling=list(none=identity, uq=UQ_FN, deseq=DESEQ_FN),
             evaluate=TRUE, k_ruv=0, k_qc=0, eval_kclust=2,
             bpparam = BiocParallel::SerialParam())
qc = as.matrix(cbind(colSums(mat), colSums(mat > 0)))
rownames(qc) = colnames(mat)
colnames(qc) = c("NCOUNTS", "NGENES")
## Not run:
sconeReport(res, rownames(get_params(res)), qc = qc)

## End(Not run)
```

scone_easybake

Wrapper for Running Essential SCONE Modules

Description

Wrapper for Running Essential SCONE Modules

Usage

```
scone_easybake(expr, qc, bio = NULL, batch = NULL, negcon = NULL,
               verbose = c("0", "1", "2"), out_dir = getwd(), seed = 112233,
               filt_cells = TRUE, filt_genes = TRUE, always_keep_genes = NULL,
               fnr_maxiter = 1000, norm_impute = c("yes", "no", "force"),
               norm_scaling = c("none", "sum", "deseq", "tmm", "uq", "fq", "detect"),
               norm_rezero = FALSE, norm_k_max = NULL, norm_qc_expl = 0.5,
               norm_adjust_bio = c("yes", "no", "force"), norm_adjust_batch = c("yes",
               "no", "force"), eval_dim = NULL, eval_expr_expl = 0.1,
               eval_poscon = NULL, eval_negcon = negcon, eval_max_kclust = 10,
               eval_stratified_pam = TRUE, report_num = 13, out_rda = FALSE, ...)
```

Arguments

- `expr` matrix. The expression data matrix (genes in rows, cells in columns).
- `qc` data frame. The quality control (QC) matrix (cells in rows, metrics in columns) to be used for filtering, normalization, and evaluation.

bio	factor. The biological condition to be modeled in the Adjustment Step as variation to be preserved. If <code>adjust_bio="no"</code> , it will not be used for normalization, but only for evaluation.
batch	factor. The known batch variable to be included in the adjustment model as variation to be removed. If <code>adjust_batch="no"</code> , it will not be used for normalization, but only for evaluation.
negcon	character. The genes to be used as negative controls for filtering, normalization, and evaluation. These genes should be expressed uniformly across the biological phenomenon of interest. Default NULL.
verbose	character. Verbosity level: higher level is more verbose. Default "0".
out_dir	character. Output directory. Default <code>getwd()</code> .
seed	numeric. Random seed. Default 112233.
filt_cells	logical. Should cells be filtered? Set to FALSE if low quality cells have already been excluded. If cells are not filtered, then initial gene filtering (the one that is done prior to cell filtering) is disabled as it becomes redundant with the gene filtering that is done after cell filtering. Default TRUE.
filt_genes	logical. Should genes be filtered post-sample filtering? Default TRUE.
always_keep_genes	logical. A character vector of gene names that should never be excluded (e.g., marker genes). Default NULL.
fnr_maxiter	numeric. Maximum number of iterations in EM estimation of expression posteriors. If 0, then FNR estimation is skipped entirely, and as a consequence no imputation will be performed, disregarding the value of the "norm_impute" argument. Default 1000.
norm_impute	character. Should imputation be included in the comparison? If 'force', only imputed normalizations will be run. Default "yes."
norm_scaling	character. Scaling options to be included in the Scaling Step. Default <code>c("none", "sum", "deseq", "tmm", "uq", "fq", "detect")</code> . See details.
norm_rezero	logical. Restore prior zeroes and negative values to zero following normalization. Default FALSE.
norm_k_max	numeric. Max number (<code>norm_k_max</code>) of factors of unwanted variation modeled in the Adjustment Step. Default NULL.
norm_qc_expl	numeric. In automatic selection of <code>norm_k_max</code> , what fraction of variation must be explained by the first <code>norm_k_max</code> PCs of qc? Default 0.5. Ignored if <code>norm_k_max</code> is not NULL.
norm_adjust_bio	character. If 'no' it will not be included in the model; if 'yes', both models with and without 'bio' will be run; if 'force', only models with 'bio' will be run. Default "yes."
norm_adjust_batch	character. If 'no' it will not be modeled in the Adjustment Step; if 'yes', both models with and without 'batch' will be run; if 'force', only models with 'batch' will be run. Default "yes."
eval_dim	numeric. The number of principal components to use for evaluation. Default NULL.
eval_expr_expl	numeric. In automatic selection of <code>eval_dim</code> , what fraction of variation must be explained by the first <code>eval_dim</code> PCs of expr? Default 0.1. Ignored if <code>eval_dim</code> is not NULL.

eval_poscon	character. The genes to be used as positive controls for evaluation. These genes should be expected to change according to the biological phenomenon of interest.
eval_negcon	character. Alternative negative control gene list for evaluation only.
eval_max_kclust	numeric. The max number of clusters (> 1) to be used for pam tightness evaluation. If NULL, tightness will be returned NA.
eval_stratified_pam	logical. If TRUE then maximum ASW for PAM_SIL is separately computed for each biological-cross-batch condition (accepting NAs), and a weighted average is returned as PAM_SIL. Default TRUE.
report_num	numeric. Number of top methods to report. Default 13.
out_rda	logical. If TRUE, sconeResults.Rda file with the object that the scone function returns is saved in the out_dir (may be very large for large datasets, but useful for post-processing) Default FALSE.
...	extra params passed to the metric_sample_filter and scone when they're called by easybake

Details

"ADD DESCRIPTION"

Value

Directory structure "ADD DESCRIPTION"

Examples

```

set.seed(101)
mat <- matrix(rpois(1000, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
obj <- SconeExperiment(mat)
res <- scone(obj, scaling=list(none=identity, uq=UQ_FN, deseq=DESEQ_FN),
             evaluate=TRUE, k_ruv=0, k_qc=0, eval_kclust=2,
             bpparam = BiocParallel::SerialParam())
qc = as.matrix(cbind(colSums(mat), colSums(mat > 0)))
rownames(qc) = colnames(mat)
colnames(qc) = c("NREADS", "RALIGN")
## Not run:
scone_easybake(mat, qc = as.data.frame(qc), verbose = "2",
               norm_adjust_bio= "no",
               norm_adjust_batch= "no", norm_k_max = 0,
               fnr_maxiter = 0, filt_cells=FALSE, filt_genes=FALSE,
               eval_stratified_pam = FALSE,
               out_dir=~ /scone_out")

## End(Not run)

```

score_matrix *SCONE Evaluation: Evaluate an Expression Matrix*

Description

This function evaluates a (normalized) expression matrix using SCONE criteria, producing 8 metrics based on i) Clustering, ii) Correlations and iii) Relative Expression.

Usage

```
score_matrix(expr, eval_pcs = 3, eval_proj = NULL, eval_proj_args = NULL,
             eval_kclust = NULL, bio = NULL, batch = NULL, qc_factors = NULL,
             uv_factors = NULL, wv_factors = NULL, is_log = FALSE,
             stratified_pam = FALSE, stratified_cor = FALSE, stratified_rle = FALSE)
```

Arguments

expr	matrix. The expression data matrix (genes in rows, cells in columns).
eval_pcs	numeric. The number of principal components to use for evaluation (Default 3). Ignored if <code>lis.null(eval_proj)</code> .
eval_proj	function. Projection function for evaluation (see Details). If NULL, PCA is used for projection
eval_proj_args	list. List of arguments passed to projection function as <code>eval_proj_args</code> (see Details).
eval_kclust	numeric. The number of clusters (> 1) to be used for pam tightness (PAM_SIL) evaluation. If an array of integers, largest average silhouette width (tightness) will be reported in PAM_SIL. If NULL, PAM_SIL will be returned NA.
bio	factor. A known biological condition (variation to be preserved), NA is allowed. If NULL, condition ASW, BIO_SIL, will be returned NA.
batch	factor. A known batch variable (variation to be removed), NA is allowed. If NULL, batch ASW, BATCH_SIL, will be returned NA.
qc_factors	Factors of unwanted variation derived from quality metrics. If NULL, qc correlations, EXP_QC_COR, will be returned NA.
uv_factors	Factors of unwanted variation derived from negative control genes (evaluation set). If NULL, uv correlations, EXP_UV_COR, will be returned NA.
wv_factors	Factors of wanted variation derived from positive control genes (evaluation set). If NULL, wv correlations, EXP_WV_COR, will be returned NA.
is_log	logical. If TRUE the expr matrix is already logged and log transformation will not be carried out prior to projection. Default FALSE.
stratified_pam	logical. If TRUE then maximum ASW is separately computed for each biological-cross-batch stratum (accepts NAs), and a weighted average silhouette width is returned as PAM_SIL. Default FALSE.
stratified_cor	logical. If TRUE then cor metrics are separately computed for each biological-cross-batch stratum (accepts NAs), and weighted averages are returned for EXP_QC_COR, EXP_UV_COR, & EXP_WV_COR. Default FALSE.
stratified_rle	logical. If TRUE then rle metrics are separately computed for each biological-cross-batch stratum (accepts NAs), and weighted averages are returned for RLE_MED & RLE_IQR. Default FALSE.

Details

Users may specify their own `eval_proj` function that will be used to compute Clustering and Correlation metrics. This `eval_proj()` function must have 2 input arguments:

- `e` matrix. log-transformed (+ pseudocount) expression data (genes in rows, cells in columns).
- `eval_proj_args` list. additional function arguments, e.g. prior data weights.

and it must output a matrix representation of the original data (cells in rows, factors in columns). The value of `eval_proj_args` is passed to the user-defined function from the `eval_proj_args` argument of the main `score_matrix()` function call.

Value

A list with the following metrics:

- `BIO_SIL` Average silhouette width by biological condition.
- `BATCH_SIL` Average silhouette width by batch condition.
- `PAM_SIL` Maximum average silhouette width from PAM clustering (see `stratified_pam` argument).
- `EXP_QC_COR` Coefficient of determination between expression pcs and quality factors (see `stratified_cor` argument).
- `EXP_UV_COR` Coefficient of determination between expression pcs and negative control gene factors (see `stratified_cor` argument).
- `EXP_WV_COR` Coefficient of determination between expression pcs and positive control gene factors (see `stratified_cor` argument).
- `RLE_MED` The mean squared median Relative Log Expression (RLE) (see `stratified_rle` argument).
- `RLE_IQR` The variance of the inter-quartile range (IQR) of the RLE (see `stratified_rle` argument).

Examples

```
set.seed(141)
bio = as.factor(rep(c(1,2),each = 2))
batch = as.factor(rep(c(1,2),2))
log_expr = matrix(rnorm(20),ncol = 4)

scone_metrics = score_matrix(log_expr,
  bio = bio, batch = batch,
  eval_kclust = 2, is_log = TRUE)
```

SCRAN_FN	<i>Simple deconvolution normalization wrapper</i>
----------	---

Description

Simple deconvolution normalization wrapper

Usage

```
SCRAN_FN(ei)
```

Arguments

`ei` Numerical matrix. (rows = genes, cols = samples).

Details

SCONE scaling wrapper for [computeSumFactors](#)).

Value

scran normalized matrix.

Examples

```
ei <- matrix(0:76,nrow = 7)
eo <- SCRAN_FN(ei)
```

<code>select_methods</code>	<i>Get a subset of normalizations from a SconeExperiment object</i>
-----------------------------	---

Description

This method let a user extract a subset of normalizations. This is useful when the original dataset is large and/or many normalization schemes have been applied.

In such cases, the user may want to run `scone` in mode `return_norm = "no"`, explore the results, and then select the top performing methods for additional exploration.

Usage

```
select_methods(x, methods)

## S4 method for signature 'SconeExperiment,character'
select_methods(x, methods)

## S4 method for signature 'SconeExperiment,numeric'
select_methods(x, methods)
```

Arguments

x	a SconeExperiment object.
methods	either character or numeric specifying the normalizations to select.

Details

The numeric method will always return the normalization corresponding to the methods rows of the scone_params slot. This means that if `scone` was run with `eval=TRUE`, `select_methods(x, 1:3)` will return the top three ranked method. If `scone` was run with `eval=FALSE`, it will return the first three normalization in the order saved by `scone`.

Value

A SconeExperiment object with selected method data.

Methods (by class)

- `x = SconeExperiment, methods = character`: If `methods` is a character, it will return the subset of methods named in `methods` (only perfect match). The string must be a subset of the `row.names` of the slot `scone_params`.
- `x = SconeExperiment, methods = numeric`: If `methods` is a numeric, it will return the subset of methods according to the `scone` ranking.

Examples

```
set.seed(42)
mat <- matrix(rpois(500, lambda = 5), ncol=10)
colnames(mat) <- paste("X", 1:ncol(mat), sep="")
obj <- SconeExperiment(mat)
res <- scone(obj, scaling=list(none=identity, uq=UQ_FN),
             evaluate=TRUE, k_ruv=0, k_qc=0,
             eval_kclust=2, bpparam = BiocParallel::SerialParam())
select_res = select_methods(res,1:2)
```

simple_FNR_params

Fit Simple False-Negative Model

Description

Fits a logistic regression model of false negative observations as a function of expression level, using a set of positive control (ubiquitously expressed) genes

Usage

```
simple_FNR_params(expr, pos_controls, fn_tresh = 0.01)
```

Arguments

expr	matrix A matrix of transcript-proportional units (genes in rows, cells in columns).
pos_controls	A logical, numeric, or character vector indicating control genes that will be used to compute false-negative rate characteristics. User must provide at least 2 control genes.
fn_tresh	Inclusive threshold for negative detection. Default 0.01. fn_tresh must be non-negative.

Details

$\text{logit}(\text{Probability of False Negative}) \sim a + b * (\text{median log-expr})$

Value

A matrix of logistic regression coefficients corresponding to glm fits in each sample (a and b in columns 1 and 2 respectively). If the a & b fit does not converge, b is set to zero and only a is estimated.

Examples

```
mat <- matrix(rpois(1000, lambda = 3), ncol=10)
mat = mat * matrix(1-rbinom(1000, size = 1, prob = .01), ncol=10)
fnr_out = simple_FNR_params(mat, pos_controls = 1:10)
```

SUM_FN

Sum scaling normalization function

Description

Sum scaling normalization function

Usage

```
SUM_FN(ei)
```

Arguments

ei Numerical matrix. (rows = genes, cols = samples).

Details

SCONE scaling by library size or summed expression.

Value

Sum-scaled normalized matrix.

Examples

```
ei <- matrix(0:20, nrow = 7)
eo <- SUM_FN(ei)
```

TMM_FN	<i>Weighted trimmed mean of M-values (TMM) scaling normalization wrapper function</i>
--------	---

Description

Weighted trimmed mean of M-values (TMM) scaling normalization wrapper function

Usage

```
TMM_FN(ei)
```

Arguments

ei Numerical matrix. (rows = genes, cols = samples).

Details

SCONE scaling wrapper for [calcNormFactors](#)).

Value

TMM normalized matrix.

Examples

```
ei <- matrix(0:20,nrow = 7)
eo <- TMM_FN(ei)
```

UQ_FN	<i>Upper-quartile (UQ) scaling normalization wrapper function</i>
-------	---

Description

Upper-quartile (UQ) scaling normalization wrapper function

Usage

```
UQ_FN(ei)
```

Arguments

ei Numerical matrix. (rows = genes, cols = samples).

Details

SCONE scaling wrapper for [calcNormFactors](#)).

Value

UQ normalized matrix.

Examples

```
ei <- matrix(0:20,nrow = 7)  
eo <- UQ_FN(ei)
```

Index

biplot_color, 2, 3
biplot_interactive, 3
bpparam, 23

calcNormFactors, 6, 36
cellcycle_genes (control_genes), 4
clr, 4
CLR_FN, 4
computeSumFactors, 33
control_genes, 4
cortical_markers (control_genes), 4

DESEQ_FN, 5

estimate_ziber, 6

factor_sample_filter, 7
fast_estimate_ziber, 8
FQ_FN, 10
FQT_FN (FQ_FN), 10

get_batch, 27
get_batch (get_bio), 10
get_batch, SconeExperiment-method
 (get_bio), 10
get_bio, 10, 27
get_bio, SconeExperiment-method
 (get_bio), 10
get_design, 11, 24, 27
get_design, SconeExperiment, character-method
 (get_design), 11
get_design, SconeExperiment, numeric-method
 (get_design), 11
get_negconeval, 27
get_negconeval (get_negconruv), 12
get_negconeval, SconeExperiment-method
 (get_negconruv), 12
get_negconruv, 12, 27
get_negconruv, SconeExperiment-method
 (get_negconruv), 12
get_normalized, 13, 24, 27
get_normalized, SconeExperiment, character-method
 (get_normalized), 13
get_normalized, SconeExperiment, numeric-method
 (get_normalized), 13

get_params, 15, 27
get_params, SconeExperiment-method
 (get_params), 15
get_poscon, 27
get_poscon (get_negconruv), 12
get_poscon, SconeExperiment-method
 (get_negconruv), 12
get_qc, 15, 27
get_qc, SconeExperiment-method (get_qc),
 15
get_score_ranks, 27
get_score_ranks (get_scores), 16
get_score_ranks, SconeExperiment-method
 (get_scores), 16
get_scores, 16, 27
get_scores, SconeExperiment-method
 (get_scores), 16

housekeeping (control_genes), 4
housekeeping_revised (control_genes), 4

impute_expectation, 17
impute_null, 18

lm_adjust, 18

make_design, 19
metric_sample_filter, 20

normalizeQuantileRank.matrix, 10
normalizeQuantiles, 10

prcomp, 2

scone, 4, 12, 14, 22, 25–27, 34
scone, SconeExperiment-method (scone), 22
scone_easybake, 28
SconeExperiment, 3, 11–16, 22, 24–26
SconeExperiment
 (SconeExperiment-class), 25
SconeExperiment, matrix-method
 (SconeExperiment-class), 25
SconeExperiment, SummarizedExperiment-method
 (SconeExperiment-class), 25
SconeExperiment-class, 25

sconeReport, [27](#)
score_matrix, [23](#), [24](#), [28](#), [31](#)
SCRAN_FN, [33](#)
select_methods, [27](#), [33](#)
select_methods, SconeExperiment, character-method
 (select_methods), [33](#)
select_methods, SconeExperiment, numeric-method
 (select_methods), [33](#)
simple_FNR_params, [34](#)
SUM_FN, [35](#)
SummarizedExperiment, [25](#)

TMM_FN, [36](#)
tolower, [4](#)
toTitleCase, [4](#)
toupper, [4](#)

UQ_FN, [36](#)